

Plastic Resurfacer Matte Black

SECTION 1 - IDENTIFICATION

1.1 Product Identifier

Product Name : Plastic Resurfacer Matte Black
 Manufacturer Product Number : 15089Z
 Supplier Product Numbers : 15089Z

1.2 Other Means Of Identification

Other Identifiers : Not Available

1.3 Relevant Identified Uses Of The Substance Or Mixture And Uses Advised Against

Recommended Use : Coating used to restore automotive plastics.
 Restrictions On Use : None Identified

1.4 Supplier Details

Company Name
 Address
 Phone Number
 Fax Number
 Email
 Website

Supplier Details

The Easthill Group, Inc./The Eastwood Company
 263 Shoemaker Road, Pottstown, PA 19464 -
 United States
 610-705-5422
 610-323-6268

1.5 24 Hr Emergency Phone Number

Emergency Number : 800-424-9300 (Chem-Trec)

SECTION 2 - HAZARDS IDENTIFICATION

2.1 Classification Of The Substance Or Mixture

Flammable Aerosols, Category 1 : Extremely flammable aerosol
 Gases Under Pressure : Compressed Gas : Contains gas under pressure; may explode if heated
 Serious Eye Damage/Eye Irritation, Category 2 : Causes serious eye irritation
 Carcinogenicity, Category 2 : Suspected of causing cancer
 Specific Target Organ Toxicity — Single Exposure, Category 3, Narcosis : May cause drowsiness or dizziness
 Hazardous To The Aquatic Environment — Acute Hazard, Category 3 : Harmful to aquatic life
 Hazardous To The Aquatic Environment — Chronic Hazard, Category 3 : Harmful to aquatic life with long lasting effects

2.2 Label Elements

Hazard Pictograms :



GHS02



GHS04



GHS07



GHS08

Signal Word :

Danger

Hazard Statements :

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

Part No. 15089Z Aerosol

Print Date: 02/21/2017

Revision Date: 02/21/2017

Version: 4.0 (EN)

Page 2 of 12

Plastic Resurfacer Matte Black

Precautionary Statements

: Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing spray. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves and eye protection. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call physician if you feel unwell. If eye irritation persists: Get medical advice/attention. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Dispose of contents/container to local regulations.

2.3 Other Hazards Which Do Not Result In Classification

2.4 Unknown Acute Toxicity

26.74% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)

37.96% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

46.63% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours))

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Substance

Not Applicable

3.2 Mixture

Ingredient	Cas Number	%	Classification*
Ethyl Acetate	141-78-6	30 - 60	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Propane	74-98-6	10 - 30	Flam. Gas 1, H220 Press. Gas (Diss.), H280
Methyl Acetate	79-20-9	5 - 10	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Stoddard Solvent	8052-41-3	5 - 10	Flam. Liq. 3, H226 Asp. Tox. 1, H304
4-Chlorobenzotrifluoride	98-56-6	1 - 5	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
Methyl Isobutyl Ketone	108-10-1	1 - 5	Flam. Liq. 2, H225 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapour), H332 Eye Irrit. 2A, H319 Carc. 2, H351 STOT SE 3, H335
Carbon Black	1333-86-4	1 - 5	Carc. 2, H351
Ethyl Benzene	100-41-4	0.1 - 1	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SAFETY DATA SHEET

Part No. 15089Z Aerosol

Print Date: 02/21/2017

Revision Date: 02/21/2017

Version: 4.0 (EN)

Page 3 of 12

Plastic Resurfacer Matte Black

SECTION 4 - FIRST-AID MEASURES

4.1 Description Of First-Aid Measures

General Measures	: IF exposed or concerned: Get medical advice/attention.
Eye Contact	: Rinse eyes with water as a precaution.
Skin Contact	: Wash skin with plenty of water.
Ingestion	: Call a poison center or a doctor if you feel unwell.
Inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-Aid Responder Protection	: Wear adequate personal protective equipment based on the nature and severity of the emergency.

4.2 Most Important Symptoms And Effects, Both Acute And Delayed

Eye Contact	: Liquid contact may cause pain along with moderate eye irritation.
Skin Contact	: Prolonged or repeated exposure may cause skin irritation. Repeated contact may cause drying or flaking skin. May cause more severe response if confined to skin.
Ingestion	: Due to being an aerosol, the product does not lend itself to ingestion. Should ingestion occur, it may cause irritation to membranes of the mouth, throat, and gastrointestinal tract resulting in vomiting and/or cramps. Aspiration of vomit into the lungs may cause inflammation, and possible chemical pneumonitis, bronchopneumonia, or pulmonary edema.
Inhalation	: Prolonged or repeated overexposure is anesthetic. May cause irritation of the respiratory tract, or acute nervous system depression characterized by headache, dizziness, staggering gait, confusion or death. Irritation of the mucous membranes, coughing, and dyspnea are also possible.

4.3 Indication Of Immediate Medical Attention And Special Treatment

Notes To Physician	: Treat symptomatically.
Specific Treatments/Antidotes	: No Information Available.
Immediate Medical Attention	: No Information Available.

SECTION 5 - FIRE-FIGHTING MEASURES

5.1 Suitable Extinguishing Media

Extinguishing Media	: Water, carbon dioxide, dry chemical, universal aqueous film forming foam.
Unsuitable Media	: Water jet.

5.2 Specific Hazards Arising From The Chemical Or Mixture

Decomposition Products	: Decomposition products may include: oxides of carbon, smoke, vapors.
Hazards From The Product	: Extremely flammable. Contents under pressure. In a fire or if heated, a pressure increase will occur which may result in container bursting. Vapors heavier than air may spread along the ground and travel to ignition source.

5.3 Special Protective Actions For Fire-Fighters

Protective Actions	: Use water spray to cool fire exposed aerosol containers, as contents can rupture violently from heat developed pressure.
Protective Equipment	: Firemen should wear self-contained breathing apparatus with full face-piece operated in positive pressure mode.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

6.1 Personal Precautions, Protective Equipment And Emergency Procedures

For Non-Emergency Personnel	: No action should be taken involving any personnel without suitable training. Remove ignition sources and provide adequate ventilation only if it is safe to do so. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spill.
For Emergency Responders	: Use personal protection as recommended in Section 8. Observe precautions provided for non-emergency personnel above.

SAFETY DATA SHEET

Part No. 15089ZAerosol

Print Date: 02/21/2017

Revision Date: 02/21/2017

Version: 4.0 (EN)

Page 4 of 12

Plastic Resurfacer Matte Black

6.2 Environmental Precautions

Precautions : Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

6.3 Methods And Materials For Containment And Cleaning Up

Containment Procedures : Product is an aerosol, therefore spills and leaks are unlikely. In case of rupture, released content may be contained with oil/solvent absorbent pads, socks, and/or absorbents.

Cleanup Procedures : Spills from aerosol cans are unlikely and are generally of small volume. Large spills are therefore not normally considered a problem. In case of actual rupture, avoid breathing vapors and ventilate area well. Remove sources of ignition and use non-sparking equipment. Soak up material with inert absorbent and place in safety containers for proper disposal.

Other Information : Aerosol products represent a limited hazard and will not spill or leak unless ruptured. In case of rupture contents are generally evacuated from the can rapidly. Area should be ventilated immediately and continuous ventilation provided until all fumes and vapors have been removed.

Prohibited Materials : Combustible absorbent material such as sawdust. Use of equipment that may cause sparking.

SECTION 7 - HANDLING AND STORAGE

7.1 Precautions For Safe Handling

General Handling Precautions : KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged or repeated skin contact. Avoid breathing of vapors. Do not incinerate (burn) containers. Always replace overcap when not in use. Avoid use around open flames or other sources of ignition. Exposure to heat or prolonged exposure to sun may cause can to burst. Use only with adequate ventilation, opening doors or windows to achieve cross-ventilation.

Hygiene Recommendations : Do not eat, drink or smoke when using this product. Wash hands thoroughly after use. Remove contaminated clothing and protective equipment before entering eating or smoking areas.

7.2 Conditions For Safe Storage Including Any Incompatibilities

Storage Requirements : Storage of individual cans should be done in an area below 55°C (120 °F), and away from heat sources. Ensure can is in a secure place to prevent knocking over and accidental rupture. For storage of pallet quantities, compliance with NFPA 30B (Manufacture and Storage of Aerosol Products) is recommended.

Incompatibilities : Segregate storage away from materials indicated in Section 10.

NFPA 30B Classification : This product is classified as a Level 2 Aerosol per NFPA 30B.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control Parameters

Propane (74-98-6)		
OSHA	OSHA PEL (TWA) (mg/m ³)	1800 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
NIOSH	US IDLH (ppm)	2100 ppm
NIOSH	NIOSH REL (TWA) (mg/m ³)	1800 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm
California	California PEL (TWA) (mg/m ³)	1800 mg/m ³
California	California PEL (TWA) (ppm)	1000 ppm
Ethyl Acetate (141-78-6)		
ACGIH	ACGIH TWA (ppm)	400 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	1400 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	400 ppm
NIOSH	US IDLH (ppm)	2000 ppm
NIOSH	NIOSH REL (TWA) (ppm)	400 ppm
California	California PEL (TWA) (mg/m ³)	1400 mg/m ³
California	California PEL (TWA) (ppm)	400 ppm

SAFETY DATA SHEET

Part No. 15089Z Aerosol

Print Date: 02/21/2017

Revision Date: 02/21/2017

Version: 4.0 (EN)

Page 5 of 12

Plastic Resurfacer Matte Black

Methyl Acetate (79-20-9)

ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (ppm)	250 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	610 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
NIOSH	US IDLH (ppm)	3100 ppm
NIOSH	NIOSH REL (TWA) (mg/m ³)	610 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	200 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	760 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	250 ppm
California	California PEL (TWA) (mg/m ³)	610 mg/m ³
California	California PEL (TWA) (ppm)	200 ppm
California	California PEL (STEL) (mg/m ³)	760 mg/m ³
California	California PEL (STEL) (ppm)	250 ppm

4-Chlorobenzotrifluoride (98-56-6)

Not applicable

Methyl Isobutyl Ketone (108-10-1)

ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	ACGIH STEL (ppm)	75 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	410 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
OSHA	OSHA PEL (STEL) (mg/m ³)	300 mg/m ³
OSHA	OSHA PEL (STEL) (ppm)	75 ppm
NIOSH	NIOSH REL (TWA) (mg/m ³)	205 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	50 ppm
California	California PEL (TWA) (mg/m ³)	205 mg/m ³
California	California PEL (TWA) (ppm)	50 ppm
California	California PEL (STEL) (mg/m ³)	300 mg/m ³
California	California PEL (STEL) (ppm)	75 ppm
BEI	MIBK in urine, End of shift	2 mg/l

Ethyl Benzene (100-41-4)

ACGIH	ACGIH TWA (ppm)	20 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
NIOSH	US IDLH (ppm)	800 ppm
NIOSH	NIOSH REL (TWA) (mg/m ³)	435
NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	545 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	125 ppm
California	California PEL (TWA) (mg/m ³)	22 mg/m ³
California	California PEL (TWA) (ppm)	5 ppm

Carbon Black (1333-86-4)

ACGIH	ACGIH TWA (mg/m ³)	3 mg/m ³
OSHA	OSHA PEL (TWA) (mg/m ³)	3.5 mg/m ³
NIOSH	US IDLH (mg/m ³)	1750 mg/m ³
NIOSH	NIOSH REL (TWA) (mg/m ³)	3.5 mg/m ³
California	California PEL (TWA) (mg/m ³)	3.5 mg/m ³

SAFETY DATA SHEET

Part No. 15089Z Aerosol

Print Date: 02/21/2017

Revision Date: 02/21/2017

Version: 4.0 (EN)

Page 6 of 12

Plastic Resurfacer Matte Black

Stoddard Solvent (8052-41-3)

ACGIH	ACGIH TWA (ppm)	100 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	2900 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	500 ppm
California	California PEL (TWA) (mg/m ³)	525 mg/m ³
California	California PEL (TWA) (ppm)	100 ppm

8.2 Exposure Controls

Engineering Measures	: Use only with adequate ventilation. General ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Local exhaust ventilation or an enclosed handling system may be necessary to control air contamination below that of the lowest OEL from the table above.
Respiratory Protection	: An approved respirator with an organic vapor cartridge may be permissible under certain circumstances where airborne concentrations are expected to exceed occupational exposure limits. If respirators are needed, in the United States compliance with OSHA standard 29 CFR 1910.134 is necessary.
Skin Protection	: For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or repeated contact could occur, use protective clothing impervious to the ingredients listed in Section 2.
Eye/Face Protection	: Safety glasses with side shields are recommended as a minimum for any type of industrial chemical handling. Where eye contact with this material could occur, chemical splash proof goggles are recommended.
Other Protective Equipment	: Safety showers and eye-wash stations should be available in the workplace near where the material will be used.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

9.1 Physical Properties

Boiling Point	> 56.90 °C	Melting / Freezing Point	> -98.00 °C
Flash Point, Liquid	> -10.00 °C	Flash Point, Propellant	-104.40 °C
Explosive Limits	LEL: 0.60 UEL: 16.00 vol %	Autoignition Temperature, Liquid	> 200.00 °C
Flammability	Extremely Flammable Aerosol	Density	0.786 g/cm ³
Molecular Weight	Not Available	Weight	6.559 lbs/gal
Vapor Pressure	Not Available	pH	Not Available
Vapor Density	Not Available	Evaporation Rate (nBAC=1)	Not Available
Viscosity	Not Available	Partition Coefficient	Not Available
Odor Threshold	Not Available	Refractive Index	Not Available
Physical Form	Pressurized Product	Heat Of Combustion	12388.95 BTU/lb
Odor	Paint-like	Water Solubility	Not Available
Appearance / Color	Black	Decomposition Temperature	Not Available

9.2 Environmental Properties

Percent Volatile	89.75 % wt	VOC Regulatory	694.05 g/L (5.79 lbs/gal)
Percent VOC	77.50 % wt	VOC Actual	609.13 g/L (5.08 lbs/gal)
Percent HAP	2.76 % wt	HAP Content	21.69 g/L (0.18 lbs/gal)
Global Warming Potential	0.83 GWP	Maximum Incremental Reactivity	0.7770 g O3/g
Ozone Depletion Potential	0.00 ODP		

SECTION 10 - STABILITY AND REACTIVITY

10.1 Reactivity

Reactivity	: No specific test data related to reactivity is available for this products or its ingredients.
------------	--

SAFETY DATA SHEET

Part No. E15089Z Aerosol

Print Date: 02/21/2017

Revision Date: 02/21/2017

Version: 4.0 (EN)

Page 7 of 12

Plastic Resurfacer Matte Black

10.2 Chemical Stability

Stability : This product is stable.

10.3 Possibility Of Hazardous Reactions

Reactions : Under normal conditions of storage and use, hazardous reactions are not expected to occur.

10.4 Conditions To Avoid

Conditions : Electrostatic Discharge, Other Ignition Sources, Heat, Flames, Sparks.

10.5 Incompatible Materials

Incompatibilities : Strong Oxidizing Agents, Strong Reducing Agents, Strong Acids, Potassium t-Butoxide, Bases, Magnesium.

10.6 Hazardous Decomposition Products

Products : Oxides of carbon, Unstable peroxides, Methanol, Acetic Acid.

SECTION 11 - TOXICOLOGICAL INFORMATION

11.1.1 Information On Toxicological Effects

Propane (74-98-6)

LC50 Inhalation (Rat) 658 mg/l/4h (Lit.)

Ethyl Acetate (141-78-6)

LD50 Oral (Rat) 5620 mg/kg (RTECS)

LD50 Dermal (Rabbit) > 18000 mg/kg (Sigma-Aldrich)

LC50 Inhalation (Rat) 200 g/m³ (RTECS)

Methyl Acetate (79-20-9)

LD50 Oral (Rat) 6970 mg/kg (Lit.)

LD50 Dermal (Rabbit) > 5000 mg/kg (RTECS)

LC50 Inhalation (Rat) 16000 - 32000 (ChemInfo)

4-Chlorobenzotrifluoride (98-56-6)

LD50 Oral (Rat) 13000 mg/kg (Hazardous Substances Data Bank)

LC50 Inhalation (Rat) 33 mg/l/4h (Hazardous Substances Data Bank)

Methyl Isobutyl Ketone (108-10-1)

LD50 Oral (Rat) 2080 mg/kg (RTECS)

LD50 Dermal (Rat) >= 2000 mg/kg bodyweight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)

LD50 Dermal (Rabbit) > 16000 mg/kg (Sigma-Aldrich)

LC50 Inhalation (Rat) 11.6 mg/l/4h (Merck SDS)

LC50 Inhalation (Rat) 2000 - 4000 ppm/4h (ChemInfo)

Ethyl Benzene (100-41-4)

LD50 Oral (Rat) 4720 mg/kg (ChemInfo)

LD50 Dermal (Rabbit) 15380 mg/kg (ChemInfo)

LC50 Inhalation (Rat) 17.2 mg/l/4h (IUCLID)

LC50 Inhalation (Rat) 4000 ppm/4h (ChemInfo)

Carbon Black (1333-86-4)

LD50 Oral (Rat) > 15400 mg/kg (RTECS)

LD50 Dermal (Rabbit) > 3000 mg/kg (RTECS)

LC50 Inhalation (Rat) 27 mg/l/4h (ChemInfo)

Stoddard Solvent (8052-41-3)

LD50 Oral (Rat) > 5000 mg/kg (RTECS)

11.1.2 Health Hazard Classification

Skin Corrosion/Irritation : Not classified

SAFETY DATA SHEET

Part No. 15089Z Aerosol

Print Date: 02/21/2017

Revision Date: 02/21/2017

Version: 4.0 (EN)

Page 8 of 12

Plastic Resurfacer Matte Black

Eye Damage/Irritation	: Causes serious eye irritation.
Respiratory Or Skin Sensitization	: Not classified
Germ Cell Mutagenicity	: Not classified
Reproductive Toxicity	: Not classified
Stot-Single Exposure	: May cause drowsiness or dizziness.
Stot-Repeated Exposure	: Not classified
Aspiration Hazard	: Not classified
Carcinogen Data	: The following ingredients are listed as known or suspected carcinogens:

Methyl Isobutyl Ketone (108-10-1)

IARC group	2B - Possibly carcinogenic to humans
------------	--------------------------------------

Ethyl Benzene (100-41-4)

IARC group	2B - Possibly carcinogenic to humans
ACGIH Category	A3 - Confirmed animal carcinogen with unknown relevance to humans

Carbon Black (1333-86-4)

IARC group	2B - Possibly carcinogenic to humans
ACGIH Category	A3 - Confirmed animal carcinogen with unknown relevance to humans

11.1.3 Information On The Likely Routes Of Exposure

Routes Of Exposure	: Eye Contact, Ingestion, Skin Contact, Inhalation.
--------------------	---

11.1.4 Symptoms Related To The Physical, Chemical And Toxicological Characteristics

Symptoms of Exposure	: Eye Irritation, Nose Irritation, Throat Irritation, Dermatitis, Confusion, Skin Irritation, Headache, Dizziness, Nausea, Narcosis, Drowsiness, Vomiting, Optical Nerve Damage, Cough, Chest Tightness.
----------------------	--

11.1.5 Delayed And Immediate Effects And Also Chronic Effects From Short And Long Term Exposure

Delayed Effects	: No known delayed effects.
Immediate Effects	: No known immediate effects.
Chronic Effects	: No chronic effects identified.
Target Organs	: Central Nervous System, Eyes, Liver, Respiratory System, Skin, Kidneys.
Medical Conditions Aggravated	: None identified.

SECTION 12 - ECOLOGICAL INFORMATION

12.1 Ecotoxicity

Ecology - general	: Harmful to aquatic life with long lasting effects. Harmful to aquatic life.
-------------------	---

Ethyl Acetate (141-78-6)

LC50 fish 1	450 - 600 mg/l Rainbow Trout - 96hr
LC50 fish 2	220 - 250 mg/l Fathead Minnow - 96h
LC50 other aquatic organisms 1	560 mg/l Water Flea - 48hr
EC50 Daphnia 1	2300 - 3090 mg/l Water Flea - 24hr
EC50 other aquatic organisms 1	4300 mg/l Green Algae - 24hr

Methyl Acetate (79-20-9)

LC50 fish 1	250 - 350 mg/l Zebra Fish - 96hr
EC50 Daphnia 1	1026.7 mg/l Water Flea - 48hr

4-Chlorobenzotrifluoride (98-56-6)

LC50 fish 1	5.6 mg/l Bluegill Sunfish - 96h
LC50 fish 2	13.5 mg/l Rainbow Trout - 24hr
EC50 Daphnia 1	3.68 mg/l (EC50; 48 h)

Methyl Isobutyl Ketone (108-10-1)

LC50 fish 1	> 179 mg/l Zebra Fish - 96hr
EC50 Daphnia 1	1550 - 3623 mg/l Water Flea - 24hr
EC50 other aquatic organisms 1	980 - 2000 mg/l Green Algae - 48hr

SAFETY DATA SHEET

Part No. 15089Z Aerosol

Print Date: 02/21/2017

Revision Date: 02/21/2017

Version: 4.0 (EN)

Page 9 of 12

Plastic Resurfacer Matte Black

Ethyl Benzene (100-41-4)

LC50 fish 1	4.2 mg/l Rainbow Trout - 96hr
EC50 Daphnia 1	2.4 mg/l Water Flea - 48hr
EC50 other aquatic organisms 1	9.68 mg/l Bacteria - 30min
EC50 other aquatic organisms 2	4.6 mg/l Green Algae - 72hr

Carbon Black (1333-86-4)

LC50 fish 1	> 1000 mg/l Zebra Fish - 96hr
EC50 Daphnia 1	> 5600 mg/l Water Flea - 24hr
EC50 other aquatic organisms 1	> 10000 mg/l Green Algae - 72hr

Stoddard Solvent (8052-41-3)

LC50 fish 1	Rainbow Trout - 96hr
-------------	----------------------

12.2 Ecological Properties

Propane (74-98-6)

Persistence and degradability	Readily biodegradable in water. Not applicable (gas). Photodegradation in the air.
BCF fish 1	9 - 25 (BCF)
Log Pow	2.28 (Calculated)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

Ethyl Acetate (141-78-6)

Persistence and degradability	Biodegradability 100% / 28 days.
Biochemical oxygen demand (BOD)	0.293 g O ₂ /g substance
Chemical oxygen demand (COD)	1.69 g O ₂ /g substance
ThOD	1.82 g O ₂ /g substance
BCF fish 1	30
Log Pow	0.73
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
Log Koc	0.778

Methyl Acetate (79-20-9)

Persistence and degradability	Biodegradability 70% / 28 days.
Chemical oxygen demand (COD)	1511.8 mg/g
ThOD	1510 mg/g
BCF fish 1	< 1 (BCF)
Log Pow	0.18
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
Log Koc	0.68

4-Chlorobenzotrifluoride (98-56-6)

Persistence and degradability	Biodegradability in water: no data available.
Log Pow	3.6
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

Methyl Isobutyl Ketone (108-10-1)

Persistence and degradability	Biodegradability 79% / 28 days.
Biochemical oxygen demand (BOD)	2.06 g O ₂ /g substance
Chemical oxygen demand (COD)	2.16 g O ₂ /g substance
ThOD	2.72 g O ₂ /g substance
BOD (% of ThOD)	0.76
BCF fish 1	2 - 5 (BCF)
Log Pow	1.9 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
Log Koc	Koc,101.85; Weight of evidence; Calculated value; log Koc; 2.008; Weight of evidence; Calculated value

Ethyl Benzene (100-41-4)

Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.
Biochemical oxygen demand (BOD)	1.44 g O ₂ /g substance (20d.)
Chemical oxygen demand (COD)	2.1 g O ₂ /g substance
ThOD	3.17 g O ₂ /g substance
BOD (% of ThOD)	45.4 (20 days)
BCF fish 1	1 (BCF; Other; 6 weeks; Oncorhynchus kisutch; Flow-through system; Salt water; Literature study)
BCF fish 2	15 - 79 (BCF)
BCF other aquatic organisms 1	4.68 (BCF)
Log Pow	3.15 (Experimental value; 3.6; Experimental value; EU Method A.8: Partition Coefficient; 20 °C)

SAFETY DATA SHEET

Part No. 15089Z Aerosol

Print Date: 02/21/2017

Revision Date: 02/21/2017

Version: 4.0 (EN)

Page 10 of 12

Plastic Resurfacer Matte Black

Ethyl Benzene (100-41-4)

Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
Log Koc	log Koc,PCKOCWIN v1.66; 2.71; Calculated value; Koc; PCKOCWIN v1.66; 517.8; Calculated value

Carbon Black (1333-86-4)

ThOD	Not applicable
Log Pow	1.09
Bioaccumulative potential	Not bioaccumulative.
Ecology - soil	Not toxic to plants. Not toxic to animals.

Stoddard Solvent (8052-41-3)

Log Pow	3.16-7.06
Log Koc	log Koc,2.85-6.74

SECTION 13 - DISPOSAL CONSIDERATIONS

13.1 Waste Treatment Methods

Waste Disposal

: Characteristics and waste stream classification can change with product use and location. It is the responsibility of the user to determine the proper storage, transportation, treatment, and/or disposal methodologies for spent materials and residues at the time of disposition. All waste must be disposed of in compliance with the respective national, federal, state, and/or local regulations.

Waste Disposal Of Packaging

: In the United States, an aerosol container that does not contain a significant amount of liquid would meet the definition of scrap metal (40 CFR 261.1(c)(6)), and would be exempt from RCRA regulation under 40 CFR 261.6(a)(3)(iv) if it is to be recycled. If containers are to be disposed of (not recycled) it must be managed under all applicable RCRA and state regulations.





Landfill Precautions

: Not Available.

Incineration Precautions

: ** DO NOT INCINERATE ** CONTENTS UNDER PRESSURE **.

SECTION 14 - TRANSPORTATION INFORMATION

Transportation Information	Ground Transportation (DOT)	Air Transportation (IATA)	Ocean Transportation (IMDG)
Identification Number	UN1950	UN1950	UN1950
Proper Shipping Name	Aerosols, Limited Quantity	Aerosols, Flammable, Limited Quantity	Aerosols, Limited Quantity
Hazard Class(es)	2.1	2.1	2.1
Packaging Group	None	None	None
Limited Quantity	Yes 	Yes 	Yes 
Marine Pollutant	No	No	No
Hazard Labels		2.1 - Flammable gas 	

SECTION 15 - REGULATORY INFORMATION

15.1 Federal Regulations

Trace Ingredient Disclosure

: The product is using this ingredient at a trace amount. This ingredient is known to the State of California to cause cancer.

Toluene CAS #108-88-3 -- 0.0015%

TSCA Inventory

: All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

SAFETY DATA SHEET

Part No. 15089Z Aerosol

Print Date: 02/21/2017

Revision Date: 02/21/2017

Version: 4.0 (EN)

Page 11 of 12

Plastic Resurfacer Matte Black

SARA 313 Reporting

: Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Methyl Isobutyl Ketone	CAS No 108-10-1	1 - 5%
Xylene	CAS No 1330-20-7	< 1%
Ethyl Benzene	CAS No 100-41-4	< 1%
Chlorobenzene	CAS No 108-90-7	< 1%
Toluene	CAS No 108-88-3	< 1%

Applicable Federal Regulations

: One or more ingredients are regulated by other Federal Regulations.

Ethyl Acetate (141-78-6)	
CERCLA RQ	5000 lb
Methyl Isobutyl Ketone (108-10-1)	
CERCLA RQ	5000 lb
Ethyl Benzene (100-41-4)	
CERCLA RQ	1000 lb
CWA Reportable Quantity	1000 lb
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard, Fire hazard, Immediate (acute) health hazard.

15.2 State Regulations

California Proposition 65

: This product contains chemicals known to the State of California to cause cancer.

Methyl Isobutyl Ketone (108-10-1)	
Cancer	Yes
Developmental Toxicity	Yes
Ethyl Benzene (100-41-4)	
Cancer	Yes
No significant risk level (NSRL)	54
Carbon Black (1333-86-4)	
Cancer	Yes

State Right-to-Know Lists

: The following ingredients appear on one or more state Right-to-Know lists.

Propane (74-98-6)	
U.S. - New Jersey - Right to Know Hazardous Substance List	
Ethyl Acetate (141-78-6)	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) List	
Methyl Acetate (79-20-9)	
U.S. - New Jersey - Right to Know Hazardous Substance List	
Methyl Isobutyl Ketone (108-10-1)	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) List	
Precipitated Silica (112926-00-8)	
U.S. - New Jersey - Right to Know Hazardous Substance List	
Ethyl Benzene (100-41-4)	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) List	
Carbon Black (1333-86-4)	
U.S. - New Jersey - Right to Know Hazardous Substance List	

SAFETY DATA SHEET

Part No. 15089ZAerosol

Print Date: 02/21/2017

Revision Date: 02/21/2017

Version: 4.0 (EN)

Page 12 of 12

Plastic Resurfacer Matte Black

Stoddard Solvent (8052-41-3)

U.S. - New Jersey - Right to Know Hazardous Substance List

SECTION 16 - OTHER INFORMATION

SDS Compliance

: This SDS complies with the below listed regulations only. For SDS that comply with other countries, please contact our Regulatory Department at msds@chem-pak.com.

OSHA Hazard Communication Standard (HCS 2012) 29 CFR 1910.1200

Globally Harmonized System of Classification and Labeling of Chemicals (GHS) Revision 3

Disclaimer Of Liability

: The information contained herein is based upon data provided to us by our suppliers, and reflects our best judgement. However, no warranty of merchantability, fitness for any use, or any other warranty or guarantee is expressed or implied regarding the accuracy of such data, or the results to be obtained from use thereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not assume any responsibility for the results of such application. This information is furnished upon the condition that the persons receiving it shall make their own determinations of the suitability of the material for any particular use. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist.

Full text of H-statements

H Code	H Phrase
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects