

SAFETY DATA SHEET

Part No. 16017ZP (Liquid)

 Print Date: 8/1/2018
 Revision Date: 8/1/2018
 Supersedes Date: 3/22/2016
 Issue Date: 8/31/2004
 Version: 4.0 (EN)-US
 Page: 1/9

Eastwood Heavy-Duty Anti Rust

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1 - IDENTIFICATION

1.1 Product Identifier

Product Name : Eastwood Heavy-Duty Anti Rust
 Supplier Product Numbers : 16017ZP

1.2 Other Means of Identification

Other Identifiers : Not Available

1.3 Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Recommended Use : Coating that protects internal surfaces from rust and corrosion.
 Restrictions on Use : None Identified

1.4 Supplier Details

Supplier Details		
Company Name	:	The Easthill Group, Inc./The Eastwood Company
Address	:	263 Shoemaker Road, Pottstown, PA 19464 - United States
Phone Number	:	800-343-9353
	:	
	:	
Website	:	www.eastwood.com

1.5 24 hr Emergency Phone Number

Emergency Number : 800-424-9300 ChemTrec

SECTION 2 - HAZARDS IDENTIFICATION

2.1 Classification of the Substance or Mixture

Flam. Liq. 2	H225	Physical Hazards	Flammable liquids Category 2
Eye Irrit. 2	H319	Health Hazards	Serious eye damage/eye irritation Category 2
Stot Se 3	H336	Health Hazards	Specific target organ toxicity (single exposure) Category 3
Asp. Tox. 1	H304	Health Hazards	Aspiration hazard Category 1

2.2 Label Elements

Hazard Pictograms



GHS02



GHS07



GHS08

Signal Word

Danger

Hazard Statements

H225 : Highly flammable liquid and vapour
 H304 : May be fatal if swallowed and enters airways
 H319 : Causes serious eye irritation
 H336 : May cause drowsiness or dizziness

Precautionary Statements

P210 : Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P233 : Keep container tightly closed.
 P240 : Ground/Bond container and receiving equipment
 P241 : Use explosion-proof electrical/ventilating/lighting equipment
 P242 : Use only non-sparking tools.
 P243 : Take precautionary measures against static discharge.

SAFETY DATA SHEET

Part No. 160172P (Liquid)

Print Date: 8/1/2018
Revision Date: 8/1/2018
Supersedes Date: 3/22/2016
Issue Date: 8/31/2004
Version: 4.0 (EN)-US
Page: 2/9

Eastwood Heavy-Duty Anti Rust

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- P261 : Avoid breathing vapors.
P264 : Wash hands thoroughly after handling.
P271 : Use only outdoors or in a well-ventilated area.
P280 : Wear protective gloves and eye protection.
P301+P310 : If swallowed: Immediately call POISON CENTER
P303+P361+P353 : If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 : If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 : If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P312 : Call physician if you feel unwell
P331 : Do NOT induce vomiting.
P337+P313 : If eye irritation persists: Get medical advice/attention.
P370+P378 : In case of fire: Use water, CO2, dry chemical, or universal aqueous film forming foam to extinguish.
P403+P233 : Store in a well-ventilated place. Keep container tightly closed.
P235 : Keep cool.
P405 : Store locked up.
P501 : Dispose of contents/container to local regulations

2.3 Other Hazards Which Do Not Result In Classification

Hazards Not Otherwise Classified : None Identified.

2.4 Unknown acute toxicity

This product does not have any ingredients with an unknown acute toxicity.

37.44% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)

77.44% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)

77.44% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Vapours))

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Substance / Mixture

Substance / Mixture : Mixture

3.2 Composition

Substance name	CAS Number	% wt*	Classification
Stoddard Solvent	8052-41-3	30 - 60	Flam. Liq. 3, H226 Asp. Tox. 1, H304
Acetone	67-64-1	10 - 30	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Hydrotreated Heavy Naphthenic Distillate	64742-52-5	1 - 5	Asp. Tox. 1, H304

Full text of hazard classes and H-statements : see section 16

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4 - FIRST-AID MEASURES

4.1 Description of First-Aid Measures

- General Measures** : Call a physician immediately.
Inhalation : Remove person to fresh air and keep comfortable for breathing.
Skin Contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.
Eye Contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion : Do NOT induce vomiting. Call a physician immediately.
First-Aid Responder Protection : Wear adequate personal protective equipment based on the nature and severity of the emergency.

SAFETY DATA SHEET

Part No. 160172P (Liquid)

Print Date: 8/1/2018
Revision Date: 8/1/2018
Supersedes Date: 3/22/2016
Issue Date: 8/31/2004
Version: 4.0 (EN)-US
Page: 3/9

Eastwood Heavy-Duty Anti Rust

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.2 Most Important Symptoms and Effects, Both Acute and Delayed

Symptoms of Exposure	: Eye Irritation, Nose Irritation, Throat Irritation, Dermatitis, Central Nervous System Depression, Confusion, Skin Irritation, Headache, Dizziness, Narcosis, Mucous Membrane.
Delayed Effects	: No known delayed effects.
Immediate Effects	: No known immediate effects.
Chronic Effects	: Because of defatting properties, repeated skin contact can cause skin damage such as chap, dermatitis, inflammation and the formation of eczema.
Target Organs	: Central Nervous System, Eyes, Liver, Reproductive System, Respiratory System, Skin, Kidneys.

4.3 Indication of Immediate Medical Attention and Special Treatment

Notes to Physician	: Treat symptomatically.
Specific Treatments/Antidotes	: No Information Available.
Medical Conditions Aggravated	: May aggravate personnel with pre-existing disorders associated with any of the Target Organs.

SECTION 5 - FIRE-FIGHTING MEASURES

5.1 Suitable Extinguishing Media

Extinguishing Media	: Water, carbon dioxide, dry chemical, universal aqueous film forming foam.
Unsuitable Media	: Water.

5.2 Specific Hazards Arising from the Chemical or Mixture

Hazardous Combustion Products	: Decomposition products may include: oxides of carbon, smoke, vapors. See also Section 10.6.
Specific Hazards During Firefighting	: CONTENTS HIGHLY FLAMMABLE. In a fire or if heated, a pressure increase will occur which may result in container bursting. Vapors heavier than air may spread along the ground and travel to an ignition source.

5.3 Special Protective Actions for Fire-Fighters

Firefighting Instructions	: Use water spray to cool fire exposed containers, as contents can rupture violently from heat developed pressure.
Protection during Firefighting	: Firemen should wear self-contained breathing apparatus with full face-piece operated in positive pressure mode.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

6.1 Personal Precautions, Protective Equipment and Emergency Procedures

For Non-Emergency Personnel	: No action should be taken involving any personnel without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spill. Remove ignition sources and provide adequate ventilation only if it is safe to do so.
For Emergency Personnel	: Use personal protection as recommended in Section 8. Observe precautions provided for non-emergency personnel above.

6.2 Environmental Precautions

Environmental Precautions	: Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.
---------------------------	---

6.3 Methods and Materials for Containment and Cleaning up

Containment Procedures	: Released content may be contained with oil/solvent absorbent pads, booms, and/or absorbents.
Cleanup Procedures	: Remove sources of ignition and use non-sparking equipment. Soak up material with inert absorbent and place in safety containers for proper disposal.
Other Information	: The North American Emergency Response Guidebook or similar resources providing emergency response information for dealing with accidents, spills, leaks, and/or fires involving dangerous goods.
Prohibited Materials	: Combustible absorbent material such as sawdust. Use of equipment that may cause sparking.

SECTION 7 - HANDLING AND STORAGE

SAFETY DATA SHEET

Part No. 160172P (Liquid)

Print Date: 8/1/2018
Revision Date: 8/1/2018
Supersedes Date: 3/22/2016
Issue Date: 8/31/2004
Version: 4.0 (EN)-US
Page: 4/9

Eastwood Heavy-Duty Anti Rust

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

7.1 Precautions for Safe Handling

- General Handling Precautions** : KEEP OUT OF THE REACH OF CHILDREN. When using in spray application, conformance to NFPA 33 Spray Application using Flammable and Combustible Materials is recommended.
- Hygiene Recommendations** : Do not eat, drink or smoke when using this product. Wash hands thoroughly after use. Remove contaminated clothing and protective equipment before entering eating or smoking areas.

7.2 Conditions for Safe Storage Including Any Incompatibilities

- Storage Requirements** : Storage of flammable materials should conform to NFPA 30 Flammable and Combustible Liquid. Keep containers tightly closed and stored in a well-ventilated place. Keep away from sources of ignition.
- Incompatibilities** : Segregate storage away from materials indicated in Section 10.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control Parameters

Stoddard Solvent (8052-41-3)		
ACGIH	ACGIH TWA (mg/m ³)	100 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	2900 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	500 ppm
California	California PEL (TWA) (mg/m ³)	525 mg/m ³
California	California PEL (TWA) (ppm)	100 ppm
Hydrotreated Heavy Naphthenic Distillate (64742-52-5)		
ACGIH	ACGIH TWA (ppm)	5 mg/m ³ Oil Mist
OSHA	OSHA PEL (TWA) (mg/m ³)	10 mg/m ³ Oil Mist
California	California PEL (TWA) (mg/m ³)	5 mg/m ³
Acetone (67-64-1)		
ACGIH	ACGIH TWA (mg/m ³)	250 ppm
ACGIH	ACGIH Ceiling (mg/m ³)	500 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	2400 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
NIOSH	US IDLH (ppm)	2500 ppm
NIOSH	NIOSH REL (TWA) (ppm)	250 ppm
California	California PEL (TWA) (mg/m ³)	1200 mg/m ³
California	California PEL (TWA) (ppm)	500 ppm
California	California PEL (STEL) (mg/m ³)	1780 mg/m ³
California	California PEL (STEL) (ppm)	750 ppm
California	California PEL (Ceiling) (ppm)	3000 ppm
Biological Exposure Index	Acetone in urine, End of shift (Ns)	25 mg/l

8.2 Exposure Controls

- Engineering Measures** : Use only with adequate ventilation. General ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Local exhaust ventilation or an enclosed handling system may be necessary to control air contamination below that of the lowest OEL from the table above.
- Personal Protective Equipment**
- Eye / Face Protection** : Safety glasses with side shields are recommended as a minimum for any type of industrial chemical handling. Where eye contact with this material could occur, chemical splash proof goggles are recommended.
- Hand Protection** : Chemical-resistant gloves, tested according to ASTM F903-17.
- Remarks** : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to the place of work.
- Skin and Body Protection** : For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or repeated contact could occur, use protective clothing impervious to the ingredients listed in Section 2.
- Respiratory Protection** : An approved respirator with an organic vapor cartridge may be permissible under certain circumstances where airborne concentrations are expected to exceed occupational exposure limits.
- Compliance** : If needed, compliance with OSHA standard 29 CFR 1910.134 is necessary.
- Other Protective Equipment** : Safety showers and eye-wash stations should be available in the workplace near where the material will be used.
- Environmental Exposure Controls** : Avoid release to the environment.

SAFETY DATA SHEET

Part No. 160172P (Liquid)

Print Date: 8/1/2018
Revision Date: 8/1/2018
Supersedes Date: 3/22/2016
Issue Date: 8/31/2004
Version: 4.0 (EN)-US
Page: 5/9

Eastwood Heavy-Duty Anti Rust

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

9.1 Physical Properties

Boiling Point	> 55.60 °C	Melting / Freezing Point	> -96.00 °C
Flash Point, Liquid	> -17.20 °C		
Explosive Limits	LEL: 0.80 UEL: 12.80 vol %	Autoignition Temperature, Liquid	229.00 °C
Flammability	Highly Flammable Liquid	Density	0.830 g/cm ³
Molecular Weight	Not Available	Weight	6.926 lbs/gal
Vapor Pressure	Not Available	pH	Not Available
Vapor Density	Not Available	Evaporation Rate (nBac=1)	Not Available
Viscosity	Not Available	Partition Coefficient (Log Pow)	Not Available
Odor Threshold	Not Available	Refractive Index	Not Available
Physical State	Liquid	Heat Of Combustion	Not Available
Appearance / Color	Amber	Water Solubility	Not Available
Odor	Paint-like	Decomposition Temperature	Not Available

9.2 Environmental Properties

Percent Volatile	60.16 % wt	VOC Regulatory	416.56 g/L (3.48 lbs/gal)
Percent VOC	40.16 % wt	VOC Actual	333.36 g/L (2.78 lbs/gal)
Percent HAP	0.00 % wt	HAP Content	0.00 g/L (0.00 lbs/gal)
Global Warming Potential	0.10 GWP	Maximum Incremental Reactivity	0.8190 g O3/g
Ozone Depletion Potential	0.00 ODP		

SECTION 10 - STABILITY AND REACTIVITY

10.1 Reactivity

Reactivity : No specific test data related to reactivity is available for this products or its ingredients.

10.2 Chemical Stability

Chemical Stability : This product is stable.

10.3 Possibility of Hazardous Reactions

Hazardous Reactions : Under normal conditions of storage and use, hazardous reactions are not expected to occur.

10.4 Conditions to Avoid

Conditions to Avoid : Electrostatic Discharge, Other Ignition Sources, Heat, Flames, Sparks.

10.5 Incompatible Materials

Materials to Avoid : Strong Oxidizing Agents, Strong Reducing Agents, Strong Acids, Bases, Hydrogen Peroxide, Chlorosulfuric Acid, Potassium Chlorate.

10.6 Hazardous Decomposition Products

Thermal Decomposition : Oxides of carbon, Aldehydes, Formaldehyde, Methanol, Acetic Acid.

SECTION 11 - TOXICOLOGICAL INFORMATION

11.1 Information on Toxicological Effects

Stoddard Solvent (CAS: 8052-41-3 / EC: 232-489-3)

LD50 Oral (Rat) > 5000 mg/kg (RTECS)

Hydrotreated Heavy Naphthenic Distillate (CAS: 64742-52-5 / EC: 265-156-6)

LD50 Oral (Rat) > 5000 mg/kg (ChemInfo)

LD50 Dermal (Rabbit) > 2000 mg/kg (ChemInfo)

LC50 Inhalation (Rat) 2180 ml/m³

SAFETY DATA SHEET

Part No. 16017ZP (Liquid)

Print Date: 8/1/2018
Revision Date: 8/1/2018
Supersedes Date: 3/22/2016
Issue Date: 8/31/2004
Version: 4.0 (EN)-US
Page: 6/9

Eastwood Heavy-Duty Anti Rust

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acetone (CAS: 67-64-1 / EC: 200-662-2)

LD50 Oral (Rat)	5800 mg/kg (Sigma-Aldrich)
LD50 Dermal (Rabbit)	20000 mg/kg (IUCCLID)
LC50 Inhalation (Rat)	76 mg/l/4h (GESTIS Substance Database)

Routes Of Exposure	: Eye Contact, Ingestion, Skin Contact, Inhalation, Skin Absorption.
Delayed and Immediate Effects and Also Chronic Effects from Short and Long Term Exposure	: See Section 4.2
Skin Corrosion/Irritation	: Not classified
Eye Damage/Irritation	: Causes serious eye irritation.
Respiratory or Skin Sensitization	: Not classified
Germ Cell Mutagenicity	: Not classified
Reproductive Toxicity	: Not classified
STOT-Single Exposure	: May cause drowsiness or dizziness.
STOT-Repeated Exposure	: Not classified
Aspiration Hazard	: May be fatal if swallowed and enters airways.
Carcinogen Data	: None of the ingredients in the product are listed with EU, IARC, or NTP as being suspected or known carcinogen in a concentration greater than 0.1% by weight.

SECTION 12 - ECOLOGICAL INFORMATION

12.1 Ecotoxicity and Ecological Properties

Stoddard Solvent (8052-41-3)

LC50 Fish	Rainbow Trout - 96hr
Log Pow	3.16-7.06
Log Koc	log Koc, 2.85-6.74

Hydrotreated Heavy Naphthenic Distillate (64742-52-5)

LC50 Fish	> 5000 mg/l Rainbow Trout - 96hr
EC50 Daphnia	> 1000 mg/l Water Flea - 48hr
Persistence and Degradability	Biodegradability in water: no data available.
Log Pow	> 6.5
Bioaccumulative Potential	No bioaccumulation data available.

Acetone (67-64-1)

LC50 Fish	5540 mg/l Rainbow Trout - 96hr
LC50 Fish	8300 mg/l Bluegill Sunfish - 96hr
EC50 Daphnia	8800 mg/l Water Flea - 48hr
Persistence and Degradability	Biodegradability 90% / 28 days.
Biochemical Oxygen Demand	1.43 g O ₂ /g substance
Chemical Oxygen Demand	1.92 g O ₂ /g substance
Theoretical Oxygen Demand	2.2 g O ₂ /g substance
BCF Fish	0.69
BCF Other Aquatic Organisms	3
Log Pow	-0.24

SECTION 13 - DISPOSAL CONSIDERATIONS

13.1 Waste Treatment Methods

Waste Disposal	: Product is suitable for burning in an enclosed, controlled burner for fuel value. Hazard characteristics and regulatory waste stream classification can change with product use and location. Accordingly, it is the responsibility of the user to determine the proper storage, transportation, treatment, and/or disposal methodologies for spent materials and residues at the time of disposition. All waste material must be disposed of in compliance with the respective national, federal, state, and/or local regulations.
Waste Disposal Of Packaging	: Consult with your local landfill to determine if empty small containers can be disposed of along with regular trash pickup. For disposal of large containers (typically 10 gallons or larger), or for containers not suitable for landfill, a licensed reconditioner should be used.
Landfill Precautions	: Not Available.

SAFETY DATA SHEET

Part No. 160172P (Liquid)

Print Date: 8/1/2018
Revision Date: 8/1/2018
Supersedes Date: 3/22/2016
Issue Date: 8/31/2004
Version: 4.0 (EN)-US
Page: 7/9

Eastwood Heavy-Duty Anti Rust

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Incineration Precautions : Not Available.

SECTION 14 - TRANSPORTATION INFORMATION

14.1 UN Number	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
UN Number	: UN1993	UN1993	UN1993

14.2 UN Proper Shipping Name	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
UN Proper Shipping Name	: Flammable Liquid, NOS (Contains Stoddard Solvent), Limited Quantity	Flammable Liquid, NOS (Contains Stoddard Solvent), Limited Quantity	Flammable Liquid, NOS (Contains Stoddard Solvent), Limited Quantity

14.3 Transport Hazard Class(es)	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
Transport Hazard Class(es)	: 3	3	3
Labels	: None	3 - Flammable liquid	None



Limited Quantity	: Yes	Yes	Yes

EmS Code	: Not Applicable	Not Applicable	F-E, S-E
----------	------------------	----------------	----------

14.4 Packing Group	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
Packing Group	: III	III	III

14.5 Environmental Hazards	DOT (USA)	IATA (AIR)	IMDG (OCEAN)
Marine Pollutant	: No	No	No

14.6 Special Precautions	Precautions : None Identified
--------------------------	-------------------------------

14.7 Transport in Bulk	Remarks : Not applicable for product as supplied
------------------------	--

SECTION 15 - REGULATORY INFORMATION

15.1 Federal Regulations

SARA Section 313 : Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Toluene	CAS-No. 108-88-3	< 1%
Cumene	CAS-No. 98-82-8	< 1%

TSCA Section 12(b) : This product or mixture is not known to contain a chemical or chemicals subject to the export notification requirements of section 12(b) of the Toxic Substances Control Act (TSCA) and 40 CFR Part 707, subpart D

CERCLA Reportable Quantity : Chemical(s) subject to reporting requirements of Section 102 of the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) if released to the environment at or above the reportable quantity

Toluene	CAS-No. 108-88-3	1000 lb
Cumene	CAS-No. 98-82-8	5000 lb
Acetone	CAS-No. 67-64-1	5000 lb

SARA Section 311/312 Hazard Classes : Delayed (chronic) health hazard, Fire hazard, Immediate (acute) health hazard.

SAFETY DATA SHEET

Part No. 160172P (Liquid)

Print Date: 8/1/2018
Revision Date: 8/1/2018
Supersedes Date: 3/22/2016
Issue Date: 8/31/2004
Version: 4.0 (EN)-US
Page: 8/9

Eastwood Heavy-Duty Anti Rust

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TSCA Inventory (United States) : All chemical substances in this product are either listed on the Toxic Substances Control Act (TSCA) Inventory or are in compliance with a TSCA Inventory exemption.

15.2 State Regulations

California Proposition 65 : This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Cumene (98-82-8)	Cancer	Yes	0.0004 %
Toluene (108-88-3)	Developmental Toxicity	Yes	0.0036 %
Toluene (108-88-3)	No significance risk level (NSRL)	7000 µg/day	

State Right-to-Know Lists : The following chemical(s) appear on one or more state RTK (Right to Know) lists as indicated

Stoddard Solvent (8052-41-3)	U.S. - New Jersey - Right to Know Hazardous Substance List
Toluene (108-88-3)	U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
2-Butoxyethanol (111-76-2)	U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List
Cumene (98-82-8)	U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
Acetone (67-64-1)	U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16 - OTHER INFORMATION

Indication of changes

Section	Changed item	Change
1	Supersedes	Added
1	SDS US Regulation reference	Added
1	Revision date	Modified
1	Date of issue	Modified
2.2	Precautionary statements (GHS-US)	Added
2.2	Hazard statements (GHS-US)	Added
2.3	Other hazards not contributing to the classification	Added
4	Symptoms/effects after ingestion	Added
4	Other medical advice or treatment	Added
4	Symptoms/effects after eye contact	Added
4	Symptoms/effects after skin contact	Added
4	Symptoms/effects	Added
4	Symptoms/effects after inhalation	Added
4.1	First-aid measures after ingestion	Added
4.1	First-aid measures after eye contact	Added
4.1	First-aid measures general	Added
4.1	First-aid measures after inhalation	Added
4.1	First-aid measures after skin contact	Added
8.2	Compliance	Added
8.2	Remarks	Added
8.2	Hand Protection	Added
8.2	Environmental Exposure Controls	Added
8.2	Respiratory Protection	Added
8.2	Other Protective Equipment	Added
8.2	Eye / Face Protection	Added
8.2	Skin and Body Protection	Added
8.2	Engineering Measures	Added
8.2	Environmental exposure controls	Added
8.2	Hand protection	Added
8.2	Appropriate engineering controls	Added
9	Relative vapor density at 20 °C	Added
9	Appearance	Added
9	Melting point	Added
9	Flash point	Added
9	Explosive limits (vol %)	Added
9	Boiling point	Added
9	Auto-ignition temperature	Added
9	Specific gravity / density	Added
10	Incompatibilities	Added
10	Prohibited Materials	Added
10	Decomposition Products due to Fire	Added
12.1	Ecology - general	Added
14	EmS Code (Column 15 in IMDG Book 2)	Added
14	User Precautions	Added
15	Select the Appropriate Proposition 65 Notice	Added
15	Display TSCA summary in 15.1	Added
15	Display SARA 313 summary in 15.1	Added
15	Display California Proposition 65 summary in 15.3	Added

SAFETY DATA SHEET

Part No. 16017ZP (Liquid)

Print Date: 8/1/2018
Revision Date: 8/1/2018
Supersedes Date: 3/22/2016
Issue Date: 8/31/2004
Version: 4.0 (EN)-US
Page: 9/9

Eastwood Heavy-Duty Anti Rust

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full Text of H-Statements

H Code	H Phrase
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

Disclaimer of Liability

The information contained herein is based upon data provided to us by our suppliers, and reflects our best judgement. However, no warranty of merchantability, fitness for any use, or any other warranty or guarantee is expressed or implied regarding the accuracy of such data, or the results to be obtained from use thereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not assume any responsibility for the results of such application. This information is furnished upon the condition that the persons receiving it shall make their own determinations of the suitability of the material for any particular use. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist.