

EASTWOOD RUST ENCAPSULATOR® is a high-performance coating that encapsulates rust and provides long term protection against corrosion build-up. RUST ENCAPSULATOR can be used as a top coat or can be top coated with almost any paint. It can be applied over bare metal or surface rusted areas. It is epoxy-fortified for excellent adhesion & fast curing, and has been tested to 500 hours in a salt spray chamber. RUST ENCAPSULATOR is ideal for any type of rusted metal surface and can withstand temperatures up to 400°F.

DIRECTIONS – READ ALL INSTRUCTIONS BEFORE USING THIS PRODUCT!

1. Ensure that the surface is free of loose rust, scale, and paint. Cleaning with a stiff wire brush should be sufficient. **2.** Remove all dust, oil, grease, or chemical contamination using EASTWOOD PRE PAINTING PREP (#10041Z). Allow to dry thoroughly. **3.** When applying EASTWOOD RUST ENCAPSULATOR to a patch area, feather the edges of the surrounding paint with coarse sandpaper. Be sure to feather into the surrounding paint by at least 1-1/4". **4.** Single coats of EASTWOOD RUST ENCAPSULATOR will be touch dry in 20 minutes and thoroughly dry in 3-4 hours at 70°F. If a second coat is desired for greater durability, allow 1 hour before applying the second coat. If applying heavy coats, allow extra drying time. May be thinned up to 20% with lacquer thinner for spraying. **5.** If applying a topcoat, allow at least 6-8 hours drying time. For maximum topcoat adhesion, scuff the surface with 320 grit wet/dry sandpaper. Allow extra drying time if wet sanding. **6.** Scuff sanding (320-400 grit) is required for topcoats applied after 36 hours.

CONTAINS: 4-Chlorobenzotrifluoride (CAS #98-56-6), Acetone (CAS #67-64-1), Barium Sulfate (CAS #7727-43-7), N-Butyl Acetate (CAS #123-86-4), Methyl N-Propyl Ketone (CAS #107-87-9), Carbon Black (CAS #1333-86-4) and Zinc Oxide (CAS #1314-13-2). 59% of the ingredients have an unknown acute toxicity.

DANGER: Highly flammable liquid and vapor. Causes skin and serious eye irritation. May cause an allergic skin reaction.

Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause respiratory irritation. May cause drowsiness or dizziness.

PRECAUTIONARY STATEMENTS: Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames and hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing fumes. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves and eye protection. In case of fire: use water, CO2, dry chemical, universal aqueous or film forming foam to extinguish. Store in a well-ventilated place. Keep container tightly closed and cool. Store locked up. Dispose of contents/container in accordance with local regulations.

FIRST AID: If exposed, concerned or feel unwell: Call a physician. **IF ON SKIN OR HAIR:** Take off immediately contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice. Take off contaminated clothing and wash it before reuse. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice.

VOC CONTENT: Primer, 179 g/L Regulatory, 103 g/L Actual

KEEP OUT OF THE REACH OF CHILDREN

 **WARNING:**
Cancer and Reproductive Harm – www.P65Warnings.ca.gov

Only in the Event of a Chemical Emergency Involving A Spill, Leaks, Fire, or Exposure Call Chemtrec
Toll Free Day or Night: 1-800-424-9300 International Call Collect: (202) 483-7616

Manufactured for The Eastwood Company, 263 Shoemaker Road, Pottstown, PA 19464 USA: 1-800-343-9353 Canada: 1-800-820-9042 International: (610) 323-2200 www.eastwood.com
© Copyright 2017 Easthill Group, Inc. Made in USA Label #16065ZPL 5/17 Rev 2



DO THE JOB RIGHT.®

RUST ENCAPSULATOR®

MATTE BLACK FINISH

- Apply Directly Over Surface Rust
- Top Coat With Almost Any Paint Or Use As A Top Coat
- Prevents Rust From Spreading
- Penetrates Deep and Cures Fast



Scan for product info

DANGER: FLAMMABLE – LIQUID AND VAPOR.
IRRITATING TO THE SKIN AND EYES.
Read Precautions On Rear Panel Before Use.

Net Contents: 1 US QUART (0.9 liter)

16065ZP