

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 11/12/2009

Reviewed on 11/12/2009

1 Identification of substance

- **Product details**

- **Trade name:** Self Etch Primer Gray

- **Article number:** 16108ZP

- **Manufactured For:**

The Easthill Group

dba/ The Eastwood Company

263 Shoemaker Road

Pottstown, PA 19464

- **Information department:**

USA & Canada: 800-345-1178

Outside USA: 610-323-2200

- **Emergency information:** 24 HR EMERGENCY CHEMTREC 1-800-424-9300

2 Composition/Data on components

- **Chemical characterization**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

108-88-3	toluene	13 - 30%
	Danger: 2.6/2; 3.10/1, 3.7/2, 3.9/2	
	Warning: 3.2/2, 3.8/3	
67-64-1	acetone	13 - 30%
	Danger: 2.6/2	
	Warning: 3.3/2A, 3.8/3	
123-86-4	n-butyl acetate	13 - 30%
	Warning: 2.6/3; 3.8/3	
78-93-3	butanone	7 - 10%
	Danger: 2.6/2	
	Warning: 3.3/2A, 3.8/3	
	Resin NJTSRN 6784	1.5 - 5%
	Warning: 3.2/2, 3.3/2A, 3.8/3	
9004-70-0	CELLULOSE NITRATE	1.5 - 5%
	Danger: 2.1; 3.1.0/3, 3.2/2, 3.3/2A, 3.8/3	
110-19-0	isobutyl acetate	1.5 - 5%
	Danger: 2.6/2	
67-63-0	propan-2-ol	1.5 - 5%
	Danger: 2.6/2	
	Warning: 3.3/2A, 3.8/3	
14808-60-7	Quartz (SiO ₂)	1.5 - 5%
	Danger: 3.6/1B, 3.8/2	
	Warning: 3.3/2A	
1330-20-7	xylene	1.5 - 5%
	Warning: 2.6/3; 3.1.D/4, 3.1.I/4, 3.2/2	
64742-94-5	Solvent naphtha (petroleum), heavy arom.	1.5 - 5%
	Danger: 3.10/1	

(Contd. on page 2)

USA

Material Safety Data Sheet








acc. to ISO/DIS 11014

Printing date 11/12/2009

Reviewed on 11/12/2009

Trade name: Self Etch Primer Gray

(Contd. of page 1)

14807-96-6	Talc ($Mg_3H_2(SiO_3)_4$)	1.5 - 5%
	Warning:  3.2/2, 3.3/2A, 3.8/3	
18268-70-7	Tetraethylene Glycol Di 2-ethylhexoate	1-1.5%
	Danger:  3.1.O/3, 3.2/2, 3.3/2A, 3.8/3	
1330-78-5	tris(methylphenyl) phosphate	≤1%
	Danger:  3.8/1	
	 4.1.C/2	
67-56-1	methanol	≤1%
	Danger:  2.6/2;  3.1.O/3, 3.1.D/3, 3.1.I/3;  3.8/1	

3 Hazards identification

· Hazard description:



Toxic
Highly flammable

· Information pertaining to particular dangers for man and environment:

The product has to be labelled due to the calculation procedure of international guidelines.

May cause cancer by inhalation.

Highly flammable.

Irritating to eyes and skin.

Also harmful: danger of serious damage to health by prolonged exposure through inhalation.

Also harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed.

Possible risk of harm to the unborn child.

· Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

· NFPA ratings (scale 0 - 4)



Health = 2

Fire = 3

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2

Fire = 3

Reactivity = 0

· GHS label elements



Danger

2.6/2 - Highly flammable liquid and vapour.

(Contd. on page 3)

USA

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 11/12/2009

Reviewed on 11/12/2009

Trade name: Self Etch Primer Gray

(Contd. of page 2)

**Danger**

- 3.6/1B - May cause cancer.
- 3.7/2 - Suspected of damaging fertility or the unborn child.
- 3.8/2 - May cause damage to organs.
- 3.9/2 - May cause damage to organs through prolonged or repeated exposure.

**Warning**

- 3.2/2 - Causes skin irritation.
- 3.3/2A - Causes serious eye irritation.

Prevention:

- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting/equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Do not breathe dust/fume/gas/mist/vapours/spray.
- Wash thoroughly after handling.
- Do not eat, drink or smoke when using this product.
- Wear protective gloves/protective clothing/eye protection/face protection.
- Use personal protective equipment as required.

Response:

- IF ON SKIN: Wash with plenty of soap and water.
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF exposed or concerned: Get medical advice/attention.
- IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.
- Get medical advice/attention if you feel unwell.
- Specific treatment (see on this label).
- If skin irritation occurs: Get medical advice/attention.
- If eye irritation persists: Get medical advice/attention.
- Take off contaminated clothing and wash before reuse.
- In case of fire: Use for extinction: CO₂, powder or water spray.

Storage:

- Store in a well-ventilated place. Keep cool.
- Store locked up.

Disposal:

- Dispose of contents/container in accordance with local/regional/national/international regulations.

4 First aid measures

- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 4)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 11/12/2009

Reviewed on 11/12/2009

Trade name: Self Etch Primer Gray

(Contd. of page 3)

- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** *If symptoms persist consult doctor.*

5 Fire fighting measures

- **Suitable extinguishing agents:** *CO2, sand, extinguishing powder. Do not use water.*
- **For safety reasons unsuitable extinguishing agents:** *Water with full jet*
- **Protective equipment:** *No special measures required.*

6 Accidental release measures

- **Person-related safety precautions:** *Wear protective equipment. Keep unprotected persons away.*
- **Measures for environmental protection:** *Do not allow to enter sewers/ surface or ground water.*
- **Measures for cleaning/collecting:**
*Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents*

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
*Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.*
- **Information about protection against explosions and fires:**
*Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.*
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** *Store in a cool location.*
- **Information about storage in one common storage facility:** *Not required.*
- **Further information about storage conditions:**
*Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.*

8 Exposure controls and personal protection

- **Additional information about design of technical systems:** *No further data; see item 7.*

(Contd. on page 5)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 11/12/2009

Reviewed on 11/12/2009

Trade name: Self Etch Primer Gray

(Contd. of page 4)

· Components with limit values that require monitoring at the workplace:

108-88-3 toluene

PEL	Short-term value: C 300; 500* ppm Long-term value: 200 ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV	75 mg/m ³ , 20 ppm

67-64-1 acetone

PEL	2400 mg/m ³ , 1000 ppm
REL	590 mg/m ³ , 250 ppm
TLV	Short-term value: 1782 mg/m ³ , 750 ppm Long-term value: 1188 mg/m ³ , 500 ppm BEI

123-86-4 n-butyl acetate

PEL	710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 713 mg/m ³ , 150 ppm

78-93-3 butanone

PEL	590 mg/m ³ , 200 ppm
REL	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm
TLV	Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm BEI

110-19-0 isobutyl acetate

PEL	700 mg/m ³ , 150 ppm
REL	700 mg/m ³ , 150 ppm
TLV	713 mg/m ³ , 150 ppm

67-63-0 propan-2-ol

PEL	980 mg/m ³ , 400 ppm
REL	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV	Short-term value: 984 mg/m ³ , 400 ppm Long-term value: 492 mg/m ³ , 200 ppm BEI

14808-60-7 Quartz (SiO₂)

PEL	see Quartz listing
REL	0.05* mg/m ³ *respirable dust
TLV	0.025* mg/m ³ *as respirable fraction

(Contd. on page 6)

-USA-

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 11/12/2009

Reviewed on 11/12/2009

Trade name: Self Etch Primer Gray

(Contd. of page 5)

1330-20-7 xylene

PEL	435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI

67-56-1 methanol

PEL	260 mg/m ³ , 200 ppm
REL	Short-term value: 325 mg/m ³ , 250 ppm Long-term value: 260 mg/m ³ , 200 ppm Skin
TLV	Short-term value: 328 mg/m ³ , 250 ppm Long-term value: 262 mg/m ³ , 200 ppm Skin; BEI

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 7)

USA

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 11/12/2009

Reviewed on 11/12/2009

Trade name: Self Etch Primer Gray

(Contd. of page 6)

· **Eye protection:**

Tightly sealed goggles

9 Physical and chemical properties· **General Information**

Form: Liquid
Color: According to product specification
Odor: Characteristic

· **Change in condition**

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 55°C (131°F)

· **Flash point:** -19°C (-2°F)· **Ignition temperature:** 370°C (698°F)· **Auto igniting:** Product is not selfigniting.· **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.· **Explosion limits:**

Lower: 1.2 Vol %
Upper: 13.0 Vol %

· **Vapor pressure at 20°C (68°F):** 233 hPa (175 mm Hg)· **Density at 20°C (68°F):** 0.95 g/cm³· **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

· **Solvent content:**

Organic solvents: 78.9 %
VOC content: 60.1 %
568.4 g/l / 4.74 lb/gl

· **Solids content:** 20.9 %**10 Stability and reactivity**

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous products of decomposition:** No dangerous decomposition products known.

USA

(Contd. on page 8)

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 11/12/2009

Reviewed on 11/12/2009

Trade name: Self Etch Primer Gray

(Contd. of page 7)

11 Toxicological information· **Acute toxicity:**· **LD/LC50 values that are relevant for classification:****108-88-3 toluene**

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

· **Primary irritant effect:**· **on the skin:** Irritant to skin and mucous membranes.· **on the eye:** Irritating effect.· **Sensitization:** No sensitizing effects known.· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

Carcinogenic if inhaled.

12 Ecological information· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

13 Disposal considerations· **Product:**· **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packagings:**· **Recommendation:** Disposal must be made according to official regulations.**14 Transport information**· **DOT regulations:**· **Hazard class:**

3

· **Identification number:**

UN1263

· **Packing group:**

II

· **Proper shipping name (technical name):** PAINT· **Label**

3

(Contd. on page 9)

USA

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 11/12/2009

Reviewed on 11/12/2009

Trade name: Self Etch Primer Gray

(Contd. of page 8)

· **Remarks** ORM-D 49CFR 173.150,156,or306

· **Land transport TDG (Canada) and ADR/RID (Europe):**



· **Hazard class:** 3 Flammable liquids
· **UN-Number:** 1263
· **Packaging group:** II
· **Label:** 3
· **Description of goods:** 1263 PAINT, special provision 640D

· **Maritime transport IMDG:**



· **IMDG Class:** 3
· **UN Number:** 1263
· **Label** 3
· **Packaging group:** II
· **EMS Number:** F-E,S-D
· **Marine pollutant:** No
· **Propper shipping name:** PAINT

· **Air transport ICAO-TI and IATA-DGR:**



· **ICAO/IATA Class:** 3
· **UN/ID Number:** 1263
· **Label** 3
· **Packaging group:** II
· **Propper shipping name:** PAINT

· **UN "Model Regulation":** UN1263, PAINT, 3, II

15 Regulations

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

108-88-3 toluene

78-93-3 butanone

67-63-0 propan-2-ol

1330-20-7 xylene

(Contd. on page 10)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 11/12/2009

Reviewed on 11/12/2009

Trade name: Self Etch Primer Gray

(Contd. of page 9)

14807-96-6	Talc ($Mg_3H_2(SiO_3)_4$)
67-56-1	methanol
	ACRYLIC RESIN
91-20-3	naphthalene
95-63-6	1,2,4-trimethylbenzene
100-41-4	ethylbenzene

· TSCA (Toxic Substances Control Act):

108-88-3	toluene
67-64-1	acetone
123-86-4	n-butyl acetate
78-93-3	butanone
9004-70-0	CELLULOSE NITRATE
13463-67-7	titanium dioxide
110-19-0	isobutyl acetate
67-63-0	propan-2-ol
14808-60-7	Quartz (SiO_2)
1330-20-7	xylene
64742-94-5	Solvent naphtha (petroleum), heavy arom.
14807-96-6	Talc ($Mg_3H_2(SiO_3)_4$)
18268-70-7	Tetraethylene Glycol Di 2-ethylhexoate
1330-78-5	tris(methylphenyl) phosphate
68911-87-5	ALKYL QUATERNARY AMMONIUM MONTMORILLONITE

· Proposition 65

· Chemicals known to cause cancer:

14808-60-7	Quartz (SiO_2)
1330-20-7	xylene
68911-87-5	ALKYL QUATERNARY AMMONIUM MONTMORILLONITE
1333-86-4	Carbon black
91-20-3	naphthalene
95-63-6	1,2,4-trimethylbenzene
100-41-4	ethylbenzene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

108-88-3	toluene
----------	---------

· Cancerogenity categories

· EPA (Environmental Protection Agency)

108-88-3	toluene	II
67-64-1	acetone	I

(Contd. on page 11)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 11/12/2009

Reviewed on 11/12/2009

Trade name: Self Etch Primer Gray

(Contd. of page 10)

78-93-3	butanone	I
1330-20-7	xylene	I
111-76-2	2-butoxyethanol	CBD
91-20-3	naphthalene	CBD
100-41-4	ethylbenzene	D

· **IARC (International Agency for Research on Cancer)**

108-88-3	toluene	3
13463-67-7	titanium dioxide	2B
67-63-0	propan-2-ol	3
14808-60-7	Quartz (SiO ₂)	I
1330-20-7	xylene	3
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	3
7631-86-9	silicon dioxide, chemically prepared	3
1333-86-4	Carbon black	2B
111-76-2	2-butoxyethanol	3
91-20-3	naphthalene	2B
100-41-4	ethylbenzene	2B

· **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO ₂)	K
91-20-3	naphthalene	R

· **TLV (Threshold Limit Value established by ACGIH)**

108-88-3	toluene	A4
67-64-1	acetone	A4
13463-67-7	titanium dioxide	A4
67-63-0	propan-2-ol	A4
14808-60-7	Quartz (SiO ₂)	A2
1330-20-7	xylene	A4
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	A4
1333-86-4	Carbon black	A4
111-76-2	2-butoxyethanol	A3
91-20-3	naphthalene	A4
100-41-4	ethylbenzene	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide	
14808-60-7	Quartz (SiO ₂)	
67-56-1	methanol	
1333-86-4	Carbon black	

· **OSHA-Ca (Occupational Safety & Health Administration)**

68911-87-5	ALKYL QUATERNARY AMMONIUM MONTMORILLONITE	
------------	---	--

· **Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

(Contd. on page 12)

USA

Material Safety Data Sheet
acc. to ISO/DIS 11014

Printing date 11/12/2009

Reviewed on 11/12/2009

Trade name: Self Etch Primer Gray

(Contd. of page 11)

· Hazard symbols:*Toxic**Highly flammable***· Hazard-determining components of labelling:***toluene**Quartz (SiO₂)**tris(methylphenyl) phosphate***· Risk phrases:***May cause cancer by inhalation.**Highly flammable.**Irritating to eyes and skin.**Also harmful: danger of serious damage to health by prolonged exposure through inhalation.**Also harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed.**Possible risk of harm to the unborn child.***· Safety phrases:***Avoid exposure - obtain special instructions before use.**Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).**Wear suitable protective clothing and gloves.**In case of insufficient ventilation, wear suitable respiratory equipment.**In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).**This material and its container must be disposed of as hazardous waste.***16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing MSDS: *Environment protection department.***· Contact:** *Steve Gaver***· Abbreviations and acronyms:***ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)**RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)**IMDG: International Maritime Code for Dangerous Goods**DOT: US Department of Transportation**IATA: International Air Transport Association**IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)**ICAO: International Civil Aviation Organization**ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)**GHS: Globally Harmonized System of Classification and Labelling of Chemicals**ACGIH: American Conference of Governmental Industrial Hygienists**NFPA: National Fire Protection Association (USA)**HMIS: Hazardous Materials Identification System (USA)**VOC: Volatile Organic Compounds (USA, EU)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent*