

## 1 Identification

- **Product identifier**
- **Trade name:** EW16114Z Self Etching Primer Black
- **Article number:** EW16114Z
- **Application of the substance / the mixture**  
Coating  
aerosol metal primer
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Eastwood Products  
263 Shoemaker Road  
Pottstown, PA 19464  
United States of America
- **Information department:** (800)343-9353
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Carc. 1A H350 May cause cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT SE 1 H370 Causes damage to organs.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

**Trade name: EW16114Z Self Etching Primer Black**

(Contd. of page 1)

**· Hazard pictograms**


GHS02   GHS04   GHS07   GHS08

**· Signal word Danger**
**· Hazard-determining components of labeling:**

 toluene  
 acetone  
 Quartz (SiO<sub>2</sub>)  
 ethyl acetate

**· Hazard statements**

H222 Extremely flammable aerosol.  
 H280 Contains gas under pressure; may explode if heated.  
 H315 Causes skin irritation.  
 H319 Causes serious eye irritation.  
 H350 May cause cancer.  
 H361 Suspected of damaging fertility or the unborn child.  
 H370 Causes damage to organs.  
 H336 May cause drowsiness or dizziness.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H304 May be fatal if swallowed and enters airways.

**· Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
 P251 Do not pierce or burn, even after use.  
 P260 Do not breathe dust/fume/gas/mist/vapors/spray.  
 P211 Do not spray on an open flame or other ignition source.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P264 Wash thoroughly after handling.  
 P270 Do not eat, drink or smoke when using this product.  
 P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P321 Specific treatment (see on this label).  
 P308+P313 IF exposed or concerned: Get medical advice/attention.  
 P332+P313 If skin irritation occurs: Get medical advice/attention.  
 P337+P313 If eye irritation persists: Get medical advice/attention.  
 P314 Get medical advice/attention if you feel unwell.  
 P331 Do NOT induce vomiting.  
 P302+P352 IF ON SKIN: Wash with plenty of water.  
 P362+P364 Take off contaminated clothing and wash it before reuse.  
 P405 Store locked up.  
 P410+P403 Protect from sunlight. Store in a well-ventilated place.  
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

USA

**Trade name: EW16114Z Self Etching Primer Black**

(Contd. of page 2)

**· Classification system:**
**· NFPA ratings (scale 0 - 4)**

**· HMIS-ratings (scale 0 - 4)**

**· Other hazards**
**· Results of PBT and vPvB assessment**
**· PBT:** Not applicable.

**· vPvB:** Not applicable.

**3 Composition/information on ingredients**
**· Chemical characterization: Mixtures**
**· Description:**

 Mixture: consisting of the following components.  
 Weight percentages

**· Dangerous components:**

67-64-1	acetone	13 - 30%
68476-86-8	Petroleum gases, liquefied, sweetened	13 - 30%
108-88-3	toluene	7 - 10%
110-19-0	isobutyl acetate	7 - 10%
141-78-6	ethyl acetate	5 - 7%
78-93-3	butanone	5 - 7%
	Resin NJTSRN 6784	
9004-70-0	CELLULOSE NITRATE	1.5 - 5%
123-86-4	n-butyl acetate	1.5 - 5%
64742-94-5	Solvent naphtha (petroleum), heavy arom.	1-1.5%
67-63-0	propan-2-ol	1-1.5%
14808-60-7	Quartz (SiO <sub>2</sub> )	1-1.5%
14807-96-6	Talc	1-1.5%
1330-78-5	tris(methylphenyl) phosphate	≤1%

**4 First-aid measures**
**· Description of first aid measures**
**· After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

**· After skin contact:** Immediately wash with water and soap and rinse thoroughly.

**· After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**· After swallowing:** If symptoms persist consult doctor.

(Contd. on page 4)

Printing date 04/11/2017

Reviewed on 04/11/2017

**Trade name: EW16114Z Self Etching Primer Black**

(Contd. of page 3)

- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

### · PAC-I:

67-64-1	acetone	200 ppm
108-88-3	toluene	67 ppm
110-19-0	isobutyl acetate	450 ppm
141-78-6	ethyl acetate	1,200 ppm
78-93-3	butanone	200 ppm
13463-67-7	titanium dioxide	30 mg/m <sup>3</sup>
123-86-4	n-butyl acetate	5 ppm
67-63-0	propan-2-ol	400 ppm
14808-60-7	Quartz (SiO <sub>2</sub> )	0.075 mg/m <sup>3</sup>
108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
1333-86-4	Carbon black	9 mg/m <sup>3</sup>
6915-15-7	malic acid	4.8 mg/m <sup>3</sup>
1330-20-7	xylene	130 ppm
112945-52-5	SILICA	18 mg/m <sup>3</sup>
67-56-1	methanol	530 ppm
100-41-4	ethylbenzene	33 ppm
91-20-3	naphthalene	15 ppm

(Contd. on page 5)

USA

# Safety Data Sheet

acc. to OSHA HCS



DO THE JOB RIGHT.

Printing date 04/11/2017

Reviewed on 04/11/2017

Trade name: EW16114Z Self Etching Primer Black

(Contd. of page 4)

122-99-6	2-Phenoxyethanol	1.5 ppm
78-83-1	butanol	150 ppm
57-55-6	Methyl glycol	30 mg/m3
95-63-6	1,2,4-trimethylbenzene	140 ppm
21645-51-2	aluminium hydroxide	8.7 mg/m3
7631-86-9	silicon dioxide, chemically prepared	18 mg/m3

## · PAC-2:

67-64-1	acetone	3200* ppm
108-88-3	toluene	560 ppm
110-19-0	isobutyl acetate	1300* ppm
141-78-6	ethyl acetate	1,700 ppm
78-93-3	butanone	2700* ppm
13463-67-7	titanium dioxide	330 mg/m3
123-86-4	n-butyl acetate	200 ppm
67-63-0	propan-2-ol	2000* ppm
14808-60-7	Quartz (SiO2)	33 mg/m3
108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
1333-86-4	Carbon black	99 mg/m3
6915-15-7	malic acid	53 mg/m3
1330-20-7	xylene	920* ppm
112945-52-5	SILICA	100 mg/m3
67-56-1	methanol	2,100 ppm
100-41-4	ethylbenzene	1100* ppm
91-20-3	naphthalene	83 ppm
122-99-6	2-Phenoxyethanol	16 ppm
78-83-1	butanol	1,300 ppm
57-55-6	Methyl glycol	1,300 mg/m3
95-63-6	1,2,4-trimethylbenzene	360 ppm
21645-51-2	aluminium hydroxide	73 mg/m3
7631-86-9	silicon dioxide, chemically prepared	740 mg/m3

## · PAC-3:

67-64-1	acetone	5700* ppm
108-88-3	toluene	3700* ppm
110-19-0	isobutyl acetate	7500** ppm
141-78-6	ethyl acetate	10000** ppm
78-93-3	butanone	4000* ppm
13463-67-7	titanium dioxide	2,000 mg/m3
123-86-4	n-butyl acetate	3000* ppm
67-63-0	propan-2-ol	12000** ppm
14808-60-7	Quartz (SiO2)	200 mg/m3
108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm

(Contd. on page 6)

USA

**Trade name: EW16114Z Self Etching Primer Black**

(Contd. of page 5)

1333-86-4	Carbon black	590 mg/m <sup>3</sup>
6915-15-7	malic acid	320 mg/m <sup>3</sup>
1330-20-7	xylene	2500* ppm
112945-52-5	SILICA	630 mg/m <sup>3</sup>
67-56-1	methanol	7200* ppm
100-41-4	ethylbenzene	1800* ppm
91-20-3	naphthalene	500 ppm
122-99-6	2-Phenoxyethanol	97 ppm
78-83-1	butanol	8000* ppm
57-55-6	Methyl glycol	7,900 mg/m <sup>3</sup>
95-63-6	1,2,4-trimethylbenzene	480 ppm
21645-51-2	aluminium hydroxide	440 mg/m <sup>3</sup>
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m <sup>3</sup>

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
No special measures required.  
Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:**  
Do not spray on a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the other constituents have no known exposure limits.

### 67-64-1 acetone

 PEL Long-term value: 2400 mg/m<sup>3</sup>, 1000 ppm

(Contd. on page 7)

USA

# Safety Data Sheet

acc. to OSHA HCS



Printing date 04/11/2017

Reviewed on 04/11/2017

Trade name: EW16114Z Self Etching Primer Black

(Contd. of page 6)

REL Long-term value: 590 mg/m<sup>3</sup>, 250 ppm  
 TLV Short-term value: 1187 mg/m<sup>3</sup>, 500 ppm  
 Long-term value: 594 mg/m<sup>3</sup>, 250 ppm  
 BEI

**108-88-3 toluene**

PEL Long-term value: 200 ppm  
 Ceiling limit value: 300; 500\* ppm  
 \*10-min peak per 8-hr shift  
 REL Short-term value: 560 mg/m<sup>3</sup>, 150 ppm  
 Long-term value: 375 mg/m<sup>3</sup>, 100 ppm  
 TLV Long-term value: 75 mg/m<sup>3</sup>, 20 ppm  
 BEI

**110-19-0 isobutyl acetate**

PEL Long-term value: 700 mg/m<sup>3</sup>, 150 ppm  
 REL Long-term value: 700 mg/m<sup>3</sup>, 150 ppm  
 TLV Short-term value: 172 mg/m<sup>3</sup>, 150 ppm  
 Long-term value: 238 mg/m<sup>3</sup>, 50 ppm

**141-78-6 ethyl acetate**

PEL Long-term value: 1400 mg/m<sup>3</sup>, 400 ppm  
 REL Long-term value: 1400 mg/m<sup>3</sup>, 400 ppm  
 TLV Long-term value: 1440 mg/m<sup>3</sup>, 400 ppm

**78-93-3 butanone**

PEL Long-term value: 590 mg/m<sup>3</sup>, 200 ppm  
 REL Short-term value: 885 mg/m<sup>3</sup>, 300 ppm  
 Long-term value: 590 mg/m<sup>3</sup>, 200 ppm  
 TLV Short-term value: 885 mg/m<sup>3</sup>, 300 ppm  
 Long-term value: 590 mg/m<sup>3</sup>, 200 ppm  
 BEI

**123-86-4 n-butyl acetate**

PEL Long-term value: 710 mg/m<sup>3</sup>, 150 ppm  
 REL Short-term value: 950 mg/m<sup>3</sup>, 200 ppm  
 Long-term value: 710 mg/m<sup>3</sup>, 150 ppm  
 TLV Short-term value: 712 mg/m<sup>3</sup>, 150 ppm  
 Long-term value: 238 mg/m<sup>3</sup>, 50 ppm

**67-63-0 propan-2-ol**

PEL Long-term value: 980 mg/m<sup>3</sup>, 400 ppm  
 REL Short-term value: 1225 mg/m<sup>3</sup>, 500 ppm  
 Long-term value: 980 mg/m<sup>3</sup>, 400 ppm  
 TLV Short-term value: 984 mg/m<sup>3</sup>, 400 ppm  
 Long-term value: 492 mg/m<sup>3</sup>, 200 ppm  
 BEI

**14808-60-7 Quartz (SiO<sub>2</sub>)**

PEL see Quartz listing

(Contd. on page 8)

USA

# Safety Data Sheet

acc. to OSHA HCS



Printing date 04/11/2017

Reviewed on 04/11/2017

Trade name: EW16114Z Self Etching Primer Black

(Contd. of page 7)

REL	Long-term value: 0.05* mg/m <sup>3</sup> *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m <sup>3</sup> *as respirable fraction

· **Ingredients with biological limit values:**

**67-64-1 acetone**

BEI	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----	--

**108-88-3 toluene**

BEI	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

**78-93-3 butanone**

BEI	2 mg/L Medium: urine Time: end of shift Parameter: MEK
-----	---

**67-63-0 propan-2-ol**

BEI	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
-----	---

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 9)



**Trade name: EW16114Z Self Etching Primer Black**

(Contd. of page 8)

**· Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

**· Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**· Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**· Eye protection:**

Safety glasses



Tightly sealed goggles

**9 Physical and chemical properties**
**· Information on basic physical and chemical properties**
**· General Information**
**· Appearance:**

<b>Form:</b>	Aerosol
<b>Color:</b>	Black
<b>· Odor:</b>	Characteristic
<b>· Odor threshold:</b>	Not determined.

**· pH-value:** Not determined.

**· Change in condition**

<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	55 °C

**· Flash point:** -103 °C

**· Flammability (solid, gaseous):** Not applicable.

**· Ignition temperature:** 405 °C

**· Decomposition temperature:** Not determined.

**· Auto igniting:** Product is not selfigniting.

**· Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

**· Explosion limits:**

<b>Lower:</b>	1.9 Vol %
<b>Upper:</b>	13.0 Vol %

(Contd. on page 10)

**Trade name: EW16114Z Self Etching Primer Black**

(Contd. of page 9)

- |   |  |
|---|--|
| · <b>Vapor pressure at 20 °C:</b>                 | 233 hPa                                    |
| · <b>Density at 20 °C:</b>                        | 0.77759 g/cm <sup>3</sup>                  |
| · <b>Relative density</b>                         | Not determined.                            |
| · <b>Vapor density</b>                            | Not determined.                            |
| · <b>Evaporation rate</b>                         | Not applicable.                            |
| · <b>Solubility in / Miscibility with Water:</b>  | Not miscible or difficult to mix.          |
| · <b>Partition coefficient (n-octanol/water):</b> | Not determined.                            |
| · <b>Viscosity:</b>                               |  |
| <b>Dynamic:</b>                                   | Not determined.                            |
| <b>Kinematic:</b>                                 | Not determined.                            |
| · <b>Solvent content:</b>                         |  |
| <b>Organic solvents:</b>                          | 85.4 %                                     |
| <b>VOC content:</b>                               | 59.5 %                                     |
|   | 621.3 g/l / 5.18 lb/gal                    |
| · <b>Solids content:</b>                          | 14.6 %                                     |
| · <b>Other information</b>                        | No further relevant information available. |

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

### 108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant

(Contd. on page 11)

USA

**Trade name: EW16114Z Self Etching Primer Black**

(Contd. of page 10)

 · **Carcinogenic categories**

 · **IARC (International Agency for Research on Cancer)**

108-88-3	toluene	3
13463-67-7	titanium dioxide	2B
67-63-0	propan-2-ol	3
14808-60-7	Quartz (SiO <sub>2</sub> )	1
14807-96-6	Talc	3
1333-86-4	Carbon black	2B
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
91-20-3	naphthalene	2B
7631-86-9	silicon dioxide, chemically prepared	3

 · **NTP (National Toxicology Program)**

14808-60-7	Quartz (SiO <sub>2</sub> )	K
91-20-3	naphthalene	R

 · **OSHA-Ca (Occupational Safety & Health Administration)**

68911-87-5	montmorillonite clay complex	
------------	------------------------------	--

 \* **12 Ecological information**

 · **Toxicity**

 · **Aquatic toxicity:** No further relevant information available.

 · **Persistence and degradability** No further relevant information available.

 · **Behavior in environmental systems:**

 · **Bioaccumulative potential** No further relevant information available.

 · **Mobility in soil** No further relevant information available.

 · **Additional ecological information:**

 · **General notes:**

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

 · **Results of PBT and vPvB assessment**

 · **PBT:** Not applicable.

 · **vPvB:** Not applicable.

 · **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

 · **Waste treatment methods**

 · **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 12)

# Safety Data Sheet

acc. to OSHA HCS



Printing date 04/11/2017

Reviewed on 04/11/2017

Trade name: EW16114Z Self Etching Primer Black

(Contd. of page 11)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1950
- **UN proper shipping name**
- **DOT** Aerosols, flammable
- **ADR** 1950 Aerosols
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable

- **Transport hazard class(es)**

- **DOT**



- **Class** 2.1
- **Label** 2.1

- **ADR**



- **Class** 2 5F Gases
- **Label** 2.1

- **IMDG, IATA**



- **Class** 2.1
- **Label** 2.1

- **Packing group**
- **DOT, ADR, IMDG, IATA** Void

- **Environmental hazards:**
- **Marine pollutant:** No

- **Special precautions for user** Warning: Gases
- **EMS Number:** F-D,S-U

(Contd. on page 13)

USA

# Safety Data Sheet

acc. to OSHA HCS



Printing date 04/11/2017

Reviewed on 04/11/2017

Trade name: EW16114Z Self Etching Primer Black

(Contd. of page 12)

· <b>Stowage Code</b>	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· <b>Segregation Code</b>	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>DOT</b>	
· <b>Quantity limitations</b>	On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg
· <b>ADR</b>	
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>UN "Model Regulation":</b>	UN 1950 AEROSOLS, 2.1

## 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

### · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

### · Section 313 (Specific toxic chemical listings):

108-88-3	toluene
78-93-3	butanone
67-63-0	propan-2-ol
14807-96-6	Talc
1330-20-7	xylene
67-56-1	methanol
	Acrylic Resin
100-41-4	ethylbenzene
91-20-3	naphthalene
122-99-6	2-Phenoxyethanol
95-63-6	1,2,4-trimethylbenzene

(Contd. on page 14)

USA

# Safety Data Sheet

acc. to OSHA HCS



Printing date 04/11/2017

Reviewed on 04/11/2017

Trade name: EW16114Z Self Etching Primer Black

(Contd. of page 13)

104-68-7	Diethylene glycol monophenyl ether
<b>· TSCA (Toxic Substances Control Act):</b>	
67-64-1	acetone
108-88-3	toluene
110-19-0	isobutyl acetate
141-78-6	ethyl acetate
78-93-3	butanone
13463-67-7	titanium dioxide
9004-70-0	CELLULOSE NITRATE
123-86-4	n-butyl acetate
64742-94-5	Solvent naphtha (petroleum), heavy arom.
67-63-0	propan-2-ol
14808-60-7	Quartz (SiO <sub>2</sub> )
14807-96-6	Talc
1330-78-5	tris(methylphenyl) phosphate
18268-70-7	Tetraethylene Glycol Di 2-ethylhexoate
108-65-6	2-methoxy-1-methylethyl acetate
68911-87-5	montmorilontie clay complex
1333-86-4	Carbon black
6915-15-7	malic acid
1330-20-7	xylene
67-56-1	methanol
1328-53-6	PHTHALO GREEN PIGMENT
100-41-4	ethylbenzene
91-20-3	naphthalene
122-99-6	2-Phenoxyethanol
78-83-1	butanol
57-55-6	Methyl glycol
95-63-6	1,2,4-trimethylbenzene
64742-95-6	Solvent naphtha (petroleum), light arom.
104-68-7	Diethylene glycol monophenyl ether
21645-51-2	aluminium hydroxide

**· Proposition 65**

<b>· Chemicals known to cause cancer:</b>	
13463-67-7	titanium dioxide
14808-60-7	Quartz (SiO <sub>2</sub> )
1333-86-4	Carbon black
1330-20-7	xylene
100-41-4	ethylbenzene
91-20-3	naphthalene
95-63-6	1,2,4-trimethylbenzene

(Contd. on page 15)

# Safety Data Sheet

acc. to OSHA HCS



Printing date 04/11/2017

Reviewed on 04/11/2017

Trade name: EW16114Z Self Etching Primer Black

(Contd. of page 14)

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3 toluene

67-56-1 methanol

· **Carcinogenicity categories**

· **EPA (Environmental Protection Agency)**

67-64-1	acetone	I
108-88-3	toluene	II
78-93-3	butanone	I
1330-20-7	xylene	I
100-41-4	ethylbenzene	D
91-20-3	naphthalene	C, CBD
95-63-6	1,2,4-trimethylbenzene	II

· **TLV (Threshold Limit Value established by ACGIH)**

67-64-1	acetone	A4
108-88-3	toluene	A4
13463-67-7	titanium dioxide	A4
67-63-0	propan-2-ol	A4
14808-60-7	Quartz (SiO <sub>2</sub> )	A2
14807-96-6	Talc	A4
1333-86-4	Carbon black	A4
1330-20-7	xylene	A4
100-41-4	ethylbenzene	A3
91-20-3	naphthalene	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide
14808-60-7	Quartz (SiO <sub>2</sub> )
1333-86-4	Carbon black
67-56-1	methanol

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS04 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

toluene

acetone

(Contd. on page 16)

USA

Printing date 04/11/2017

Reviewed on 04/11/2017

**Trade name: EW16114Z Self Etching Primer Black**

(Contd. of page 15)

Quartz (SiO<sub>2</sub>)

ethyl acetate

**· Hazard statements**

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn child.

H370 Causes damage to organs.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

**· Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P251 Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P211 Do not spray on an open flame or other ignition source.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see on this label).

P308+P313 IF exposed or concerned: Get medical advice/attention.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P331 Do NOT induce vomiting.

P302+P352 IF ON SKIN: Wash with plenty of water.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**· National regulations:**
**· Additional classification according to Decree on Hazardous Materials:**

Carcinogenic hazardous material group III (dangerous).

**· Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.

Exceptions can be made by the authorities in certain cases.

**· Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 17)

USA



**Trade name: EW16114Z Self Etching Primer Black**

(Contd. of page 16)

· **Department issuing SDS:** Environment protection department.

**Date of preparation / last revision** 04/11/2017 / 16

· **Abbreviations and acronyms:**

ICAO: International Civil Aviation Organisation

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Aerosol 1: Aerosols – Category 1

Press. Gas: Gases under pressure – Compressed gas

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Carc. 1A: Carcinogenicity – Category 1A

Repr. 2: Reproductive toxicity – Category 2

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

· **\* Data compared to the previous version altered.**