



DO THE JOB RIGHT.®

EASTWOOD RUST ENCAPSULATOR® PLATINUM is a high-performance, moisture-cured coating that encapsulates and stops rust from spreading. RUST ENCAPSULATOR PLATINUM can be used as a top coat or can be top coated with almost any paint. It can be applied over bare metal or surface rusted areas. Brush or spray applied with conventional spray equipment. RUST ENCAPSULATOR PLATINUM is ideal for any type of rusted metal surface and can withstand temperatures up to 350°F.

DIRECTIONS – READ ALL INSTRUCTIONS BEFORE USING THIS PRODUCT!

1. Clean loose rust and scale with stiff wire brush before application.
2. Clean surface to be painted with PRE Painting Prep # 10041Z or lacquer thinner. Allow to dry.
3. **Application Temperature/Time to Recoat:** Apply when metal surface temperature is between 40°F and 80°F. Top coat after 4 hours up to 48 hours. After 48 hours surface must be scuff sanded with Scotchbrite pad or 320 grit paper for maximum adhesion.
4. **Brush Application:** Apply one medium wet coat with bristle brush to all rusted areas. Assure hard to reach areas are coated.
5. **Spray Application:** Product can be thinned up to 20% with Xylene. Clean spray equipment immediately with acetone or lacquer thinner.
6. **Product Storage:** If product is to be stored in this container. Wipe recessed area on can lid to remove product before closing lid. Failure to clean area will result in lid bonding to can and destroying product.

CONTAINS: Tert-butyl acetate (CAS #540-88-5), 4,4'-methylenediphenyl diisocyanate (CAS #101-68-8), aluminum powder (stabilized) (CAS #7429-90-5), Diphenylmethanediisocyanate, isomers and homologues (CAS #9016-87-9), Solvent naphtha (petroleum), light arom (CAS #64742-95-6), O-(p-isocyanatobenzyl)phenyl isocyanate (CAS #5873-54-1), N-methyl-2-pyrrolidone (CAS #872-50-4).

DANGER: Highly flammable liquid and vapor. Causes skin and serious eye irritation. May cause an allergic skin reaction. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause respiratory irritation. May cause drowsiness or dizziness.

PRECAUTIONARY STATEMENTS: Do not use product until all precautionary statements are read and understood. Keep away from sources of ignitions, sparks, heat or flame. No smoking near product or in use. When not in use reseal container lid tightly and store in well ventilated, cool, dry area. Ground all spray equipment, personnel, booth, lighting and ensure explosion proof exhaust fan motors are in use when spray applying. Avoid all source of static electricity. Avoid breathing vapors, always apply in well ventilated area, and wear approved respirator or breather equipment. Use non-sparking tools to open container. Wash hands thoroughly after use and before eating. Do not allow product to reach sewage or any water course. Always wear splash proof goggles when applying product. Always wear (impervious) gloves during use and application of product. Cover all exposed skin during use and application of product. Avoid contact with eyes and skin. In case of fire: Do not use water blast, use CO2, dry chemical or sand. Dispose of product in accordance with local regulations. Remove and dispose of all contaminated clothing.

FIRST AID: If exposed, concerned or feel unwell: Call a physician. IF ON SKIN OR HAIR: Take off immediately contaminated clothing. Rinse skin with water/shower.

If skin irritation or rash occurs: Get medical advice. Take off contaminated clothing and wash it before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.


If eye irritation persists: Get medical advice.

VOC CONTENT: Primer, 179 g/L Regulatory, 100 g/L Actual

KEEP OUT OF THE REACH OF CHILDREN



OSHA HMIS Rating	
Health	2
Flammability	3
Reactivity	0



WARNING:
Cancer and Reproductive Harm – www.P65Warnings.ca.gov


Only in the Event of a Chemical Emergency Involving A Spill, Leaks, Fire, or Exposure Call Chemtrec
Toll Free Day or Night: 1-800-424-9300 International Call Collect: (202) 483-7616

Manufactured for The Eastwood Company, 263 Shoemaker Road, Pottstown, PA 19464
1-800-343-9353 www.eastwood.com © Copyright 2018 Easthill Group, Inc. Made in USA Label #16257ZPL 5/18 Rev 1

RUST ENCAPSULATOR® PLATINUM

Professional Formulation

- 3X Stronger Than Original Rust Encapsulator®
- Metallic Silver Finish
- Apply Directly Over Surface Rust
- Heat Resistant to 350°F
- Apply with Brush or Spray



Scan for product info

DANGER: FLAMMABLE – LIQUID AND VAPOR.
IRRITATING TO THE SKIN AND EYES.
Read Precautions On Rear Panel Before Use.

Net Contents: 1 US GALLON (3.785 liter)

16257ZP