

**MATERIAL SAFETY DATA SHEET**

Date Prepared: 12/20/05

Page: 1 of 5

Flexible Urethane Foam

MSDS Number: 110001

**SECTION 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION****Material Identity**

Product Name: Flexible Urethane Foam

Product Numbers: 20543Z

Product Use: flexible foam

**Distributed By**

The Easthill Group  
dba/ The Eastwood Company  
263 Shoemaker Road  
Pottstown, PA 19464  
USA & Canada: 800-345-1178  
Outside USA: 610-323-2200

**Emergency Telephone Numbers:**

CHEMTREC: 1-800-424-9300

**SECTION 2. COMPOSITION / INFORMATION ON INGREDIENTS**

Ingredient(s)	CAS Number	EINECS Number	% (by weight)
Polyether Polyol	52624-57-4	NE	25-50%
POLYMERIC MDI	Proprietary	NE	25-50%
diphenylmethanediisocyanate, isomers and homologues	9016-87-9	NE	10-25%
POLYETHER POLYOL	Proprietary	NE	10-25%

**SECTION 3. HAZARDS IDENTIFICATION****\*\*\*EMERGENCY OVERVIEW\*\*\***

**DANGER!** Vapor harmful. Overexposure may cause lung damage. May cause allergic skin reaction, effects may be permanent. Combustible liquid and vapor.

**Potential Health Effects****Acute Effects (Short Term):**

**Eye:** Can cause tearing, eye reddening, and swelling and other irritation.

**Skin:** Avoid contact with skin, may cause irritation, sensitization possible through skin contact.

**Swallowing:** harmful if swallowed.

**Inhalation:** High concentrations may irritate respiratory system, may cause sensitization.

**Chronic Effects of Overexposure (Long Term):** Polyisocyanate: as a result of previous exposure, certain individuals develop sensitization which will cause them to react to a later exposure to product at levels well before the TLV. Symptoms include chest tightness, wheezing, cough, shortness of breath or asthma attack. Effect could be immediate or delayed.

**MATERIAL SAFETY DATA SHEET**

Date Prepared: 12/20/05

Page: 2 of 5

Flexible Urethane Foam

MSDS Number: 110001

**Cancer Information:** none anticipated.**Primary Route(s) of Entry:** eye contact, skin contact, inhalation**SECTION 4. FIRST AID MEASURES**

**Eyes:** In case of eye contact, immediately flush eyes with running water for a minimum of 15 minutes. Hold eyelids open during flushing. If irritation persists repeat flushing. Obtain medical attention immediately.

**Skin:** Wash thoroughly with soap and water. If irritation persists, get medical attention.

**Swallowing:** If swallowed, DO NOT induce vomiting. Rinse the mouth. Drink 1-2 glasses of milk to dilute product. Water may be used instead but not as effective. Obtain medical attention immediately.

**Inhalation:** Remove affected person to fresh air. If breathing is difficult, get medical attention.

**SECTION 5. FIRE FIGHTING MEASURES**

**Flash Point:** 250° F (121° C)

**Explosive Limit:** Lower: NA Upper: NA

**Autoignition Temperature:** NA

**OSHA Flammability Class:** Combustible liquid

**Fire and Explosion Hazards:** none known

**Extinguishing Media:** foam, CO2, dry chemicals

**Fire Fighting Instructions:** Water may be used to keep fire-exposed containers cool until fire is out. Wear a self-contained breathing apparatus NIOSH approved with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment.

**\*NFPA Rating:** Health - 2, Flammability - 1, Reactivity - 0

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

**In Case of Spill:** Eliminate all sources of ignition such as flares, flames (including pilot lights), and electrical sparks. Ventilate the area. Wear proper protective equipment (Section 8). Avoid breathing vapors. Collect with an inert absorbent and dispose of properly.

**SECTION 7. HANDLING AND STORAGE**

**Handling:** Do not use in presence of open flame, sparks or ignition sources. Keep away from heat. Avoid breathing vapors and spray mists. Avoid contact with skin and eyes. After handling always wash hands thoroughly with soap and water.

**MATERIAL SAFETY DATA SHEET**

Date Prepared: 12/20/05  
Flexible Urethane Foam

Page: 3 of 5  
MSDS Number: 110001

**Storage:** Keep in a cool, well-ventilated place. Keep away from heat, open flames, sparks and all other sources of ignition. Do not place in hot water or near radiator, stove or other sources of heat. Do not puncture, incinerate, store the container at temperature over 120° F or in direct sunlight.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Eye Protection:** Chemical splash goggles in compliance with OSHA regulations are recommended.

**Skin Protection:** Protective gloves and proper clothing should be worn to prevent skin contact. A barrier cream may be used for additional skin protection. To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

**Respiratory Protection:** Use a NIOSH approved respirator designed to remove particulate matter and organic solvent vapors.

**Engineering Controls:** Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below acceptable limits. Explosion-proof ventilation system is acceptable.

**Exposure Guidelines:** Not available

Hazardous Ingredients	CAS Number	OSHA PEL/TWA	ACGIH TLV
Mppcf- millions of particles per cubic foot of air		N/E-Not Established	

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Boiling Point:</b>	NA	<b>Vapor Density:</b>	NA
<b>Density:</b>	1.08 g/cm <sup>3</sup>	<b>Percent Volatiles by weight:</b>	1.4
<b>Evaporation Rate:</b>	NA	<b>Physical State:</b>	Fluid
<b>Melting Point:</b>	NA	<b>pH:</b>	NA
<b>Odor:</b>	Charateristic	<b>Solubility:</b>	Not Miscuble
<b>Vapor Pressure:</b>	NA	<b>Appearance:</b>	According to product specification
<b>Octanol/Water Partition Coefficient:</b>	NA		

**MATERIAL SAFETY DATA SHEET**

Date Prepared: 12/20/05  
Flexible Urethane Foam

Page: 4 of 5  
MSDS Number: 110001

**SECTION 10. STABILITY AND REACTIVITY**

**Hazardous Polymerization:** no dangerous reactions known.

**Hazardous Decomposition:** no dangerous decomposition products known.

**Chemical Stability:** Stable under normal handling conditions

**Incompatibility:** Avoid contact with strong oxidizing agents, isocyanates, water, alcohol, ammonia and acids.

**SECTION 11. TOXICOLOGICAL INFORMATION**

**Acute Toxicity Data:** not available

**Carcinogenicity:** See section 15

**Mutagenicity:** not available

**Teratogenicity:** not available

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity:** none

**SECTION 13. DISPOSAL CONSIDERATION**

**RCRA Hazardous Waste:** This material as supplied, if discarded, would be regulated as a hazardous waste under RCRA (40 CFR 261). Dispose of in accordance with applicable federal, state, and local regulations.

**RCRA Hazard Class:** This material would be regulated as EPA Hazardous Waste.

**SECTION 14. TRANSPORT INFORMATION**

**DOT Description:** The DOT Classification for shipping is dependant on quantity, type of packaging (a kit may include other components), or method of shipment.

**SECTION 15. REGULATORY INFORMATION****US Federal Regulations****TSCA (Toxic Substances Control Act) Status**

TSCA (USA) The intentional ingredients of this product are listed.

**MATERIAL SAFETY DATA SHEET**

Date Prepared: 12/20/05  
Flexible Urethane Foam

Page: 5 of 5  
MSDS Number: 110001

**CERCLA RQ - 40 CFR 302.4(a)**

None

**SARA Title III: Section 302- Extremely Hazardous Substances**

None

**SARA Title III: Section 313- Toxic Chemical List**

Component	CAS Number	Percentage
Diphenylmethane diisocyanate	9016-87-9	25-50
4,4'-methylenediphenyl diisocyanate	101-68-8	10-25
Methylenediphenyl diisocyanate	26447-40-5	<2.5

**EPA Hazardous Air Pollutants (HAPS) 40 CFR 63**

None

**International Regulations**

**EINECS (Europe)**

**DSL (Canada)**

**WHMIS Classification**

**Health Hazard: D2B**

**Physical Hazard: None**

**State and Local Regulations****California Proposition 65:**

This product contains the following chemical(s) known to the state of California to cause cancer. CARBON BLACK

**SECTION 16. OTHER INFORMATION**

**HMIS Rating:** Health -2\*, Flammability -1, Reactivity - 1  
Key- 0=Least, 1=Slight, 2=Moderate, 3=Serious, 4=Extreme, \*=Chronic Effects

**Other Precautions for Use:**

Additional Information may be obtained by calling the Evercoat MSDS Hotline at 1-800-729-7600.

**NOTICE:** The information accumulated herein is believed to be correct as of the date issued from sources, which are believed to be accurate and reliable. Since it is not possible to anticipate all circumstances of use, recipients are advised to confirm, in advance of need, that the information is current, applicable and suitable to their circumstances.