




DO THE JOB RIGHT.™

3:1 SINGLE-STAGE URETHANE PAINT ACTIVATOR

MEDIUM SPEED: 70°- 80°F



- Medium Speed, 70°- 80°F
- For Use With All Eastwood 3:1 Urethane Paints

FOR PROFESSIONAL USE ONLY

SEE BACK PANEL FOR SAFETY PRECAUTIONS.
KEEP OUT OF REACH OF CHILDREN

One US Quart (0.946 LITERS)

21856ZP

21856ZP

3:1 Single-Stage Urethane Paint Activator

DANGER – Highly flammable liquid and vapor. Harmful if inhaled. Causes serious eye irritation. May cause respiratory irritation, drowsiness or dizziness. May cause an allergic skin reaction.



PRECAUTIONS: Read all warning statements on all labels for this and any other products to be mixed with it prior to use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and other tools or equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust, fumes, gas, mist, vapors or spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, protective clothing and eye protection/face protection. Wear an appropriate, properly fitted fresh-air supplied respirator (NIOSH-approved TC19 or equivalent) during and after application, and until all organic solvent vapors and spray mists are exhausted, or any time airborne contaminant levels exceed exposure limits indicated on the Safety Data Sheet. In case of fire: Use appropriate method to extinguish. Keep container tightly closed. Store locked up, in a cool, well-ventilated place. Dispose of unused amounts and empty container with an approved waste disposal facility only, in accordance with all local, regional and national regulations. Avoid release to environment. If spilled, contain material with inert absorbent, in compliance with local, regional and national regulations.

FIRST AID: IF ON SKIN (or hair): Take off immediately all contaminated clothing and wash before reuse. Wash skin with plenty of water/shower. If skin irritation or rash occurs: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Call a POISON CENTER, doctor or physician if you feel unwell.

CONTENTS: 4-Methyl-2-Pentanone 108-10-1, Homopolymer of Hexamethylene Diisocyanate 28182-81-2, 2-Heptanone 110-43-0, N-Butyl Acetate 123-86-4, 1,2,4-Trimethylbenzene 95-63-6, Light Aromatic Solvent Naphtha (petroleum) 64742-95-6, Xylene 1330-20-7. Contents of this can may contain materials reportable under SARA 313.

REFER TO SAFETY DATA SHEET FOR FURTHER SAFETY AND FIRST AID INFORMATION. FOR PROFESSIONAL USE ONLY.

KEEP OUT OF REACH OF CHILDREN AND PETS AT ALL TIMES. PHOTOCHEMICALLY REACTIVE.

VOC INFORMATION: Coating Category: Component Actual VOC (as supplied): 650 grams/liter (5.42 lbs/gallon). Regulatory VOC (as supplied): 650 grams/liter (5.42 lbs/gallon). Combined system VOC will vary by color, but will not exceed 2.8 lbs/gallon when all components are mixed as directed. See specific VOC details on Single-Stage Urethane Paint label to determine the combined system VOC.

DIRECTIONS FOR USE: SEE PAINT LABEL FOR MIXING AND APPLICATION DIRECTIONS. Keep cap tightly closed at all times. Moisture will contaminate Urethane Activator. Clean all spray equipment immediately after use. Refer to Product Information Sheet for more specific mixing and application directions.

WARRANTY: All recommendations for the use of EASTWOOD products are based on tests and experience believed to be reliable. It is the responsibility of the purchaser to determine the suitability of this product for its intended use. Since the methods of use, conditions of application and the application itself are beyond the manufacturer's and seller's control, product warranty is restricted to replacement of defective materials only. No other warranty, written or oral, is expressed or implied.

OSHA HMIS Rating	
Health	3
Flammability	3
Personal Hazard	1
Personal Protection	X



WARNING: Cancer – www.P65Warnings.ca.gov

Only in the Event of a Chemical Emergency Involving A Spill, Leaks, Fire, or Exposure Call Chemtrec Toll Free Day or Night: 1-800-424-9300 International Call Collect: (202) 483-7616

Manufactured for The Eastwood Company, 263 Shoemaker Road, Pottstown, PA 19464
1-800-343-9353 www.eastwood.com © Copyright 2018 Easthill Group, Inc. Made in USA

