

\*Estimate  
N/A-Not Applicable  
N/R-Not Restricted  
N/E-Not Established

# MATERIAL SAFETY DATA SHEET

<b>NOTE: BLANK SPACES ARE NOT PERMITTED. IF ANY ITEM IS NOT APPLICABLE, THE SPACE MUST BE MARKED TO INDICATE THAT.</b>					
<b>IDENTITY</b> (As shown on Label or package) EASTWOOD FLEXI BLACK COATING			<b>PART NO.</b> IF APPLICABLE 25011Z		
<b>SECTION I</b>					
<b>MANUFACTURED FOR:</b> The Easthill Group dba/ The Eastwood Company			<b>EMERGENCY</b> <b>PHONE No.</b> Chem-Trec 1-800-424-9300		
<b>ADDRESS (NUMBER, STREET, CITY, STATE AND ZIP CODE)</b> 263 Shoemaker Road			<b>REVISION #</b> 0001		
Pottstown, PA 19464			<b>PHONE:</b> USA & Canada: 1-800-345-1178 Outside USA: 610-323-2200		
			<b>DATE MSDS</b> <b>WAS PREPARED</b> April 24, 2006		
<b>SECTION II - HAZARDOUS INGREDIENTS INFORMATION.</b> All Health Hazards which comprise 1% or greater of the composition and all carcinogens if 0.1% of the composition or greater.					
<b>HAZARDOUS COMPONENTS CHEMICAL and IDENTITY AND COMMON NAME (S)</b>	<b>% Wt. (OPTIONAL)</b>	<b>CAS NO.</b>	<b>OSHA PEL</b>	<b>ACGIH TLV</b>	<b>OTHER LIMITS RECOMMEND</b>
Propane	24	74-98-6	1000 ppm	1000 ppm	None
VM&P Naphtha	18	64742-89-8	300 ppm	300 ppm	None
Heptane	13	426260-76-6	500 ppm	400 ppm	None
Xylene	15	1330-20-7	100 ppm	100 ppm	None
N-Butane	11	106-97-8	800 ppm	800 ppm	None
Ethylbenzene	3	100-41-4	100 ppm	100 ppm	None
Methyl n-Amyl Ketone	3	110-43-0	100 ppm	50 ppm	None
<b>SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS</b>					
<b>BOILING POINT</b> <0 – 325 °F	<b>SPECIFIC GRAVITY</b> (H <sub>2</sub> O =1) 0.67		<b>APPROXIMATE WEIGHT PER GALLON (LBS)</b> 5.59		
<b>VAPOR PRESSURE</b> 760 mm Hg @ 20 °C	<b>VAPOR DENSITY</b> (AIR = 1) Heavier than Air		<b>EVAPORATION RATE</b> (BUTYL ACETATE =1) >1.0		
<b>SOLUBILITY IN WATER</b> N/A	<b>% VOLATILE</b> 87%		<b>OTHER</b> (IF ANY)		
<b>APPEARANCE AND ODOR</b> Various colors, syrupy liquid, with solvent odor					
<b>SECTION IV-FIRE AND EXPLOSION HAZARD DATA</b>					
<b>FLASH POINT</b> Propellant < 0 °F		<b>FLAMMABLE LIMITS</b>	<b>LEL</b> 0.9	<b>UEL</b> 9.5	
<b>EXTINGUISHING MEDIA</b> Carbon Dioxide, Dry Chemical, or Foam					
<b>SPECIAL FIRE FIGHTING PROCEDURES</b> Self contained breathing apparatus with a full face piece, operated in pressure demand or other positive pressure mode.					
<b>UNUSUAL FIRE AND EXPLOSION HAZARDS</b> This material is flammable and may be ignited by heat, sparks, flame or static electricity. Level 3 aerosol (NFPA 30B). Contents under pressure if heated over 120°F aerosol can could explode, even when empty.					
<b>HAZARDOUS PRODUCTS FORMED BY FIRE OR THERMAL DECOMPOSITION</b> Carbon Dioxide and/or Carbon Monoxide and unidentifiable organic materials.					
<b>EXPLOSIVE LIMITS</b> (% BY VOLUME IN AIR) 0.9 – 9.5					
<b>SECTION V - OPTIONAL HAZARD RATINGS IDENTIFICATION</b>					
<b>HAZARD RATING</b> 4-EXTREME 3-HIGH 2-MODERATE 1-SLIGHT 0-INSIGNIFICANT **SEE SECTION IV		<b>National Fire Protection Association (NFPA)</b>  <b>FIRE</b> <u>4</u> <b>REACTIVITY</b> <u>0</u> .  <b>HEALTH</b> <u>2</u> <b>SPECIAL HAZARDS</b> <u>NONE</u>			

<b>SECTION VI - REACTIVITY AND STABILITY DATA</b>			
<b>STABILITY</b>		UNSTABLE      STABLE X	
INCOMPATIBILITY (Materials to Avoid) Strong acids, bases, oxidizing agents, selected amines with alkali metals and halogens.			
HAZARDOUS DECOMPOSITION OR BY PRODUCTS Carbon Monoxide and/or Carbon Dioxide			
<b>HAZARDOUS POLYMERIZATION</b>		MAY OCCUR WILL NOT OCCUR X	<b>CONDITIONS TO AVOID</b> Avoid contact with heat, sparks, and open flame. Product may explode if heated.
<b>SECTION VII - HEALTH HAZARD DATA</b>			
<b>ROUTES OF ENTRY</b>		INHALATION? YES	SKIN? YES      INGESTION? YES      EYES? YES
<b>HEALTH HAZARDS</b>	ACUTE	X	
	CHRONIC	X	
<b>CARCINOGENICITY:</b>		IARC 2B	
<b>SIGNS AND SYMPTOMS OF EXPOSURE</b>		Headache, Dizziness, Drowsiness, Fatigue, Irregular Heartbeat, Skin and Eye Irritation.	
<b>MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE</b>			
<b>EMERGENCY AND FIRST AID PROCEDURES</b>		Ingestion: Contact Physician or Poison Control Immediately. Inhalation: Remove to fresh air. Administer Oxygen or Artificial Respiration if Necessary. Eye Contact: Flush with large amounts of water. If irritation persists, contact Physician. Skin: Wash with soap and water.	
<b>SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE</b>			
<b>STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED</b>		Wipe up with floor absorbent. Transfer to hood. Prevent run-off to sewers. Eliminate all sources of ignition. Ventilate to maintain exposure below PEL's.	
<b>WASTE DISPOSAL METHODS</b>		Dispose of product in accordance with local, county, state and federal regulations.	
<b>PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE</b>		Keep away from sparks, flames, and heat sources. Do Not store above 120°F Level 3 aerosol (NFPA 30B).	
<b>OTHER PRECAUTIONS</b>		Keep Container Closed When Not In Use. Store this product with adequate ventilation in cool areas. Never place aerosol in flame or fire, Even when Empty.	
<b>SECTION IX - CONTROL MEASURES</b>			
<b>RESPIRATORY PROTECTION (SPECIFY TYPE)</b> Depending on the Airborne concentration, use a Respirator with appropriate NIOSH approved cartridge or supplied air equipment.			<b>PROTECTIVE GLOVES</b> Impervious
<b>VENTILATION</b>	<b>LOCAL EXHAUST</b> Supplemental (if needed)		<b>SPECIAL</b> None
	<b>MECHANICAL (GENERAL)</b> To maintain exposure below PEL's		<b>OTHER</b> None
<b>EYE PROTECTION</b> Chemical splash goggles or approved eye protection.			<b>OTHER PROTECTIVE CLOTHING OR EQUIPMENT</b> Chemical Apron/Eye bath/Safety Shower
<b>WORK HYGIENIC PRACTICES</b> Wash thoroughly after handling.			
<b>SECTION X - TRANSPORTATION INFORMATION</b>			
<b>DOT PROPER SHIPPING NAME</b> Aerosols		<b>DOT HAZARD CLASS</b> 2.1	
<b>DOT UN NUMBER</b> UN1950		<b>DOT PACKING GROUP</b> N/A	
<b>IATA PROPER SHIPPING NAME</b> Aerosols, flammable		<b>IATA HAZARD CLASS</b> 2.1	
<b>IATA UN NUMBER</b> UN1950		<b>IATA PACKING GROUP</b> N/A	
<b>SECTION XI - 313 SUPPLIER NOTIFICATION</b>			
<b>THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS SUBJECT TO REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT -TO-KNOW ACT OF 1986, 40 CFR 372, (see table on page 1 for CAS # and percent by weight).</b> Xylene and Ethylbenzene			
<b>WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM.</b>			

This is the "back" when printed in duplex. Page 2 of 2 pages if not duplex.

Prepared By: Andrew Stooksbury