

Eastwood[®]

DO THE JOB RIGHT.[®]

Item #31475

DAMAGED LUG NUT REMOVAL SOCKETS

INSTRUCTIONS



The **EASTWOOD DAMAGED LUG NUT REMOVAL SOCKETS** fit three of the most popular sized lug nuts in 17mm, 19mm & 21mm dimensions by cutting into rounded hex surfaces (will also fit 5/8", 3/4" & 13/16" dimensions).

SAFETY INFORMATION

The following explanations are displayed in this manual, on the labeling, and on all other information provided with this product:

DANGER

DANGER indicates a hazardous situation which, if not avoided, will result in death or serious injury.

WARNING


WARNING indicates a hazardous situation which, if not avoided, could result in death or serious injury.

CAUTION

CAUTION used with the safety alert symbol, indicates a hazardous situation which, if not avoided, could result in minor or moderate injury.

NOTICE

NOTICE is used to address practices not related to personal injury.



READ INSTRUCTIONS

- Thoroughly read and understand these product instructions before using the Damaged Lug Nut Removal Sockets.
- Keep these product instructions for future reference.



WARNING IMPROPER MOTOR VEHICLE REPAIR WORK CAN RESULT IN INJURY OR DEATH!

- Performing automotive repair work can cause injury, death and vehicle accidents. DO NOT attempt to use this tool or begin work without proper training and a thorough understanding of motor vehicle mechanical systems.



WARNING IMPROPER VEHICLE JACKING CAN RESULT IN INJURY OR DEATH!

- Always consult an authorized manufacturer's service manual or reference materials on the particular vehicle under repair for the proper jacking procedures.



⚠ WARNING CUT HAZARD!

- Produces sharp edges. Wear heavy work gloves while handling Removal Sockets and damaged lug nuts.



⚠ CAUTION EYE INJURY HAZARD!

- Chips or particles may be ejected from components causing eye injury. Wear ANSI approved eye protection while using.



⚠ CAUTION FALL HAZARD!

- Components may suddenly shift while being operated. Failure to ensure proper footing can quickly result in a fall which could inflict serious personal injury or property damage.

OPERATION:

- Select the Removal Socket that fits the damaged lug nut to be removed.
- Place Removal Socket over damaged lug nut and remove in normal way.

NOTE:

- Use of the matching size Removal Socket may round off damaged lug nut corners causing Removal Socket to spin freely. Should this occur, use the next smallest Removal Socket size.
- Use to remove lug nuts that employ right-hand thread only.
- Do Not use to tighten lug nuts.
- Do Not re-use lug nuts that have been removed using this tool.

If you have any questions about the use of this product, please contact

The Eastwood Technical Assistance Service Department: 800.343.9353 >> email: techelp@eastwood.com

PDF version of this manual is available online >> eastwood.com/31475manual

The Eastwood Company 263 Shoemaker Road, Pottstown, PA 19464, USA

US and Canada: 800.343.9353 Outside US: 610.718.8335

Fax: 610.323.6268 eastwood.com