

MATERIAL SAFETY DATA SHEET

Distributed by:

The Easthill Group dba/ The Eastwood Company

263 Shoemaker Road, Pottstown, PA 19464

USA & Canada: 800-345-1178

Outside USA: (610) 323-2200

Emergency Contact: Chem-Trec 800-424-9300

PRODUCT IDENTIFICATION**REVISION DATE: 07/01/09**

IDENTITY: (As used on label)	Synonyms:
Auto Air Semi- Opaque Process Blue Item # 34353 (001, 002, 003 & 004)	
Chemical family:	Formula

HAZARDOUS INGREDIENTS

COMPONENT	CAS #	%	OSHA/PEL
Proprietary Ingredient	Not specified	75-95	Not established
Methoxy 2	107-98-2	<1	100 PPM
Methoxy 1	1589-47-5	< .05	150 PPM

PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling /melting point: 408°F (209° C)
Solubility in water: Appreciable (>20%)
Vapor pressure (mm Hg): <0.2 mm Hg @ 20° C
Vapor density: (Air=1) 6.6
Specific Gravity (H₂O-1): (Water=1) 0.972
Evaporation Rate: (BuAct=1): .07
Appearance and Odor: Colorless liquid, combustible, sweet ether odor
Flash Point: 79° C / 174°F

Volatile Organic Compound

*Paint 80%: .92
**Reducer 20% : .61
Combined VOC: 1.53

*Paint can be sprayed without reduction

**Refer to Colors for combined VOC

FIRE AND EXPLOSION HAZARD DATA

Extinguisher Media: Water, CO ₂ foam, water fog, dry chemical, chemical foam
Fire fighting Procedures: Self-contained respiratory equipment; cool container to prevent pressure buildup and possible explosion when exposed to extreme heat. Caution- material is combustible!
Unusual Fire and Explosion Hazards: Closed containers can explode due to buildup of pressure when exposed to extreme heat

REACTIVITY DATA

Stability: (X) Stable () Unstable	Conditions to avoid: extreme temperatures, open flames
--	---

Incompatibility (materials to avoid) : strong oxidizers, strong acids
Hazardous Decomposition or Byproducts: Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.
Hazardous Polymerization: () may occur (X) will not occur Conditions to avoid: None

HEALTH INFORMATION

Primary Route of Exposure:			
Inhalation:	Skin: X	Ingestion:	Eyes:
Carcinogen:	IARC: no	NTP: no	OSHA: no
Signs and Symptoms of Exposure: none found			
Medical Conditions Generally Aggravated by Exposure: none found			
Emergency and First Aid Procedures: <u>Eye Contact</u> , remove contact lenses. Flush with water for 15 min. and consult physician if irritation persists. <u>Ingestion</u> , If victim is conscious give water, <i>do not</i> induce vomiting. Call physician.			

SPECIAL PROTECTION DATA

Respiratory Protection: Respiratory protection equipment is required under normal conditions of anticipated use with adequate ventilation. , wear a NIOSH/MSHA approved respirator.
Ventilation: The use of local exhaust ventilation is recommended to control emissions near the source. Provide mechanical ventilation of confined spaces. Use explosion proof ventilation equipment.
Protective Gloves: Neoprene or rubber gloves with cuffs
Other Protective Clothing: Coveralls, apron, or other equipment should be worn to minimize skin contact. Where use can result in skin contact, wash thoroughly before eating, drinking, or smoking.

SPILL AND LEAK PROCEDURES

Steps to be taken in case of material spill: COMBUSTIBLE-Evacuate and ventilate area: remove all sources of sparks, ignition, and open flames; confine and absorb into approved absorbent; place material into approved containers for disposal; do not wash to sewer or waterway.
Storing/Handling: Store in tightly closed containers in a cool, well-ventilated area.
Waste Disposal Method: Sanitary landfill in accordance with local, state, and federal regulations. Other Precautions: None