

Distributed By:
The Easthill Group dba/ The Eastwood Company
263 Shoemaker Road, Pottstown, PA 19464
USA & Canada: 800-345-1178
Outside USA: 610-323-2200
Emergency Contact: Chem-Trec 800-424-9300

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: DASHBOARD REPAIR KIT
Item No: 40013
Product Type: Sealant

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%.	ACGIH; TLV-TWA	OSHA PEL
ACETONE 67-64-1	40-50	500 ppm; 1188 mg/m3	1000 ppm TWA; 2400 mg/m3 TWA
TETRAHYDROFURAN 109-99-9	20-30	50 ppm TWA ACGIH	200 ppm TWA; 590 mg/m3 TWA
VINYL COPOLYMER 9003-22-9	15-25	Not listed	Not listed
BENZOATE ESTERS MIXTURE	<10	Not listed	Not listed
SILICON DIOXIDE, AMORPHOUS 112945-52-5	<5	5 mg/m3, TWA	6 mg/m3 TWA

3. HAZARDS IDENTIFICATION

Toxicity: This material is irritating to skin, eyes and mucous membranes.. Note: This product does not contain microcrystalline silica.

Primary Routes of Entry: Eye and skin contact, ingestion, inhalation

Signs and Symptoms of Exposure: Skin: Exposure may cause mild skin irritation. Prolonged or repeated exposure may dry the skin.

Symptoms may include redness, burning, drying, cracking and skin burns. Preexisting skin disorders may be aggravated by exposure. Skin absorption is possible, but harmful effects are not expected from this route under normal conditions of handling and use. Excessive overexposure may cause giddiness, dizziness, headache, nausea and in extreme cases, unconsciousness and respiratory depression. Inhaling may cause mild irritation to the nose, throat and respiratory tract and may result in central nervous system (CNS) depression

Component	Weight%	NTP	ACGIH Carcinogens	IARC
ACETONE 67-64-1	40-50	Not known	A4 - Not Classifiable as a Human Carcinogen	
TETRAHYDROFURAN 109-99-9	20-30	male rat-some evidence; female ratno evidence; male mice-no evidence; female mice-clear evidence	A3 Confirmed animal carcinogen with unknown relevance to humans	
VINYL COPOLYMER 9003-22-9	15-25			Group 3 Supplement 7, 1987; Monograph 19, 1979
SILICON DIOXIDE, AMORPHOUS 112945-52-5	<5			Amorphous Silica, Group 3: Vol. 68: 1997

**Medical Conditions Recognized as
Being Aggravated by Exposure:**

Preexisting pulmonary and dermatological disorders.

4. FIRST AID MEASURES

Ingestion: Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Oxygen or artificial respiration if needed. Obtain medical attention.

Skin Contact: Wash off with soap and water. If skin irritation persists, call a physician.

4. FIRST AID MEASURES

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point °F(C°): 0°F TCC

Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.

Special Fire-Fighting Procedures: Firefighters should wear self-contained breathing apparatus. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.

Hazardous Products of Combustion: Hydrogen chloride, Irritating vapors, Oxides of carbon, Oxides of phosphorus

Unusual Fire/Explosion Hazards: Vapors may travel from container toward sources of ignition and flashback.

Lower Explosive Limit: Acetone: 2.6; tetrahydrofuran: 2

Upper Explosive Limit: Acetone: 12.8; tetrahydrofuran: 11.8

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE

Storage: Store away from heat, sparks or open flame. Do not store at temperatures above 120 degrees F.

Handling: Avoid breathing vapors, if exposed to high vapor concentration, leave area at once. Avoid contact with skin and eyes. Do not use near heat, sparks or open flame. Keep container closed when not in use. Use only in a well ventilated area. Wash hands before eating, drinking, chewing gum, using tobacco or using the toilet.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses.

Skin: Neoprene or nitrile gloves recommended.

Ventilation: General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.

Respiratory Protection: An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear liquid

Odor: Pungent

Boiling Point: 135°F

pH: Does not apply

Solubility in Water: Slight

Specific Gravity: 0.94

VOC Content(Wt.%): 25% by weight

Vapor Pressure: Not Determined

Vapor Density (Air=1): >1

Evaporation Rate: Not Determined

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at normal conditions

Hazardous Polymerization: WILL NOT OCCUR.

Incompatibilities: Strong oxidizers, Acids, Reducing agents

Conditions to Avoid: Keep away from heat, sparks and open flame. - No smoking

Hazardous Products of Combustion: Hydrogen chloride, Irritating vapors, Oxides of carbon, Oxides of Phosphorus

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations.

US EPA Waste Number: D001 as per 40CFR 261.21

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Domestic Ground Transport

DOT Shipping Name: Consumer Commodity (not more than one liter)

Hazard Class: ORM-D

UN/ID Number: None

IATA

Proper Shipping Name: Consumer Commodity (Not more than 1 liter)

Class or Division: Class 9

UN/ID Number: ID 8000

IMDG

Proper Shipping: Adhesives containing flammable liquid, Limited Quantity

Hazard Class: Class 3, PG II

UN Number: UN 1133

Marine Pollutant: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.
None

CALIFORNIA PROP 65:

No California Prop 65 chemicals are known to be present at or above the No Significant Risk Level.

TSCA Inventory Status:

Listed on Inventory: YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 3, REACTIVITY 1.

Estimated HMIS Classification: HEALTH 2, FLAMMABILITY 3, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Lifetime Repair Corporation

3985 Eastern Rd

Norton, Oh 44203

Telephone:330-706-9791

Revision Date: March/01/2008