

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/31/2008

Reviewed on 01/31/2008

## 1 Identification of substance

### · Product details

· **Trade name:** 50106Z - Urethane Bumper Stripper Aerosol

· **Article number:** 39913

### · Distributed by:

The Easthill Group  
dba/ The Eastwood Company  
263 Shoemaker Road  
Pottstown, PA 19464

### · Information department:

USA & Canada: 800-345-1178  
Outside USA: (610) 323-2200










· **Emergency information:** 24 HR EMERGENCY CHEMTREC 1-800-424-9300

## 2 Composition/Data on components

### · Chemical characterization

· **Description:** Mixture of the substances listed below with nonhazardous additions.

### · Dangerous components:

75-09-2	dichloromethane	Warning:  3.6/2	50-75%
68476-86-8	Petroleum gases, liquefied, sweetened	Danger:  2.2/1 Warning:  2.5/C	10-25%
67-63-0	propan-2-ol	Danger:  2.6/2 Warning:  3.3/2A, 3.8/3	2.5-10%
64742-88-7	Solvent naphtha (petroleum), medium aliph.	Danger:  3.10/1 Warning:  2.6/3	1-2.5%
141-43-5	2-aminoethanol	Danger:  3.2/1C Warning:  3.1.1/4, 3.8/3; 2.6/4	1-2.5%

## 3 Hazards identification

### · Hazard description:



Harmful  
Extremely flammable

### · Information pertaining to particular dangers for man and environment:

The product has to be labelled due to the calculation procedure of international guidelines.

Warning! Pressurized container.

Extremely flammable.

Irritating to eyes, respiratory system and skin.

Limited evidence of a carcinogenic effect.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

Buildup of explosive mixtures possible without sufficient ventilation.

Keep out of the reach of children.

(Contd. on page 2)

USA

**Material Safety Data Sheet**  
acc. to ISO/DIS 11014

Printing date 01/31/2008

Reviewed on 01/31/2008

**Trade name: 50106Z - Urethane Bumper Stripper Aerosol**

(Contd. of page 1)

**· Classification system:**

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

**· NFPA ratings (scale 0 - 4)**

Health = 2

Fire = 4

Reactivity = 0

**· HMIS-ratings (scale 0 - 4)**

Health = 2

Fire = 4

Reactivity = 0

**· GHS label elements****Danger**

2.2/1 - Extremely flammable gas.

2.3/1 - Extremely flammable aerosol.

**Warning**

3.6/2 - Suspected of causing cancer.

**Warning**

3.2/2 - Causes skin irritation.

3.3/2A - Causes serious eye irritation.

3.8/3 - May cause respiratory irritation.

**· Prevention:**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Use personal protective equipment as required.

**· Response:**

IF ON SKIN: Wash with plenty of soap and water.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a POISON CENTER or doctor/physician if you feel unwell.

Specific treatment (see label).

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

(Contd. on page 3)

**Material Safety Data Sheet**  
**acc. to ISO/DIS 11014**

Printing date 01/31/2008

Reviewed on 01/31/2008

**Trade name: 50106Z - Urethane Bumper Stripper Aerosol**

(Contd. of page 2)

Take off contaminated clothing and wash before reuse.  
Leaking gas fire: Do not extinguish, unless leak can be stopped safely.  
Eliminate all ignition sources if safe to do so.

**· Storage:**

Store in a well-ventilated place.  
Store in a well-ventilated place. Keep container tightly closed.  
Store locked up.  
Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.

**· Disposal:**

Dispose of contents/container in accordance with local/regional/national/international regulations.

**4 First aid measures**

- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.

**5 Fire fighting measures**

- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Protective equipment:** No special measures required.

**6 Accidental release measures**

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:** Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents

**7 Handling and storage**

- **Handling:**
- **Information for safe handling:**  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.
- **Information about protection against explosions and fires:**  
Do not spray on a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

(Contd. on page 4)

USA

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/31/2008

Reviewed on 01/31/2008

Trade name: 50106Z - Urethane Bumper Stripper Aerosol

(Contd. of page 3)

- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Do not gas tight seal receptacle.  
Store in cool, dry conditions in well sealed receptacles.  
Protect from heat and direct sunlight.

## 8 Exposure controls and personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Components with limit values that require monitoring at the workplace:**

### 75-09-2 dichloromethane

PEL	Short-term value: 125 ppm Long-term value: 25 ppm see 29 CFR 1910.1052
REL	LFC
TLV	174 mg/m <sup>3</sup> , 50 ppm BEI

### 67-63-0 propan-2-ol

PEL	980 mg/m <sup>3</sup> , 400 ppm
REL	Short-term value: 1225 mg/m <sup>3</sup> , 500 ppm Long-term value: 980 mg/m <sup>3</sup> , 400 ppm
TLV	Short-term value: 984 mg/m <sup>3</sup> , 400 ppm Long-term value: 492 mg/m <sup>3</sup> , 200 ppm BEI

### 141-43-5 2-aminoethanol

PEL	6 mg/m <sup>3</sup> , 3 ppm
REL	Short-term value: 15 mg/m <sup>3</sup> , 6 ppm Long-term value: 8 mg/m <sup>3</sup> , 3 ppm
TLV	Short-term value: 15 mg/m <sup>3</sup> , 6 ppm Long-term value: 7.5 mg/m <sup>3</sup> , 3 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.
- **Breathing equipment:**  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 5)

USA

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/31/2008

Reviewed on 01/31/2008

Trade name: 50106Z - Urethane Bumper Stripper Aerosol

(Contd. of page 4)

## · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

## · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

## · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

## · Eye protection:



Tightly sealed goggles

## 9 Physical and chemical properties

### · General Information

**Form:** Aerosol  
**Color:** According to product specification  
**Odor:** Characteristic

### · Change in condition

**Melting point/Melting range:** Undetermined.  
**Boiling point/Boiling range:** < -17°C (< 1°F)

**Flash point:** < -17°C (< 1°F)

**Ignition temperature:** 425°C (797°F)

**Auto igniting:** Product is not selfigniting.

**Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.

### · Explosion limits:

**Lower:** 1.9 Vol %  
**Upper:** 22.0 Vol %

**Vapor pressure at 20°C (68°F):** 453 hPa (340 mm Hg)

**Density at 20°C (68°F):** 0.99 g/cm<sup>3</sup>

### · Solubility in / Miscibility with

**Water:** Not miscible or difficult to mix.

### · Solvent content:

**Organic solvents:** 95.0 %

(Contd. on page 6)

USA

**Material Safety Data Sheet**  
**acc. to ISO/DIS 11014**

Printing date 01/31/2008

Reviewed on 01/31/2008

**Trade name: 50106Z - Urethane Bumper Stripper Aerosol**

(Contd. of page 5)

<b>Water:</b>	5.0 %
<b>VOC content:</b>	28.0 %
	277.0 g/l / 2.31 lb/gal

**10 Stability and reactivity**

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous products of decomposition:** No dangerous decomposition products known.

**11 Toxicological information**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

**75-09-2 dichloromethane**

Oral	LD50	1600 mg/kg (rat)
Inhalative	LC50/4 h	88 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant

**12 Ecological information**

- **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.

**13 Disposal considerations**

- **Product:**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

USA

(Contd. on page 7)

**Material Safety Data Sheet**  
acc. to ISO/DIS 11014

Printing date 01/31/2008

Reviewed on 01/31/2008

Trade name: 50106Z - Urethane Bumper Stripper Aerosol

(Contd. of page 6)

**14 Transport information**

## · DOT regulations:



- Hazard class: 2.1
- Identification number: UN1950
- Packing group: -
- Proper shipping name (technical name): AEROSOLS, flammable, containing substances in Division 6.1, Packing Group I or II
- Label: 2.1+6.1
- Remarks: ORM-D

## · Land transport TDG (Canada) and ADR/RID (Europe):



- Hazard class: 2 5TF Gases
- UN-Number: 1950
- Packaging group: -
- Label: 2.1+6.1
- Description of goods: 1950 AEROSOLS

## · Maritime transport IMDG:



- IMDG Class: 2.1
- UN Number: 1950
- Label: 2.1+6.1
- Packaging group: -
- EMS Number: F-D,S-U
- Marine pollutant: No
- Proper shipping name: AEROSOLS

## · Air transport ICAO-TI and IATA-DGR:



- ICAO/IATA Class: 2.1
- UN/ID Number: 1950
- Label: 2.1+6.1
- Packaging group: -
- Proper shipping name: AEROSOLS, flammable, containing substances in Division 6.1, Packing Group I or II

(Contd. on page 8)

USA

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/31/2008

Reviewed on 01/31/2008

Trade name: 50106Z - Urethane Bumper Stripper Aerosol

(Contd. of page 7)

· UN "Model Regulation": UN1950; AEROSOLS; 2.1 (6.1); -

## 15 Regulations

## · Sara

## · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

## · Section 313 (Specific toxic chemical listings):

75-09-2 dichloromethane

67-63-0 propan-2-ol

## · TSCA (Toxic Substances Control Act):

All ingredients are listed.

## · Proposition 65

## · Chemicals known to cause cancer:

75-09-2 dichloromethane

## · Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

## · Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

## · Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

## · Cancerogenity categories

## · EPA (Environmental Protection Agency)

75-09-2 dichloromethane

B2

## · IARC (International Agency for Research on Cancer)

75-09-2 dichloromethane

2B

67-63-0 propan-2-ol

3

## · NTP (National Toxicology Program)

75-09-2 dichloromethane

R

## · TLV (Threshold Limit Value established by ACGIH)

75-09-2 dichloromethane

A3

## · NIOSH-Ca (National Institute for Occupational Safety and Health)

75-09-2 dichloromethane

## · OSHA-Ca (Occupational Safety &amp; Health Administration)

75-09-2 dichloromethane

## · Product related hazard informations:

The product has been classified and marked in accordance with directives on hazardous materials.

## · Hazard symbols:

Harmful

Extremely flammable

## · Hazard-determining components of labelling:

dichloromethane

(Contd. on page 9)

USA



**Material Safety Data Sheet**  
**acc. to ISO/DIS 11014**

Printing date 01/31/2008

Reviewed on 01/31/2008

**Trade name: 50106Z - Urethane Bumper Stripper Aerosol**

(Contd. of page 8)

**· Risk phrases:***Extremely flammable.**Irritating to eyes, respiratory system and skin.**Limited evidence of a carcinogenic effect.***· Safety phrases:***Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).**Wear suitable protective clothing, gloves and eye/face protection.**Use only in well-ventilated areas.**This material and its container must be disposed of as hazardous waste.***· Special labeling of certain preparations:***Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.**Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.**Buildup of explosive mixtures possible without sufficient ventilation.**Keep out of the reach of children.***16 Other information**

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

**· Department issuing MSDS:** Environment protection department.**· Contact:** Steve Gaver**· Abbreviations and acronyms:**

*ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*

*RID: Reglement internationale concernent le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*

*IMDG: International Maritime Code for Dangerous Goods*

*DOT: US Department of Transportation*

*IATA: International Air Transport Association*

*IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)*

*ICAO: International Civil Aviation Organization*

*ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)*

*GHS: Globally Harmonized System of Classification and Labelling of Chemicals*

*ACGIH: American Conference of Governmental Industrial Hygienists*

*NFPA: National Fire Protection Association (USA)*

*HMIS: Hazardous Materials Identification System (USA)*

*VOC: Volatile Organic Compounds (USA, EU)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*