
MATERIAL SAFETY DATA SHEET

1. PRODUCT AND PREPARATION INFORMATION

Distributed By: The Easthill Group
dba/ The Eastwood Company
263 Shoemaker Road
Pottstown, PA 19464
USA & Canada: 800-345-1178
Outside USA: 610-323-2200

Emergency Contact: Chem-Trec 800-424-9300

Product Name: Shake and Shoot, Part A
Product Code: BSSBLA
Synonyms: Not Applicable
Chemical Family: Organic Solvents, Resins
Molecular Formula: Mixture
Product Use: Truck Bed Liner Coating
Prepared by: Regulatory Department
Preparation Date: August 8, 2007

2. HAZARDOUS INGREDIENTS

Hazardous Ingredients	CAS Number	Wt. %	TLV ppm	LD/50 Route, Species	LC/50 Route, Species
Xylene	1330-20-7	15-40	100	4,300 mg/Kg (ORL-RAT) > 2,000 mg/Kg (DRML-RBT)	5,000 ppm/4H (RAT)
Acetone	67-64-1	10-30	500	5,800 mg/Kg (ORL-RAT) > 2,000 mg/Kg (DRML-RBT)	33,100 ppm/4H (RAT)

2. HAZARDOUS INGREDIENTS (CONTINUED)

Hazardous Ingredients	CAS Number	Wt. %	TLV ppm	LD/50 Route, Species	LC/50 Route, Species
Toluene	108-88-3	3-7	50	5,500 mg/Kg (ORL-RAT) 14,000 mg/Kg (DRML-RBT)	8,000 ppm/4H (RAT)
Ethylbenzene	100-41-4	1-5	Not Available	3,500 mg/Kg (ORL-RAT) 15,400 mg/Kg (DRML-RBT)	4,000 ppm/4H (RAT)
1-methoxy-2-propanol acetate	108-65-6	1-5	Not Available	8,532 mg/Kg (ORL-RAT) 5,000 mg/Kg (DRML-RBT)	4,345 ppm/4H (RAT)

3. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid
Appearance	Black
Odour	Mild Solvent
Odour Threshold	Not Available
Boiling Point (Deg.C)	57 (Start)
Melting/Freezing Point (Deg. C)	Not Available
Vapour Density (Air = 1)	> 1
Specific Gravity	1.10
Vapour Pressure (mm Hg)	Not Available
VOC, A & B kit mixed	2.97 lbs/gal (356 g/L)

3. PHYSICAL AND CHEMICAL PROPERTIES (CONTINUED)

PH	Not Applicable
Solubility in Water	Slight

4. FIRE AND EXPLOSION HAZARD

Flammability:	Yes
If Yes, Under Which Conditions:	Excessive heat, sparks and open flame.
Flammability Limits in Air (%):	1.0 - 7.0
Flash Point (TCC deg.C)	- 18
Autoignition Temperature (Deg. C):	Not available.
Hazardous Combustion Products:	Carbon monoxide.
Sensitivity to Mechanical Impact:	Not available. Not expected to be sensitive to mechanical impact.
Rate of Burning:	Not available.
Explosive Power:	Not available.
Sensitivity to Static Discharge:	Not available. Expected to be sensitive to static discharge when vapours in air are between the flammability limits.
Extinguishing Media:	Carbon Dioxide, dry chemicals, foam, water fog. In case of large fire cool containers with water jet in order to prevent pressure build up, autoignition or explosion.

5. REACTIVITY DATA

Chemical Stability:	Yes, under normal conditions.
Compatibility with Other Substances:	No, with strong acids, alkalis and oxidizing agents.
Hazardous Products of Decomposition:	Carbon monoxide.
Hazardous Polymerisation:	Will not occur.

6. TOXICOLOGICAL PROPERTIES

Route of Entry:	
Skin Contact:	Yes
Skin Absorption:	Yes
Eye Contact:	Yes
Inhalation:	Yes
Ingestion:	Yes
Effects of Exposure:	Inhalation of large amounts of product may be harmful, may be associated with cardiac arrhythmias. Material and its vapors are irritating to eyes, nose, throat and respiratory tract. May cause defatting, drying and cracking of the skin. Prolonged and repeated contact may lead to dermatitis. Swallowing may lead to nausea and diarrhea.
Carcinogenicity of material:	Ethylbenzene has been shown to cause cancer in laboratory animals. The relevance of this finding to humans is uncertain. The IARC has classified Ethylbenzene as a possible human carcinogen.
Reproductive effects:	Toluene may be harmful to the human fetus based on positive test results with laboratory animals. Case studies show that prolonged intentional abuse of Toluene during pregnancy can cause birth defects in humans.
Teratogenicity:	No information is available and no adverse Teratogenic effects are anticipated.
Mutagenicity:	No information is available and no adverse Mutagenic effects are anticipated.

7. PREVENTIVE MEASURES

Eye Protection:	Use chemical safety goggles with side shields.
Skin Protection:	Rubber gloves.
Respiratory Protection:	If exposure exceeds occupational limits, wear a NIOSH approved air-purifying respirator with organic vapour cartridges for mists and vapours.
Engineering Controls:	Good general ventilation. Exhaust ventilation is recommended if used indoors on continuous basis.

Leak/Spill Clean-Up Procedures:	Ventilate enclosed spaces. Collect product for disposal. Do not use combustible materials such as sawdust as an absorbent. Eliminate all sources of ignition. Notify applicable government authority if release is reportable or could adversely affect the environment.
Storage Instructions:	Keep away from heat, sparks, and open flames.

8. FIRST AID MEASURES

In case of eye contact, immediately flush eyes with running water for a minimum of 15 minutes. Hold eyelids open during flushing. If irritation persists, repeat flushing. Obtain medical attention IMMEDIATELY. For skin, wash thoroughly with soap and water. If irritation develops, get medical attention. If affected by inhalation of vapour or spray mist, move to fresh air. If swallowed, do not induce vomiting. Obtain medical attention IMMEDIATELY.

9. TRANSPORT INFORMATION

Proper Shipping Name:	Coating Solution
UN Number:	1139
Class or Division:	3
Sub Risk:	Not Applicable
Packing Group:	II

10. REGULATORY INFORMATION

WHMIS Classification:	B2, D2A, D2B
-----------------------	--------------

11. OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR. **This MSDS is valid for three years.**

The information contained herein is based on data considered accurate. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Dominion Sure Seal assumes no responsibility for personal injury or property damage to vendees or users or third parties, caused by the material. Such vendees or users assume all risks with the use of the material.