

MATERIAL SAFETY DATA SHEET

50457ZB EW STAINLESS STEEL EPOXY CATALYST PART B

Printed: 10/11/08

```

=====
----- HMIS CODES -----
Hazard Rating:      Health      3
Least --> Greatest  Flammability 3
0 --> 4             Reactivity   1
Manufacturer:      Personal Protection J
THE EASTWOOD COMPANY
263 SHOEMAKER ROAD
POTTSTOWN, PA 19464
Phone: 800-345-1178
EMERGENCY TELEPHONE: 800-424-9300
=====

```

SECTION I: PRODUCT IDENTIFICATION

```

-----
Product Code: 50457ZB           Product Class: PAINT
Product Name:  EW STAINLESS STEEL EPOXY CATALYST PART B
Product(s):   EW STAINLESS STEEL EPOXY CATALYST PART B
CAS Number:   NA
=====

```

SECTION IIA: HAZARDOUS INGREDIENTS

```

-----
Ingredient          CAS Number      (To Nearest 1.00%)      Vapor
                   % by Wt.      % by Vol.      LEL Press.
1. POLYAMIDE        NA              38.00         43.00         1.0      NA
2. BUTYL CELLOSOLVE 000111-76-2    2.00          3.00          1.1      .60
3. AROMATIC NAPHTHA TYPE 1 64742-95-6    18.00         22.00         .5       2.70
4. XYLENE           1330-20-7     23.00         29.00         1.0      9.50
                   NA = Not Applicable; NE = Not Established
=====

```

SECTION IIB: OCCUPATIONAL EXPOSURE LIMITS

```

-----
-----OSHA PEL's-----
Ingr. #  OSHA ppm  OSHA mg/m3  TWA ppm  TWA mg/m3  STEL ppm  STEL mg/m3
1.        10.000      NA          10.000   NA          NA         NA
2.         NA         NA          25.000   NA          NA         NA
3.       100.000    305.000    100.000  305.000    150.000   450.000
4.       100.000    435.000    100.000  435.000    150.000   655.000
                   NA = Not Applicable; NE = Not Established
=====

```

SECTION III: PHYSICAL DATA

```

-----
Boiling Range (degrees F): 176.00 - 400.00   Pounds per Gallon: 9.04
Vapor Density: HEAVIER THAN AIR             Evaporation Rate: SLOWER THAN ETHER
Solubility in Water: NIL
=====

```

```

-----
Volatiles (%)
                by Weight      by Volume
                Total         43.07         53.59
                Exempt VOC     .00           .00
                Non-exempt     43.07         53.59
=====

```

```

-----
VOC wt/gal: 3.89 lbs non-exempt solvent per adjusted gallon
Appearance: SILVER FLUID
=====

```

MATERIAL SAFETY DATA SHEET

50457ZB EW STAINLESS STEEL EPOXY CATALYST PART B

Printed: 10/11/08

=====

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

Flammability Classification:

OSHA: FLAMMABLE DOT: FLAMMABLE

Flash Point: 81.00 (Method: Tcc)

Extinguishing Media: CO2/FOAM

Unusual Fire and Explosion Hazards

THIS MATERIAL MAY BE IGNITED BY HEAT, SPARKS, FLAME OR STATIC ELECTRICITY. KEEP CONTAINERS CLOSED WHEN NOT IN USE. ISOLATE FROM HEAT, SPARKS, PILOT LIGHTS SMOKING MATERIALS AND OTHER SOURCES OF IGNITION.

Special Firefighting Procedures

THE USE OF SCBA IS RECOMMENDED FOR FIRE FIGHTERS. WATER SPRAY MAY BE USEFUL IN COOLING CONTAINERS EXPOSED TO HEAT AND FLAME. AVOID SPREADING BURNING LIQUID WITH WATER USED FOR COOLING PURPOSES.

FIGHT AS VOLATILE LIQUID FIRE. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. USE WATER TO COOL FIRE EXPOSED CONTAINERS.

SECTION V: HEALTH HAZARD DATA

Effects of Overexposure

DIZZINESS, NAUSEA, VOMITING, LOSS OF COORDINATION, AND FATIGUE.

Medical Conditions Prone to Aggravation by Exposure

ASTHMA, HEART CONDITION

Primary Routes of Entry into the Body, and Effects

MOUTH ,SKIN, LUNGS

EMERGENCY FIRST-AID PROCEDURES

INHALATION: REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION IF BREATHING IS DIFFICULT, GIVE OXYGEN. CALL PHYSICIAN.

EYE OR SKIN CONTACT: FLUSH EYES OR SKIN WITH PLENTY OF WATER FOR AT LEAST 15 MIN. IF IRRITATION PERSISTS SEE A DOCTOR

INGESTION: IF CONSCIOUS, DRINK LARGE QUANTITIES OF WATER. DO NOT INDUCE VOMITING, TAKE IMMEDIATELY TO HOSPITAL. IF UNCONSCIOUS, OR IN CONVULSIONS TAKE IMMEDIATELY TO HOSPITAL.

SECTION VI: REACTIVITY DATA

Stability: STABLE Hazardous Polymerization: MAY OCCUR

Hazardous Decomposition Products

HYDROGEN CHLORIDE AND POSSIBLE TRACES OF PHOSGENE

Conditions to Avoid

HEAT, SPARKS OPEN FLAMES, STATIC ELECTRICITY

Incompatibilities (Materials to Avoid)

MATERIAL SAFETY DATA SHEET

50457ZB EW STAINLESS STEEL EPOXY CATALYST PART B

Printed: 10/11/08

SECTION VII: SPILL OR LEAK PROCEDURES; WASTE DISPOSAL

Steps to be taken if Material is Leaked or Spilled
 STAY UPWIND AND AWAY FROM SPILL. KEEP ALL SOURCES OF IGNITION AWAY. KEEP
 OUT OF DRAINS SEWERS, OR WATERWAYS. USE ABSORBANT PADS. DISPOSE OF
 ACCORDING TO FEDERAL, STATE, AND LOCAL REGULATIONS.

Waste Disposal Methods
 IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL LAW.

SECTION VIII: SAFE HANDLING AND USE INFORMATION

Respiratory Protection
 APPROVED ORGANIC SUPPLIED AIR RESPIRATOR

Ventilation
 MECHANICAL EXPLOSIONPROOF

Protective Gloves
 YES

Eye Protection
 YES

Other Protective Equipment
 IMPERVIOUS CLOTHING

Hygienic Practices
 NO SMOKING OR EATING IN AREA. WASH HANDS BEFORE EATING.

SECTION IX: SPECIAL PRECAUTIONS

Handling and Storing
 KEEP IN COOL PROPERLY VENTILATED EXPLOSION PROOF AREA.

Other Precautions
 KEEP AWAY FROM HEAT SPARKS, AND OPEN FLAMES. USE APPROVED GROUNDING
 EQUIPMENT TO AVOID STATIC SPARKS.
 NOTE: THIS PRODUCT CONTAINS THE FOLLOWING INGREDIENTS WHICH ARE SUBJECT TO THE
 REPORTING REQUIREMENTS OF SARA 313 - 40 CFR 372.65

XYLENE	1330-20-7
BUTYL CELLOSOLVE	000111-76-2

California Proposition 65
 WARNING! This product contains chemical substance(s) known to the state of
 California to cause cancer and birth defects or other reproductive harm.

DISCLAIMER: THE INFORMATION AND RECOMMENDATIONS SET FORTH HEREIN ARE
 PRESENTED IN GOOD FAITH AND BELIEVED TO BE CORRECT AS OF THIS DATE.
 EASTWOOD MAKES NO REPRESENTATION AS TO THE COMPLETENESS OR ACCURACY
 THEREOF. INFORMATION IS SUPPLIED UNDER THE CONDITION THAT THE RECIPIENT
 WILL MAKE HIS OWN DETERMINATION AS TO ITS SUITABILITY FOR THEIR
 INTENDED PURPOSE, PRIOR TO USE.

END OF MSDS