MATERIAL SAFETY DATA SHEET

Manufactured For: The Easthill Group dba/ The Eastwood Company 263 Shoemaker Road Pottstown, PA 19464

USA & Canada: 800-345-1178 Outside USA: 610-323-2200

Emergency Contact: Chem-Trec 800-424-9300

Prepared by Technical Dept. 4-21-02

PRODUCT IDENTIFICATION

Name...... 50472 HotCoat Powder

Color: Vtwin Black
Chemistry: Polyester TGIC

DOT proper shipping name....: Not a regulated material.

HMIS RATINGS FOR HAZARDOUS INGREDIENTS

Health: 1 Flammability: 1 Reactivity: 0 For PPE (Personal Protection Equipment) please refer to occupational control procedures, page 2.

HAZARDOUS INGREDIENTS

Levei		
In Product	OSHA PEL	ACGIH TLV.
<OR = 6%	NE	.05 mg/m ³
<or 33%<="" =="" td=""><td>15.0 mg/m³</td><td>10.0 mg/m³</td></or>	15.0 mg/m ³	10.0 mg/m ³
<or 3%<="" =="" td=""><td>3.5 mg/m³</td><td>3.5 mg/m³</td></or>	3.5 mg/m ³	3.5 mg/m ³
<or 70%<="" =="" td=""><td>15.0 mg/m³</td><td>10.0 mg/m³</td></or>	15.0 mg/m ³	10.0 mg/m ³
rable)	5.0 mg/m ³	3.0 mg/m ³
	In Product <or 6%="" <or="70%</td" ==""><td>In Product OSHA PEL OR = 6% OR = 33% OR = 3% OR = 3% OR = 70% OSHA PEL NE 15.0 mg/m³ 15.0 mg/m³ 15.0 mg/m³</td></or>	In Product OSHA PEL OR = 6% OR = 33% OR = 3% OR = 3% OR = 70% OSHA PEL NE 15.0 mg/m³ 15.0 mg/m³ 15.0 mg/m³

^{*}Please note that exposure standards may vary from state to state.

PHYSICAL DATA

•	Physical State:	Solid
•	Boiling Range:	N/A
•	pH:	N/A
-	Percent Volatile by Weight:	N/A
-	Weight per Gallon:	N/A

FIRE PROTECTION

Flash Point Method:
N/A

Appropriate Extinguishers: Dry chemical, sand or ground limestone.

Special Fire Fighting Procedures: Persons exposed to products of

combustion should wear self-contained breathing apparatus and full protective equipment. Do not allow powder to be dispersed into the air while

fighting fires.

Unusual Fire and Explosion Hazards: Dust mixtures in air may be flammable.

REACTIVITY DATA

MATERIAL SAFETY DATA SHEET

• Stability: Stable

Incompatibility: N/E

Hazardous Decomposition Products: Incomplete combustion can yield low molecular

weight hydrocarbons and carbon monoxide.

Hazardous Polymerization: Will not occur.

EFFECTS OF OVEREXPOSURE

Acute: Powder coatings may irritate the skin or

respiratory tract in sensitive individuals.

Eye contact may be abrasive. May cause irritation

of skin, eyes, nose and throat.

Existing Health Conditions:
Inhalation of dust may aggravate lung conditions

such as asthma, emphysema or chronic bronchitis.

EMERGENCY AND FIRST AID PROCEDURES

For Eye Contact: Flush eye immediately with water for 15 minutes.

If irritation persists get medical attention.

For Skin Irritation: Wash affected area with soap and water.

Inhalation: Remove from exposure. Keep warm and still.

Notify a physician.

OCCUPATIONAL CONTROL PROCEDURES

Eye Protection: Safety glasses, eye wash.

Skin Protection: Gloves, long sleeve shirt and other clothing as

needed to minimize skin contact.

Respiratory Protection:
 NIOSH approved particulate respirator.

Ventilation: Local exhaust with an appropriate dust collection

system.

SPILL, LEAK AND DISPOSAL PROCEDURES

Spill or Leak Procedures: Remove all sources of ignition. Vacuum or sweep

up spilled material.

Waste Disposal: This product should be disposed of in accordance

with federal, state and local regulations.

ADDITIONAL INFORMATION

Store in a cool, dry location.

After handling the product, wash thoroughly before eating or smoking.

 Use adequate ventilation or NIOSH approved organic vapor respirator when welding, cutting or brazing coated parts.

MATERIAL SAFETY DATA SHEET

REGULATORY INFORMATION:

■ TSCA: We certify that all components of this product are registered under the regulations of the Toxic Substance Control Act.

SARA: This product contains the following toxic chemical subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act 1986 (SARA) and 40CFR part 372:

Chemical Name / CAS Number

<u>Percentage</u>

N/A