

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/30/2008

Reviewed on 01/30/2008

## 1 Identification of substance

### · Product details

· **Trade name:** 51007Z - Flexible Bumper Coating

· **Article number:** 51007Z

### · Distributed by:

The Easthill Group  
dba/ The Eastwood Company  
263 Shoemaker Road  
Pottstown, PA 19464

### · Information department:

USA & Canada: 800-345-1178  
Outside USA: (610) 323-2200
















· **Emergency information:** 24 HR EMERGENCY CHEMTREC 1-800-424-9300

## 2 Composition/Data on components

### · Chemical characterization

· **Description:** Mixture of the substances listed below with nonhazardous additions.

### · Dangerous components:

108-88-3	toluene Danger:  2.6/2;  3.10/1, 3.7/2 Warning:  3.2/2, 3.3/2A, 3.8/3	50-75%
	ACRYLIC RESIN Warning:  3.2/2, 3.3/2A, 3.8/3	10-25%
37244-96-5	NEPHELINE SYENITE Warning:  3.3/2A, 3.8/3	2.5-10%
78-93-3	butanone Danger:  2.6/2 Warning:  3.3/2A, 3.8/3	2.5-10%
1333-86-4	Carbon black Warning:  3.2/2, 3.3/2A, 3.8/3	1-2.5%
108-65-6	2-methoxy-1-methylethyl acetate Warning:  2.6/3;  3.3/2A	1-2.5%
2807-30-9	2-(propyloxy)ethanol Danger:  3.1.D/3, 3.3/2A Warning:  2.6/3	1-2.5%
67-56-1	methanol Danger:  2.6/2;  3.1.O/2, 3.1.D/2, 3.1.I/2;  3.8/1	≤1%

## 3 Hazards identification

### · Hazard description:



Harmful  
Highly flammable

### · Information pertaining to particular dangers for man and environment:

The product has to be labelled due to the calculation procedure of international guidelines.

(Contd. on page 2)

USA

**Material Safety Data Sheet**  
acc. to ISO/DIS 11014

Printing date 01/30/2008

Reviewed on 01/30/2008

**Trade name: 51007Z - Flexible Bumper Coating**

(Contd. of page 1)

Highly flammable.  
Harmful by inhalation.  
Irritating to eyes, respiratory system and skin.  
Danger of serious damage to health by prolonged exposure.  
Possible risk of harm to the unborn child.  
Harmful: may cause lung damage if swallowed.

**· Classification system:**

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

**· NFPA ratings (scale 0 - 4)**

Health = 2  
Fire = 3  
Reactivity = 0

**· HMIS-ratings (scale 0 - 4)**

Health = 2  
Fire = 3  
Reactivity = 0

**· GHS label elements****Danger**

2.6/2 - Highly flammable liquid and vapour.

**Danger**

3.10/1 - May be fatal if swallowed and enters airways.  
3.7/2 - Suspected of damaging fertility or the unborn child.

**Warning**

3.1/4 - Harmful if inhaled.  
3.2/2 - Causes skin irritation.  
3.3/2A - Causes serious eye irritation.  
3.8/3 - May cause respiratory irritation.

**· Prevention:**

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Keep container tightly closed.  
Ground/bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting/ equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Avoid breathing dust/fume/gas/mist/vapours/spray.  
Wash thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves/protective clothing/eye protection/face protection.  
Use personal protective equipment as required.

(Contd. on page 3)

**Material Safety Data Sheet**  
**acc. to ISO/DIS 11014**

Printing date 01/30/2008

Reviewed on 01/30/2008

**Trade name: 51007Z - Flexible Bumper Coating**

(Contd. of page 2)

**· Response:***IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.**IF ON SKIN: Wash with plenty of soap and water.**IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.**IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.**IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**IF exposed or concerned: Get medical advice/attention.**Call a POISON CENTER or doctor/physician if you feel unwell.**Specific treatment (see label).**Do NOT induce vomiting.**If skin irritation occurs: Get medical advice/attention.**If eye irritation persists: Get medical advice/attention.**Take off contaminated clothing and wash before reuse.**In case of fire: Use for extinction: CO2, powder or water spray.***· Storage:***Store in a well-ventilated place. Keep container tightly closed.**Store in a well-ventilated place. Keep cool.**Store locked up.***· Disposal:***Dispose of contents/container in accordance with local/regional/national/international regulations.***4 First aid measures****· General information:***Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.***· After inhalation:***Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.**In case of unconsciousness place patient stably in side position for transportation.***· After skin contact:** *Immediately wash with water and soap and rinse thoroughly.***· After eye contact:***Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.***· After swallowing:** *If symptoms persist consult doctor.***5 Fire fighting measures****· Suitable extinguishing agents:** *CO2, sand, extinguishing powder. Do not use water.***· For safety reasons unsuitable extinguishing agents:** *Water with full jet***· Protective equipment:** *Mouth respiratory protective device.***6 Accidental release measures****· Person-related safety precautions:** *Wear protective equipment. Keep unprotected persons away.***· Measures for environmental protection:***Do not allow product to reach sewage system or any water course.**Inform respective authorities in case of seepage into water course or sewage system.**Do not allow to enter sewers/ surface or ground water.*

(Contd. on page 4)

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/30/2008

Reviewed on 01/30/2008

Trade name: 51007Z - Flexible Bumper Coating

(Contd. of page 3)

· **Measures for cleaning/collecting:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

## 7 Handling and storage

· **Handling:**

· **Information for safe handling:**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** Store in a cool location.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

## 8 Exposure controls and personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Components with limit values that require monitoring at the workplace:**

### 108-88-3 toluene

PEL Short-term value: C 300; 500\* ppm

Long-term value: 200 ppm

\*10-min peak per 8-hr shift

REL Short-term value: 560 mg/m<sup>3</sup>, 150 ppm

Long-term value: 375 mg/m<sup>3</sup>, 100 ppm

TLV 75 mg/m<sup>3</sup>, 20 ppm

### 78-93-3 butanone

PEL 590 mg/m<sup>3</sup>, 200 ppm

REL Short-term value: 885 mg/m<sup>3</sup>, 300 ppm

Long-term value: 590 mg/m<sup>3</sup>, 200 ppm

TLV Short-term value: 885 mg/m<sup>3</sup>, 300 ppm

Long-term value: 590 mg/m<sup>3</sup>, 200 ppm

BEI

### 1333-86-4 Carbon black

PEL 3.5 mg/m<sup>3</sup>

REL 3.5\* mg/m<sup>3</sup>

\*0.1 in presence of PAHs, as PAHs; 10-hr TWA

TLV 3.5 mg/m<sup>3</sup>

### 108-65-6 2-methoxy-1-methylethyl acetate

WEEL 50 ppm

(Contd. on page 5)

USA

**Material Safety Data Sheet**  
acc. to ISO/DIS 11014

Printing date 01/30/2008

Reviewed on 01/30/2008

**Trade name: 51007Z - Flexible Bumper Coating**

(Contd. of page 4)

**67-56-1 methanol**

PEL	260 mg/m <sup>3</sup> , 200 ppm
REL	Short-term value: 325 mg/m <sup>3</sup> , 250 ppm Long-term value: 260 mg/m <sup>3</sup> , 200 ppm Skin
TLV	Short-term value: 328 mg/m <sup>3</sup> , 250 ppm Long-term value: 262 mg/m <sup>3</sup> , 200 ppm Skin; BEI

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

**9 Physical and chemical properties****General Information**

<b>Form:</b>	Liquid
<b>Color:</b>	According to product specification
<b>Odor:</b>	Characteristic

(Contd. on page 6)

USA

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/30/2008

Reviewed on 01/30/2008

Trade name: 51007Z - Flexible Bumper Coating

(Contd. of page 5)

· **Change in condition****Melting point/Melting range:** Undetermined.**Boiling point/Boiling range:** 110°C (230°F)· **Flash point:** 4°C (39°F)· **Ignition temperature:** 535°C (995°F)· **Auto igniting:** Product is not selfigniting.· **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.· **Explosion limits:****Lower:** 1.2 Vol %**Upper:** 7.0 Vol %· **Vapor pressure at 20°C (68°F):** 29 hPa (22 mm Hg)· **Density at 20°C (68°F):** 0.95 g/cm<sup>3</sup>· **Solubility in / Miscibility with****Water:** Not miscible or difficult to mix.· **Solvent content:****Organic solvents:** 74.5 %**VOC content:** 74.5 %  
707.0 g/l / 5.90 lb/gl· **Solids content:** 25.5 %

## 10 Stability and reactivity

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.· **Dangerous reactions** No dangerous reactions known.· **Dangerous products of decomposition:** No dangerous decomposition products known.

## 11 Toxicological information

· **Acute toxicity:**· **LD/LC50 values that are relevant for classification:****108-88-3 toluene**

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

· **Primary irritant effect:**· **on the skin:** Irritant to skin and mucous membranes.· **on the eye:** Irritating effect.· **Sensitization:** No sensitizing effects known.· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

(Contd. on page 7)

USA

**Material Safety Data Sheet**  
acc. to ISO/DIS 11014

Printing date 01/30/2008

Reviewed on 01/30/2008

**Trade name: 51007Z - Flexible Bumper Coating**

Irritant

(Contd. of page 6)

**12 Ecological information**· **General notes:***Water hazard class 2 (Self-assessment): hazardous for water**Do not allow product to reach ground water, water course or sewage system.**Danger to drinking water if even small quantities leak into the ground.***13 Disposal considerations**· **Product:**· **Recommendation:***Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*· **Uncleaned packagings:**· **Recommendation:** Disposal must be made according to official regulations.**14 Transport information**· **DOT regulations:**

- **Hazard class:** 3
- **Identification number:** UN1263
- **Packing group:** II
- **Proper shipping name (technical name):** PAINT
- **Label:** 3

· **Land transport TDG (Canada) and ADR/RID (Europe):**

- **Hazard class:** 3 Flammable liquids
- **UN-Number:** 1263
- **Packaging group:** II
- **Label:** 3
- **Description of goods:** 1263 PAINT, special provision 640D

· **Maritime transport IMDG:**

- **IMDG Class:** 3
- **UN Number:** 1263

(Contd. on page 8)

USA

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/30/2008

Reviewed on 01/30/2008

Trade name: 51007Z - Flexible Bumper Coating

(Contd. of page 7)

· **Label** 3  
 · **Packaging group:** II  
 · **EMS Number:** F-E,S-D  
 · **Marine pollutant:** No  
 · **Propper shipping name:** PAINT

· **Air transport ICAO-TI and IATA-DGR:**

· **ICAO/IATA Class:** 3  
 · **UN/ID Number:** 1263  
 · **Label** 3  
 · **Packaging group:** II  
 · **Propper shipping name:** PAINT

· **UN "Model Regulation":** UN1263; PAINT; 3; II

## 15 Regulations

· **Sara**· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

108-88-3 toluene

ACRYLIC RESIN

78-93-3 butanone

67-56-1 methanol

· **TSCA (Toxic Substances Control Act):**

108-88-3 toluene

78-93-3 butanone

1333-86-4 Carbon black

108-65-6 2-methoxy-1-methylethyl acetate

2807-30-9 2-(propyloxy)ethanol

67-56-1 methanol

7732-18-5 water, distilled, conductivity or of similar purity

· **Proposition 65**· **Chemicals known to cause cancer:**

1333-86-4 Carbon black

68911-87-5 ALKYL QUATERNARY AMMONIUM MONTMORILLONITE

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

(Contd. on page 9)

USA



# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/30/2008

Reviewed on 01/30/2008

Trade name: 51007Z - Flexible Bumper Coating

(Contd. of page 8)

· **Chemicals known to cause developmental toxicity:**

108-88-3 toluene

· **Cancerogenity categories**

· **EPA (Environmental Protection Agency)**

108-88-3 toluene

D

78-93-3 butanone

D

· **IARC (International Agency for Research on Cancer)**

108-88-3 toluene

3

1333-86-4 Carbon black

2B

68911-87-5 ALKYL QUATERNARY AMMONIUM MONTMORILLONITE

TRACE AMOUNTS OF 14808-60-7

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

108-88-3 toluene

A4

1333-86-4 Carbon black

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

1333-86-4 Carbon black

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

· **Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

· **Hazard symbols:**

Harmful

Highly flammable

· **Hazard-determining components of labelling:**

toluene

· **Risk phrases:**

Highly flammable.

Harmful by inhalation.

Irritating to eyes, respiratory system and skin.

Danger of serious damage to health by prolonged exposure.

Possible risk of harm to the unborn child.

Harmful: may cause lung damage if swallowed.

· **Safety phrases:**

Keep out of the reach of children.

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

Wear suitable protective clothing and gloves.

If swallowed, seek medical advice immediately and show this container or label.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 10)

USA

**Material Safety Data Sheet**  
**acc. to ISO/DIS 11014**

Printing date 01/30/2008

Reviewed on 01/30/2008

**Trade name: 51007Z - Flexible Bumper Coating**

(Contd. of page 9)

· **Department issuing MSDS:** Environment protection department.

· **Contact:** Steve Gaver

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Reglement internationale concernent le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

USA