



DO THE JOB RIGHT.

|              |           |
|--------------|-----------|
| DATE ISSUED: | 5/25/2015 |
| Version No.: | 51540-1   |

## SAFETY DATA SHEET

### 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** Eastwood Single Stage Urethane Automotive Topcoat (2.8 VOC) – CANDEEZ Custom Finishes

PRODUCT CODE: See list below

PRODUCT USE: FOR PROFESSIONAL USE ONLY

**MANUFACTURED FOR:**

The Easthill Group  
dba The Eastwood Company  
263 Shoemaker Road,  
Pottstown, PA 19464  
USA: 1-800-345-1178 or (610) 323-2200 CANADA: 1-800-820-9042

**24 HR. EMERGENCY TELEPHONE NUMBER:**

Only in the Event of a Chemical Emergency Involving A Spill, Leaks, Fire, or Exposure  
Call Chemtrec Toll Free Day or Night: 1-800-424-9300 International Call Collect: (202) 483-7616

|          |                       |          |                              |
|----------|-----------------------|----------|------------------------------|
| 51540ZPA | Vino Rojo             | 51541ZPA | Cherry Gumball               |
| 51542ZPA | Orange U Bad          | 51543ZPA | Sugar Coat It Gold           |
| 51544ZPA | Tequila Lime 'N Gold  | 51545ZPA | Eye Candy Green              |
| 51546ZPA | Salt Water Taffy Teal | 51547ZPA | Blue By You                  |
| 51548ZPA | Candy Pants Violet    | 51549ZPA | Silver Metallic Candeez Base |

### 2. HAZARDS IDENTIFICATION

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

**CLASSIFICATION:**

FLAMMABLE LIQUIDS - Category 2  
ACUTE TOXICITY: Inhalation - Category 4  
ACUTE TOXICITY: Oral - Category 4  
ACUTE TOXICITY: Dermal - Category 4  
ASPIRATION HAZARD: Category 1  
CARCINOGENICITY: Category 2  
SKIN IRRITATION: Category 2  
SKIN SENSITIZATION: Category 1  
EYE IRRITATION: Category 2A  
SPECIFIC TARGET ORGAN TOXICITY: SINGLE EXPOSURE - Category 3 (Respiratory, Central Nervous System)  
SPECIFIC TARGET ORGAN TOXICITY: REPEATED EXPOSURE - Category 2 (Liver, Kidney, Central Nervous System)  
Percentage of mixture consisting of ingredients of unknown toxicity: 20%

#### GHS label elements

#### PICTOGRAMS



#### SIGNAL WORD: Danger

**HAZARD STATEMENTS:** Highly flammable liquid and vapor. Harmful if swallowed. May be fatal if swallowed and enters airways. Harmful in contact with skin, causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation, drowsiness or dizziness. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.

#### PRECAUTIONARY STATEMENTS:

**PREVENTION:** Read label before use. If medical advice is needed, have product container or label at hand. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting, and other tools or equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust, fumes, gas, mist, vapors or spray. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this

product. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Use personal protective equipment as required, (see Section 8). Wear protective gloves, protective clothing, eye and face protection. Wear an appropriate, properly fitted fresh air supplied respirator (NIOSH-approved TC19 or equivalent) during and after application, and until all organic solvent vapors and spray mists are exhausted, or any time airborne contaminant levels exceed exposure limits indicated in Section 8. Avoid release to the environment. Keep out of reach of children and pets at all times.

**RESPONSE:** Get Medical attention if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or physician. Rinse mouth. Do NOT induce vomiting. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing and wash before reuse. Rinse skin with water or shower. If skin irritation or rash occurs: Get medical attention. Immediately call a POISON CENTER or physician if you feel unwell. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction, do not use water, see Section 5.

**STORAGE:** Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

**DISPOSAL:** Dispose of contents and container in accordance with all local, regional, national and international regulations.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name              | CAS Number | Range %<br>by Wt |
|----------------------------|------------|------------------|
| TERTIARY BUTYL ACETATE     | 540-88-5   | 20 – 40 %        |
| TITANIUM DIOXIDE           | 13463-67-7 | 10 – 35 %        |
| *XYLENE                    | 1330-20-7  | 3 – 25 %         |
| METHYL AMYL KETONE         | 110-43-0   | < 10 %           |
| DIACETONE ALCOHOL          | 123-42-2   | < 10 %           |
| DIMETHYL CARBONATE         | 616-38-6   | < 10 %           |
| PARACHLOROBENZOTRIFLUORIDE | 98-56-6    | < 10 %           |
| *GLYCOL ETHER EB ACETATE   | 112-07-2   | < 10 %           |
| ACETONE                    | 67-64-1    | < 10 %           |

\* Toxic chemical subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

### 4. FIRST AID MEASURES

**EYES:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes, check for and remove contact lenses. Seek immediate medical attention.

**SKIN:** Remove contaminated clothing. Immediately flush exposed area with large amounts of water. If symptoms persist, seek medical attention. Wash clothing separately and clean shoes before reuse.

**INGESTION:** Seek immediate medical attention, contact physician or poison control center. Do NOT induce vomiting unless directed to do so by medical professional. Never give anything by mouth to an unconscious person.

**INHALATION:** Seek immediate medical attention. Remove from exposure to fresh air. If not breathing or if breathing is irregular, provide artificial respiration or oxygen by trained personnel; rescuers should put on appropriate protective gear.

**MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:** Vapor and spray mist harmful. May be harmful or fatal if swallowed, aspiration hazard. Exposure may cause lung damage, allergic reaction and respiratory reaction. May cause eye, skin, nose, throat and respiratory irritation. May affect the central nervous system causing dizziness, headache, or nausea. May cause skin dryness or cracking. Sanding dust may be harmful if inhaled, do not breath dust, use personal protective equipment.

**EFFECTS:** Repeated and prolonged overexposure to solvents may lead to permanent brain and nervous system damage causing dizziness, headache, or nausea and may cause adverse liver and kidney effects. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal. Individuals with chronic respiratory problems should neither use this product nor be exposed to its vapors or spray mist.

**NOTES TO PHYSICIAN:** This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. Symptoms of poisoning may appear several hours after exposure.

### 5. FIRE FIGHTING MEASURES

**SUITABLE EXTINGUISHING MEDIA:** Carbon Dioxide, Dry Chemical, Alcohol-resistant Foam. Do not use water, material will float and may ignite on surface of water.

**FIRE FIGHTING PROCEDURES:** Fight as volatile liquid fire. Wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Eliminate all sources of ignition. Evacuate unnecessary personnel. Use water spray to cool containers with caution, avoid spreading burning liquid. Water runoff can cause environmental damage. Dike and collect water used to fight fire.

**UNUSUAL FIRE AND EXPLOSION HAZARD:** Flammable liquid and vapor. Vapors can travel to a source of ignition and flash back. Vapors/dust may cause flash fire or explosion. This material may be ignited by heat, sparks, flame or static electricity. Closed containers may explode when exposed to extreme heat. Empty containers retain product residue

(liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition.

## 6. ACCIDENTAL RELEASE MEASURES

**ENVIRONMENTAL PRECAUTIONS:** Avoid runoff and contact with soil, drains, sewers and waterways. Contact appropriate authority if spill is in excess of reportable quantity.

**PERSONAL PRECAUTIONS:** Eliminate all ignition sources. No smoking, do not use flares. Contact emergency personnel. Evacuate the spill area and keep unnecessary, unprotected personnel away. Do not breathe vapors, use suitable personal protective equipment. Do not touch or walk through spilled material. Prevent additional discharge of material if able to do so safely. Ventilate spill area.

**METHOD OF CLEANING UP:** For small spills, add absorbent (soil may be used in the absence of other suitable materials) and use a non-sparking or explosion-proof means to transfer material to a sealable, appropriate container for disposal. For large spills, dike spilled material, or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal using non-sparking tools.

Dispose of spilled material and contaminated absorbent material in compliance with local and national regulations, use a licensed waste disposal contractor, see Section 13.

## 7. HANDLING AND STORAGE

**PRECAUTIONS FOR SAFE HANDLING:** Use only in a well ventilated area, with appropriate personal protective equipment, (see section 8). Do not eat, drink or smoke when handling this material. Wash hands and face before eating, drinking or smoking. Do not breathe vapor, fumes or mist. Do not get in eyes, or on skin, or clothing.

Always open containers slowly to allow any excess pressure to vent. Containers should be grounded when pouring. Take precautionary measures against static discharge. When transferring, follow proper grounding procedures. Use spark-proof tools and explosion proof equipment.

This material is part of a multiple component system, read the Safety Data Sheet(s) for all components before mixing, as the mixture will have the hazards of all of its parts. Empty containers retain product residue and can be hazardous. Do not reuse container.

**CONDITIONS FOR SAFE STORAGE, INCLUDING INCOMPATIBILITIES:** Store in accordance with local regulations. Store locked up. Keep container closed when not in use. Isolate from heat, flame, sparks, pilot lights, smoking materials and other sources of ignition. Containers can build up pressure if exposed to heat (fire). Store containers in a cool, well ventilated, explosion proof area. Protect from direct sunlight. KEEP OUT OF REACH OF CHILDREN AND PETS AT ALL TIMES.

## 8. EXPOSURE CONTROLS\PERSONAL PROTECTION

| Components                 | CAS        | Exposure Limits  |
|----------------------------|------------|--|
| TERTIARY BUTYL ACETATE     | 540-88-5   | ACGIH TWA 200 PPM<br>OSHA PEL TWA 200 PPM                              |
| TITANIUM DIOXIDE           | 13463-67-7 | ACGIH TLV 10mg/m <sup>3</sup><br>OSHA PEL TWA 15mg/m <sup>3</sup> dust |
| XYLENE                     | 1330-20-7  | ACGIH TWA 100 PPM<br>OSHA PEL TWA 100 PPM                              |
| METHYL AMYL KETONE         | 110-43-0   | ACGIH TWA 50 PPM<br>OSHA PEL TWA 100 PPM                               |
| DIACETONE ALCOHOL          | 123-42-2   | ACGIH TWA 50 PPM<br>OSHA PEL TWA 50 PPM                                |
| DIMETHYL CARBONATE         | 616-38-6   | Data not available   |
| PARACHLOROBENZOTRIFLUORIDE | 98-56-6    | Data not available   |
| GLYCOL ETHER EB ACETATE    | 112-07-2   | ACGIH TWA 20 PPM<br>NIOSH REL TWA 5 PPM                                |
| ACETONE                    | 67-64-1    | ACGIH TWA 500 PPM<br>OSHA PEL TWA 1,000 PPM                            |

**ENGINEERING CONTROLS:** Provide explosion proof exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits.

### PERSONAL PROTECTIVE EQUIPMENT

**EYES AND FACE:** Use chemical splash goggles and face shield (ANSI Z87.1 or approved equivalent).

**SKIN:** Wear impervious gloves to prevent contact with the skin. Where contact is likely, wear chemical resistant gloves, a chemical suit, long sleeves, rubber boots, and chemical safety goggles plus a face shield.

**RESPIRATORY:** Wear an appropriate, properly fitted fresh-air supplied respirator, (NIOSH-approved TC-19C or equivalent), during and after application, until all organic vapors and spray mists are exhausted or any time airborne contaminate levels exceed exposure limits. Follow respirator manufacturer's directions and observe OSHA regulations for respirator use (29 cfr 1910.134).

**WORK HYGIENIC PRACTICES:** Do not eat, drink, or smoke in areas where this material is used. Avoid breathing vapors. Remove contaminated clothing and wash before reuse. Wash thoroughly after handling. Wash hands before eating. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

**9. PHYSICAL AND CHEMICAL PROPERTIES****PHYSICAL STATE:** Liquid**COLOR:** Liquid in various colors**ODOR:** Typical**ODOR THRESHOLD:** Not available**pH:** Not available**MELTING POINT:** Not applicable**BOILING POINT:** 133°F**FLASH POINT AND METHOD:** -4°F TCC**EVAPORATION RATE:** Not available**FLAMMABILITY(Solid/Gas):** Not applicable**FLAMMABLE LIMITS:** .5 - 13.0**VAPOR PRESSURE:** Not available**VAPOR DENSITY:** Heavier than air**DENSITY (lbs/gl):** 8.3 - 11.0**SPECIFIC GRAVITY:** 1.0 - 1.20**% SOLUBILITY IN WATER:** Not available**OCTANOL/WATER PARTITION COEFFICIENT:** Not available**AUTO-IGNITION TEMPERATURE:** Not available**DECOMPOSITION TEMPERATURE:** Not available**VISCOSITY:** 54 - 56 Krebs Units**VOC INFORMATION:** This is a Low-VOC Automotive Topcoat (Single-Stage). VOC (both Actual and Regulatory) as supplied, varies by color. Please see information on product label for specific VOC contents. When mixed as directed, RTS VOC will not exceed 2.8 lbs/gallon.**10. STABILITY AND REACTIVITY****HAZARDOUS POLYMERIZATION:** Under normal conditions of storage and use, hazardous polymerization will not occur.**CONDITIONS TO AVOID:** Keep away from heat, sparks, flames, and other sources of ignition. Do not smoke, extinguish all flames and pilot lights. Turn off stoves, heaters, electrical motors, tools, appliances and any other possible sources of ignition prior to spray application, during use and until all vapors are exhausted from the area.**CHEMICAL STABILITY:** The product is stable. Avoid heat, open flame, sparks, static electricity, freezing.**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide, carbon dioxide, and possible oxides of nitrogen**INCOMPATIBLE MATERIALS:** Alkaline materials, strong acids and oxidizing materials.**POSSIBILITY OF HAZARDOUS REACTIONS:** Under normal conditions of use and storage, hazardous reactions will not occur.**11. TOXICOLOGICAL INFORMATION**

This product has not been tested as a whole, individual component data, (where available), is listed below:

**ACETONE(67-64-1)**

|                                |  |   |
|--------------------------------|--|---|
| Acute Dermal Toxicity          | LD50: >7,426 mg/kg   | May cause skin irritation.                    |
| Acute Inhalation Toxicity      | LC50: 76.0 mg/l 4hrs (rat)   |   |
| Acute Oral Toxicity            | LD50: 5,800 mg/kg (rat)  |   |
| Aspiration Toxicity            | May be fatal if swallowed and enters airways   |   |
| Target Organ, Single Exposure  | Central Nervous System   | Category 3 May cause drowsiness or dizziness. |
| Eye Irritation                 | Category 2A  | Causes serious eye irritation.                |
| Symptoms of Overexposure       | Headache, dizziness, tiredness, nausea and vomiting. Concentrations substantially above the TLV may cause narcotic effects. Solvents may degrease the skin.                |   |
| Carcinogenicity Classification | No ingredient in this component is present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC, NTP or OSHA. |   |

**DIACETONE ALCOHOL(123-42-2)**

|                               |                            |  |
|-------------------------------|----------------------------|--|
| Acute Dermal Toxicity         | LD50: >1,875 mg/kg         | May cause skin irritation and/or dermatitis. |
| Acute Inhalation Toxicity     | LC50: >7.6 mg/l 4hrs (rat) |  |
| Acute Oral Toxicity           | LD50: 3,002 mg/kg (rat)    |  |
| Target Organ, Single Exposure | Respiratory System         | Category 3 May cause respiratory irritation  |
| Eye Irritation                | Category 2A                | Causes serious eye irritation.               |

**DIMETHYL CARBONATE(616-38-6)**

|                           |   |                            |
|---------------------------|---|----------------------------|
| Acute Dermal Toxicity     | LD50: >2,000 mg/kg (rabbit)             | May cause skin irritation. |
| Acute Inhalation Toxicity | LC50: 5.36 mg/l 4hrs (rat)              |                            |
| Acute Oral Toxicity       | LD50: >5,000 mg/kg (rat)                |                            |
| Eye Irritation            | Contact with eyes may cause irritation. |                            |

**GLYCOL ETHER EB ACETATE(112-07-2)**

|                                |  |            |   |
|--------------------------------|--|------------|---|
| Acute Dermal Toxicity          | LD50: 1,500 mg/kg (rabbit)   | Category 4 | May cause skin irritation and/or dermatitis, harmful by skin absorption.                      |
| Acute Inhalation Toxicity      | No data available  |            | Vapors may cause irritation to the eyes, respiratory system and the skin, harmful if inhaled. |
| Acute Oral Toxicity            | LD50: 1,800 mg/kg (rat)  | Category 4 | Harmful if swallowed  |
| Eye Irritation                 | Irritating to eyes.  |            |   |
| Carcinogenicity Classification | No ingredient in this component is present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC, NTP or OSHA. |            |   |

**METHYL AMYL KETONE(110-43-0)**

|                               |                             |   |
|-------------------------------|-----------------------------|---|
| Acute Dermal Toxicity         | LD50: >2,000 mg/kg (rat)    | May cause mild skin irritation.               |
| Acute Inhalation Toxicity     | LC50: >16.7 mg/l 4hrs (rat) | Category 4 Harmful if inhaled.                |
| Acute Oral Toxicity           | LD50: 1,670 mg/kg (rat)     | Category 4 Harmful if swallowed.              |
| Target Organ, Single Exposure | Central Nervous System      | Category 3 May cause drowsiness or dizziness. |
| Eye Irritation                | Moderate eye irritant.      |   |

**PARACHLOROBENZOTRIFLUORIDE(98-56-6)**

|                               |                             |  |
|-------------------------------|-----------------------------|--|
| Acute Dermal Toxicity         | LD50: >3,300 mg/kg (rabbit) | Irritating to skin.                          |
| Acute Inhalation Toxicity     | LC50: 33 mg/l 4hrs (rat)    | Moderate respiratory irritant.               |
| Acute Oral Toxicity           | LD50: 13,000 mg/kg (rat)    |  |
| Target Organ, Single Exposure | Respiratory System          | Category 3 May cause respiratory irritation. |
| Eye Irritation                | Category 2A                 | Causes serious eye irritation.               |
| Skin Irritation               | Category 2                  | Moderate skin irritant                       |
| Skin Sensitization            | Category 1                  | May cause an allergic skin reaction.         |

**TERTIARY BUTYL ACETATE(540-88-5)**

|                               |   |  |
|-------------------------------|---|--|
| Acute Dermal Toxicity         | LD50: >2,000 mg/kg (rat)  | Repeated exposure may cause skin dryness or cracking.  |
| Acute Inhalation Toxicity     | LC50: 12.52 mg/l 4hrs   | Harmful if inhaled, may cause difficulty in breathing, chest congestion, shortness of breath and/or fever. |
| Category 4                    |   | May cause lung damage if swallowed.  |
| Acute Oral Toxicity           | LD50: 4,500 mg/kg (rat)   |  |
| Aspiration Toxicity           | Can cause pulmonary edema if aspirated into lungs.  |  |
| Target Organ, Single Exposure | Respiratory, Central Nervous System   | Category 3 May cause respiratory irritation, drowsiness or dizziness.                                      |
| Eye Irritation                | May cause moderate eye irritation.  |  |
| Symptoms of Overexposure      | The onset of respiratory symptoms may be delayed for several hours after exposure. High doses may cause CNS depression. |  |

**TITANIUM DIOXIDE(13463-67-7)**

|                                |                             |                                  |
|--------------------------------|-----------------------------|----------------------------------|
| Acute Dermal Toxicity          | LD50: >5,000 mg/kg (rabbit) |                                  |
| Acute Inhalation Toxicity      | LC50: >6.8 mg/l 4hrs (rat)  |                                  |
| Acute Oral Toxicity            | LD50: >5,000 mg/kg (rat)    |                                  |
| Carcinogenicity Classification | IARC Group 2B               | Possibly carcinogenic to humans. |

**XYLENE(1330-20-7)**

|                                 |                                       |            |  |
|---------------------------------|---------------------------------------|------------|--|
| Acute Dermal Toxicity           | 1,100 mg/kg                           | Category 4 | Harmful by skin absorption.  |
| Acute Inhalation Toxicity       | LC50 6700 ppm 4hrs (rat)              | Category 4 | Harmful if inhaled.  |
| Acute Oral Toxicity             | LD50 3,523 mg/kg (rat)                |            |  |
| Aspiration Toxicity             | Category 1                            |            | May be fatal if swallowed and enters airways.                      |
| Target Organ, Single Exposure   | Respiratory System                    | Category 3 | May cause respiratory irritation.                                  |
| Target Organ, Repeated Exposure | Liver, Kidney, Central Nervous System | Category 2 | May cause damage to organs through prolonged or repeated exposure. |
| Eye Irritation                  | Category 2A                           |            | Causes serious eye irritation.                                     |
| Skin Irritation                 | Category 2                            |            | Causes skin irritation.  |
| Carcinogenicity Classification  | IARC Group 2B                         |            | Possibly carcinogenic to humans.                                   |

**12. ECOLOGICAL INFORMATION**

This product has not been tested as a whole, individual component data, (where available), is listed below:

**ACETONE(67-64-1)**

|  |                                     |                        |
|--|-------------------------------------|------------------------|
| Toxicity to fish                                   | Oncorhynchus mykiss (rainbow trout) | LC50: 6,100 mg/l 48hrs |
| Toxicity to daphnia and other aquatic invertebrate | Daphnia magna (Water flea)          | EC50: 7,630 mg/l 48hrs |
| Toxicity to algae                                  | No data available                   | No data available      |
| Persistence and degradability                      | Biodegradability                    | Readily                |
| Bioaccumulative potential                          | N/A                                 | Negative               |

**DIACETONE ALCOHOL(123-42-2)**

|  |  |                             |
|--|--|-----------------------------|
| Toxicity to fish                                   | Lepomis macrochirus (Bluegill sunfish) | LC50: 420 mg/l 96hrs        |
| Toxicity to daphnia and other aquatic invertebrate | Daphnia magna (Water flea)             | EC50: 9,000 mg/l 24hrs      |
| Persistence and degradability                      | Biodegradability                       | Readily                     |
| Bioaccumulative potential                          | Bioaccumulation                        | Bioaccumulation is unlikely |

**DIMETHYL CARBONATE(616-38-6)**

|  |   |                             |
|--|---|-----------------------------|
| Toxicity to fish                                   | Danio rerio (zebra fish)                      | LC50: >100 mg/l 96hrs       |
| Toxicity to daphnia and other aquatic invertebrate | Daphnia magna (Water flea)                    | EC50: 83 mg/l 24hrs         |
| Toxicity to algae                                  | Pseudokirchneriella subcapitata (green algae) | EBC50: 72 mg/l 72hrs        |
| Toxicity to bacteria                               | Activated sludge                              | EC50: >1,000 mg/l 3hrs      |
| Persistence and degradability                      | Biodegradability                              | Readily                     |
| Bioaccumulation Potential                          | Bioaccumulation                               | Bioaccumulation is unlikely |

**GLYCOL ETHER EB ACETATE(112-07-2)**

|  |   |                                   |
|--|---|-----------------------------------|
| Toxicity to fish                                   | Oncorhynchus mykiss (rainbow trout)           | LC50: 28 mg/l 96hrs               |
| Toxicity to daphnia and other aquatic invertebrate | (Daphnia)                                     | 37 mg/l 48hrs                     |
| Toxicity to algae                                  | Pseudokirchneriella subcapitata (green algae) | 520 mg/l 72hrs                    |
| Toxicity to bacteria                               | (Bacteria)                                    | 2,800 mg/l 18hrs                  |
| Persistence and degradability                      | Biodegradability                              | Readily                           |
| Bioaccumulative potential                          | Bioaccumulation                               | Low potential for bioaccumulation |

**METHYL AMYL KETONE(110-43-0)**

|  |   |                        |
|--|---|------------------------|
| Toxicity to fish                                   | Pimephales promelas (fathead minnow)    | LC50: 131 mg/l 96hrs   |
| Toxicity to daphnia and other aquatic invertebrate | daphnia magna (Water flea)              | EC50: >90.1 mg/l 48hrs |
| Toxicity to algae                                  | Selenastrum capricornutum (green algae) | EC50: 98.2 MG/L 72 hrs |
| Persistence and degradability                      | Biodegradability                        | Readily                |
| Bioaccumulative potential                          | Partition coefficient: n-octanol/water  | Log Pow: 1.98          |

**PARACHLOROBENZOTRIFLUORIDE(98-56-6)**

|  |   |                                       |
|--|---|---------------------------------------|
| Toxicity to fish                                   | Danio rerio (zebra fish)                      | LC50: 3 mg/l 96hrs                    |
| Toxicity to daphnia and other aquatic invertebrate | Daphnia magna (Water flea)                    | IC50: 2 mg/l 48hrs                    |
| Toxicity to algae                                  | Pseudokirchneriella subcapitata (green algae) | EC50: >0.41 mg/l 72hrs                |
| Persistence and degradability                      | Biodegradability                              | Not readily biodegradable             |
| Bioaccumulative potential                          | Partition coefficient: n-octanol/water        | Pow: 5,030 (25 C) log Pow: 3.7 (25 C) |

**TERTIARY BUTYL ACETATE(540-88-5)**

|                               |   |                               |
|-------------------------------|---|-------------------------------|
| Toxicity to algae             | Can inhibit growth of aquatic algae                                   | EC50: 16 ml/l 72hrs           |
| Toxicity to bacteria          | High concentrations may be harmful to sewage treatment plant microbes | 1.5 mg/l                      |
| Persistence and degradability | Biodegradability  | Inherently biodegradable      |
| Bioaccumulative potential     | Bioaccumulation   | Not expected to bioaccumulate |

**XYLENE(1330-20-7)**

|  |   |                       |
|--|---|-----------------------|
| Toxicity to fish                                   | Oncorhynchus mykiss (rainbow trout)           | LC50: 2.6 mg/l 96hrs  |
| Toxicity to daphnia and other aquatic invertebrate | Daphnia magna (Water flea)                    | IC50: 1 mg/l 24hrs    |
| Toxicity to algae                                  | Pseudokirchneriella subcapitata (green algae) | EC50: 4.36 mg/l 73hrs |
| Persistence and degradability                      | Biodegradability                              | Readily               |
| Bioaccumulative potential                          | Partition coefficient: n-octanol/water        | log Pow: 2.77 - 3.15  |

**13. DISPOSAL CONSIDERATIONS**

**RECOMMENDATIONS:** The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection, waste disposal legislation and any regional local authority requirements. Empty containers should be disposed of through an approved waste management facility. Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261, ensure conformity to all applicable hazardous waste regulations, consult your local or regional authorities.

**14. TRANSPORT INFORMATION**

**UN NUMBER:** UN1263

**UN PROPER SHIPPING NAME:** PAINT

**TRANSPORT HAZARD CLASS:** 3

**PACKING GROUP:** II

**SPECIAL PRECAUTIONS:** The listed transportation information applies only to ground transport and does not address regulatory variations due to changes in package size, mode of shipment or other regulatory descriptors. This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. It is the responsibility of the shipper and the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material. Local Government regulations and rules should prevail.

**15. REGULATORY INFORMATION****UNITED STATES FEDERAL REGULATIONS:**

**OSHA:** OSHA Hazard Communication Standard 29 CFR 1910.1200

A component(s) of this product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**Toxic Substance Control Act (TSCA):**

All components of this product are listed or are exempt from Listing on the TSCA Inventory.

**EPCRA - Emergency Planning and Community Right-to-Know Act****CERCLA RQ - 40 CFR302.4 (a)****List of Hazardous Substances and Reportable Quantities (RQ)**

| <u>Chemical Name</u>            | <u>CAS Number</u> | <u>RQ</u>          |
|---------------------------------|-------------------|--------------------|
| TERTIARY BUTYL ACETATE          | 540-88-5          | 5,000 lbs.         |
| XYLENE                          | 1330-20-7         | 100 lbs            |
| Xylene Component: ETHYL BENZENE | 100-41-4          | 1,000 lbs.         |
| GLYCOL ETHER EB ACETATE         | 112-07-2          | Glycol Ethers N230 |
| ACETONE                         | 67-64-1           | 5,000 lbs.         |

**SARA Section 311/312 Hazard Category - 40 CFR 370.2**

This product is considered, under applicable definitions, to meet the following categories:

(X) Fire Hazard (X) Acute Health Hazard (X) Chronic Health Hazard

**SARA 313 Components - 40 CFR 372.65**

This product contains the following substances subject to the reporting requirements of Section 313 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and 40 CFR 372:

| <u>Chemical Name</u>            | <u>CAS Number</u> |
|---------------------------------|-------------------|
| XYLENE                          | 1330-20-7         |
| Xylene Component: ETHYL BENZENE | 100-41-4          |
| GLYCOL ETHER EB ACETATE         | 112-07-2 N230     |

**STATE REGULATIONS:****California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

| <b><u>Chemical Name</u></b>     | <b><u>CAS Number</u></b> |
|---------------------------------|--------------------------|
| TITANIUM DIOXIDE                | 13463-67-7               |
| XYLENE                          | 1330-20-7                |
| Xylene Component: ETHYL BENZENE | 100-41-4                 |
| GLYCOL ETHER EB ACETATE         | 112-07-2                 |
| ACETONE                         | 67-64-1                  |

**New Jersey Right-To-Know Component Information**

| <b><u>Chemical Name</u></b>     | <b><u>CAS Number</u></b> |
|---------------------------------|--------------------------|
| TERTIARY BUTYL ACETATE          | 540-88-5                 |
| TITANIUM DIOXIDE                | 13463-67-7               |
| XYLENE                          | 1330-20-7                |
| Xylene Component: ETHYL BENZENE | 100-41-4                 |
| METHYL AMYL KETONE              | 110-43-0                 |
| DIACETONE ALCOHOL               | 123-42-2                 |
| DIMETHYL CARBONATE              | 616-38-6                 |
| PARACHLOROBENZOTRIFLUORIDE      | 98-56-6                  |
| GLYCOL ETHER EB ACETATE         | 112-07-2                 |
| ACETONE                         | 67-64-1                  |

**Pennsylvania Right-To-Know Component Information**

| <b><u>Chemical Name</u></b>     | <b><u>CAS Number</u></b> |
|---------------------------------|--------------------------|
| TERTIARY BUTYL ACETATE          | 540-88-5                 |
| TITANIUM DIOXIDE                | 13463-67-7               |
| XYLENE                          | 1330-20-7                |
| Xylene Component: ETHYL BENZENE | 100-41-4                 |
| METHYL AMYL KETONE              | 110-43-0                 |
| DIACETONE ALCOHOL               | 123-42-2                 |
| DIMETHYL CARBONATE              | 616-38-6                 |
| PARACHLOROBENZOTRIFLUORIDE      | 98-56-6                  |
| GLYCOL ETHER EB ACETATE         | 112-07-2                 |
| ACETONE                         | 67-64-1                  |


**Massachusetts Right-To-Know Component Information**

| <b><u>Chemical Name</u></b>     | <b><u>CAS Number</u></b> |
|---------------------------------|--------------------------|
| TERTIARY BUTYL ACETATE          | 540-88-5                 |
| TITANIUM DIOXIDE                | 13463-67-7               |
| XYLENE                          | 1330-20-7                |
| Xylene Component: ETHYL BENZENE | 100-41-4                 |
| METHYL AMYL KETONE              | 110-43-0                 |
| DIACETONE ALCOHOL               | 123-42-2                 |
| DIMETHYL CARBONATE              | 616-38-6                 |
| PARACHLOROBENZOTRIFLUORIDE      | 98-56-6                  |
| GLYCOL ETHER EB ACETATE         | 112-07-2                 |
| ACETONE                         | 67-64-1                  |

**16. OTHER INFORMATION**

| <b>HMIS RATING</b>          |          |
|-----------------------------|----------|
| <b>Health:</b>              | <b>3</b> |
| <b>Flammability:</b>        | <b>3</b> |
| <b>Personal Hazard:</b>     | <b>1</b> |
| <b>Personal Protection:</b> | <b>J</b> |

0 = not significant, 1 = Slight, 2 = Moderate, 3 = High, 4 = Extreme, \* = Chronic

**NFPA CODES**

DISCLAIMER: The information and recommendations set forth herein are presented in good faith and believed to be correct as of this date. The Eastwood Company makes no representation, warranty or guarantee as to the completeness or accuracy thereof. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

DATE ISSUED: 5/25/2015  
Version No.: 51540-1