

SAFETY DATA SHEET

Prepared according to USA OSHA Hazcom 2012 / Canada WHMIS 2015



Date Prepared : 07/22/2015

SDS No : 51653Z Part B_ENG

Date Revised : 12/08/2016

Revision No : 2

Eastwood 2K Self Leveling Seam Sealer 51653 Z Part B

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name : Eastwood 2K Self Leveling Seam Sealer 51653 Z Part B
Product Description : Part B Epoxy Seam Sealer, 125 ml / 4.23 fl oz US
General Use : Epoxy adhesive / sealant
Product Stock/Code : 51653 Z (Kit: 250 ml / 8.45 fl oz US)
Chemical Family : Mercaptan
Molecular Formula : Mixture / Mélange

Manufacturer / Supplier

The Easthill Group
Dba The Eastwood Company
263 Shoemaker Road, Pottstown, PA 19464
USA & Canada: 800-343-9353
Outside USA: (610) 323-2200
www.eastwood.com

Emergency Telephone Numbers (24 hour)

CHEMTREC : (800) 424-9300

2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

The classification and label elements stated below were prepared in accordance with the USA OSHA Hazard Communication Standard (29 CFR 1910.1200; Hazcom 2012) and the Canadian WHMIS regulations (Hazardous Products Regulations; WHMIS 2015). This information may be different from the actual product label information for labels that are regulated by other agencies.

Health hazards:

Skin Corrosion, Category 1C
Serious Eye Damage, Category 1
Specific Target Organ Toxicity - Single Exposure, Category 3 (Respiratory Tract Irritation)

Label elements

Hazardous components for labelling:

Mercaptan terminated polymer, 2,4,6-Tris(dimethylaminomethyl) phenol and Bis(dimethylaminomethyl) phenol.



Corrosion



Exclamation
mark

Signal Word: DANGER

Hazard statement(s)

H314: Causes severe skin burns and eye damage.
H335: May cause respiratory irritation.

Precautionary statement(s)**Prevention:**

P264: Wash hands thoroughly after handling.
P280: Wear protective gloves and eye protection.
P261: Avoid breathing vapours.
P271: Use only outdoors or in a well-ventilated area.

Response:

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P363: Wash contaminated clothing before reuse.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310: Immediately call a POISON CENTER or doctor/physician.
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P312: Call a POISON CENTER or doctor/physician if you feel unwell.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.
P405: Store locked up.

Disposal:

P501: Dispose of contents/container in accordance with applicable local, regional and/or national regulations.

Hazards Not Otherwise Classified: No data available.

Emergency Overview

Immediate concerns: Causes eye damage. Prolonged skin contact causes burns. May cause respiratory irritation. Strong, offensive odor. Vapors may have a strong offensive odor which may cause headaches, nausea and vomiting.

Comments: See sections 9 and 10 for more detailed information on physicochemical effects.

See section 11 for more detailed information on health effects.

See sections 12 for more detailed information on environmental effects.

The actual container label may not include the above label elements. The labeling shown above applies to products used solely for industrial / professional use.

Consumer products should be labeled in accordance with the Canadian Consumer Chemicals and Containers Regulations and US Consumer Product Safety Commission regulations. Consumer product labeling takes precedence over Canadian WHMIS 2015 and OSHA Hazcom 2012 Hazard Communication labeling.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS number
Mercaptan terminated polymer	89 - 93	101359-87-9
2,4,6-Tris(dimethylaminomethyl) phenol	7.8 - 8.6	90-72-2
Bis(dimethylaminomethyl) phenol	0.8 - 1	71074-89-0

Comments: There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the product and hence require reporting in this section.

4. FIRST AID MEASURES

Eye Contact: In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Get medical attention immediately.

Skin Contact: Immediately flush skin with plenty of water. Remove clothing. Get medical attention immediately. Wash clothing separately before reuse.

Ingestion: Do not induce vomiting. Rinse mouth with water. Give 1 to 2 glasses of water to drink. Never give anything by mouth to an unconscious person. Get medical attention.

Inhalation: No specific treatment is necessary since this material is not likely to be hazardous by inhalation. If you experience eye watering, headaches or dizziness, increase fresh air or leave the area.

Signs and Symptoms of Overexposure

Eye Contact: Corrosive. Will cause eye burns and permanent tissue damage.

Skin Contact: Contact causes severe skin irritation and possible burns.

Ingestion: Corrosive and may cause severe and permanent damage to mouth, throat and stomach.

Inhalation: May be irritating to the eyes, nose, throat, and lungs. Prolonged or excessive inhalation may cause respiratory tract irritation. Vapors may have a strong offensive odor which may cause headaches, nausea and vomiting.

Additional Information: No data available.

5. FIRE FIGHTING MEASURES

Flammable Properties: Will burn if involved in a fire.

Extinguishing Media: Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material. Use an extinguishing agent suitable for the surrounding fire.

Hazardous Combustion Products: During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

Fire Fighting Procedures: Containers can build up pressure if exposed to heat (fire).

Fire Fighting Equipment: As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.

Sensitivity to Static Discharge: Product is not sensitive to static discharge.

Sensitivity to Mechanical Impact: Product is not sensitive to mechanical impact.

6. ACCIDENTAL RELEASE MEASURES

Small Spill: Ensure adequate ventilation. Cover spill area with suitable absorbent material (e.g., sand, earth, sawdust, vermiculite, Oil-Dri, Kitty Litter, etc.). Sweep up material being careful not to raise dust. Place in an appropriate disposal container and seal tightly. Avoid contact with eyes, skin, and clothing.

Environmental Precautions

Water Spill: Do not flush to sewer.

Land Spill: Avoid runoff into storm sewers and ditches which lead to waterways.

Special Protective Equipment: Clean up spills immediately, observing precautions in Protective Equipment section 8.

7. HANDLING AND STORAGE

General Procedures: Ensure thorough ventilation of stores and work areas.

Handling: Use only with adequate ventilation. Avoid breathing vapour. Avoid contact with eyes, skin, and clothing. Wear recommended personal protective equipment. After handling, always wash hands thoroughly with

soap and water.

Storage: Store away from heat, sparks, open flames, strong oxidizing agents and direct sunlight. Protect from physical damage. Keep containers tightly closed, when not in use. Store in a cool place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

OSHA / WHMIS 2015 HAZARDOUS COMPONENTS				
		Occupational Exposure Limits		
Chemical Name	Type		ppm	mg/m ³
Mercaptan terminated polymer	-	-	-- [1]	-- [1]
2,4,6-Tris(dimethylaminomethyl) phenol	USA OEL	-	-- [2]	-- [2]
Bis(dimethylaminomethyl) phenol	USA OEL	-	-- [2]	-- [2]
Footnotes:				
1. This material does not have established exposure limits.				
2. This material does not have established exposure limits in the USA under OSHA, NIOSH, ACGIH.				

Engineering Controls: Good general ventilation should be sufficient to control airborne levels.

Personal Protective Equipment

Eyes and Face: Wear safety glasses with side shields (or goggles). Contact lenses should not be worn when working with this product. Eye wash fountains should be readily available to areas of use and handling.

Skin Contact: Wear chemical resistant gloves.

Respiratory: In case of insufficient ventilation, wear suitable respiratory equipment. NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Protective Clothing: Wear protective clothing as necessary to prevent contact.

Work Hygienic Practices: Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Promptly remove soiled clothing/wash thoroughly before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	: Liquid
Odor	: Mercaptan odor, stench
Odor Threshold	: No data available.
Appearance	: Viscous liquid
Color	: Clear
pH	: No data available.
% Volatiles	: < 0.2% w/w
Flash Point and Method	: > 124 °C Closed Cup
Flammable Limits	: No data available.
Autoignition Temperature	: No data available.
Vapor Pressure	: No data available.
Vapor Density	: No data available.

Eastwood 2K Self Leveling Seam Sealer 51653 Z Part B

Boiling Point	: No data available.
Freezing Point	: No data available.
Melting Point	: Not Applicable
Solubility in Water	: Practically insoluble
Evaporation Rate (n-butyl acetate = 1)	: No data available.
Density	: 1.14±0.02g/ml at 20°C
Viscosity	: 10000 to 20000 cps at 20°C
VOC Content	: < 2.5 g/l (< 0.2% w/w)
Oxidizing Properties	: None

Comments:

VOC Compliance Statement

Part B VOC Content:	Less Exempts: < 2.5 g/l (< 0.021 lb/gal) Total Material: < 2.5 g/l (< 0.021 lb/gal)
Part B Density:	1.14 ± 0.02 g/ml
Part B Total Volatiles:	< 0.2 % w/w
Part B Exempt Content:	0 % w/w; 0% v/v

VOC Regulation:	CARB-California, OTC state, Canada proposed Consumer Product Regulations
Coating Category:	Sealant or Caulking Compound, Chemically Curing, non-aerosol
Mixed Kit VOC Content:	< 0.4 % w/w Less Exempts: < 5.0 g/l (< 0.04 lb/gal) Total Material: < 5.0 g/l (< 0.04 lb/gal)

The product VOC content meets the current 3% w/w limit under the CARB Consumer Product Regulations for Sealant or Caulking Compound, Chemically Curing, non-aerosol.
50 State compliant.

Note: In California this product is exempt under Adhesives and Sealants district rules (meets small container exemption - packaged in ≤ 475 ml (16 fl oz) cartridges) but is covered by the CARB Consumer Product Regulation.

10. STABILITY AND REACTIVITY

Reactive Hazard : No

Hazardous Polymerization: Not expected to occur.

Stability: Stable.

Conditions to Avoid: Keep away from flames and incompatible materials. Keep away from flames and any object that sparks.

Possibility of Hazardous Reactions: No data available.

Hazardous Decomposition Products: By fire and high heat: Carbon monoxide, Carbon dioxide, Oxides of nitrogen and other undetermined compounds.

Incompatible Materials: Oxidizing materials.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Eastwood 2K Self Leveling Seam Sealer 51653 Z Part B

Chemical Name	Oral LD ₅₀ mg/kg (rat)	Dermal LD ₅₀ mg/kg (rabbit)	Inhalation LC ₅₀ mg/l
Mercaptan terminated polymer	> 2000 Based on similar compounds.	> 2000 Based on similar compounds.	> 10(rat;4h) Based on similar compounds.
2,4,6-Tris(dimethylaminomethyl) phenol	1200, 2500, 2169, 1673	1400(rbt), 1280(rat)	>0.5(rat;1h)
Bis(dimethylaminomethyl) phenol	No data available.	No data available.	No data available.

Acute Toxicity - Dermal LD₅₀: Based on available ingredient data, the classification criteria for Acute Dermal Toxicity are not met for this mixture. The calculated ATE is >2000 mg/kg. Slightly toxic. May be harmful in contact with skin.

Acute Toxicity - Oral LD₅₀: Based on available ingredient data, the classification criteria for Acute Oral Toxicity are not met for this mixture. The calculated ATE is >2000 mg/kg. Slightly toxic. May be harmful if swallowed.

Acute Toxicity - Inhalation LC₅₀: Based on available ingredient data, the classification criteria for Acute Toxicity - inhalation are not met for this mixture. The calculated ATE is >20 mg/l/4h (vapours). An estimate based on component information. Vapors may have a strong offensive odor which may cause headaches, nausea and vomiting.

Notes: < 5% of the mixture consists of an ingredient or ingredients of unknown acute toxicity.
No additional toxicology information is available for this product itself. (See Component Toxicity Information).

Primary Routes of Entry:

Eye contact. Skin contact. Inhalation.

Skin Irritation / Corrosion: Contains: 2,4,6-Tris(dimethylaminomethyl) phenol and Bis(dimethylaminomethyl) phenol. The mixture is classified as: Skin Corrosive, category 1, based on summation of ingredient data (>5% ingredients classified as skin corrosive, category 1). Corrosive, causes permanent skin damage (scarring).

Eye Irritation / Serious Eye Damage: Contains: 2,4,6-Tris(dimethylaminomethyl) phenol and Bis(dimethylaminomethyl) phenol. The mixture is classified as: Eye Damage, category 1, based on summation of ingredient data (> 3% ingredients classified as skin and/or eye category 1). Corrosive. Will cause eye burns and permanent tissue damage.

Respiratory / Skin Sensitizer: Based on available data, the classification criteria for skin/respiratory sensitization are not met for this mixture (< 0.1% ingredients classified as a skin sensitizer, category 1 or sub-category 1A and < 1.0% ingredients classified as a skin/respiratory sensitizer, sub-category 1B).

Germ Cell Mutagenicity: Based on available data, the classification criteria for Germ Cell Mutagenicity are not met for this mixture (< 0.1% ingredients classified as Germ Cell Mutagen, category 1A or 1B and < 1.0% ingredients classified as Germ Cell Mutagen, category 2).

Carcinogenicity

Chemical Name	NTP status	IARC status	OSHA status	Other
Mercaptan terminated polymer	--	--	--	--
2,4,6-Tris(dimethylaminomethyl) phenol	--	--	--	--
Bis(dimethylaminomethyl) phenol	--	--	--	--

Notes: Based on available data, the classification criteria for Carcinogenicity are not met for this mixture (< 0.1% ingredients classified as a Carcinogen, category 1 or 2).

Reproductive Toxicity: Based on available data, the classification criteria for Reproductive Toxicity are not met for this mixture (< 0.1% ingredients classified as Reproductive Toxicity, category 1 or 2).

Specific Target Organ Toxicity - Single Exposure: Contains: Mercaptan terminated polymer. The mixture is classified as: Specific Target Organ Toxicity - Single Exposure, category 3, based on summation of ingredient

Eastwood 2K Self Leveling Seam Sealer 51653 Z Part B

data using the applicable cut-off/concentration limits ($\geq 20\%$ summation of all ingredients classified as Specific Target Organ Toxicity - Single Exposure, category 3). May be irritating to the eyes, nose, throat, and lungs. Prolonged or excessive inhalation may cause respiratory tract irritation. Vapors may have a strong offensive odor which may cause headaches, nausea and vomiting.

Specific Target Organ Toxicity - Repeated Exposure: Based on available data, the classification criteria for Specific Target Organ Toxicity - Repeated Exposure are not met for this mixture ($< 1.0\%$ ingredients classified as Specific Target Organ Toxicity - Repeated Exposure, category 1 or 2).

Aspiration Hazard: Based on available data, the classification criteria for Aspiration Hazard are not met for this mixture ($< 10\%$ ingredients classified as an Aspiration Hazard, category 1 and/or mixture viscosity $> 20.5 \text{ mm}^2/\text{s}$ at 40°C).

12. ECOLOGICAL INFORMATION

Environmental Data: No data available.

Ecotoxicological Information: No data available.

Bioaccumulation/Accumulation: No data available.

Distribution: No data available.

Aquatic Toxicity (Acute): No data available.

Chemical Fate Information: No data available.

13. DISPOSAL CONSIDERATIONS

Disposal Method: Comply with applicable local, state or international regulations concerning solid or hazardous waste disposal and/or container disposal. Do not discharge substance/product into sewer system.

Product Disposal: Empty containers retain product residue; observe all precautions for product. Decontaminate containers prior to disposal.

14. TRANSPORT INFORMATION

DOT (Department of Transportation)

Proper Shipping Name : POLYAMINES, LIQUID, CORROSIVE, N.O.S.

Technical Name : 2,4,6-Tris(dimethylaminomethyl) phenol and Bis(dimethylaminomethyl) phenol

Primary Hazard Class/Division: 8

UN/NA Number : 2735

Packing Group : III

Marine Pollutant : No

Other Shipping Information:

For products with an inner packaging $< 5.0 \text{ L}$, this product may be shipped as a Limited Quantity.

Vessel (IMO/IMDG)

Shipping Name : POLYAMINES, LIQUID, CORROSIVE, N.O.S.

Technical Name : 2,4,6-Tris(dimethylaminomethyl) phenol and Bis(dimethylaminomethyl) phenol

UN/NA Number : 2735

Primary Hazard Class/Division: 8

Packing Group : III

Marine Pollutant : No

Note: For products with an inner packaging < 5.0 L, this product may be shipped as a Limited Quantity.

Canadian Transportation of Dangerous Goods Regulations

Shipping Name : POLYAMINES, LIQUID, CORROSIVE, N.O.S.

Technical Name : 2,4,6-Tris(dimethylaminomethyl) phenol and Bis(dimethylaminomethyl) phenol

UN/NA Number : 2735

Primary Hazard Class/Division: 8

Packing Group : III

TDG Note:

With an inner packaging < 5.0 L, this component may be shipped as a Limited Quantity as per TDG Section 1.17.

15. REGULATORY INFORMATION

UNITED STATES

SARA Section 311/312 Hazard Categories

Fire Hazard : No

Sudden Release of Pressure : No

Reactive Hazard : No

Product Acute Toxicity : Yes

Product Chronic Toxicity : No

EPCRA Section 313 Toxic Chemicals:

This product does not contain any listed toxic chemicals that exceed the threshold reporting levels established by SARA Title III, Section 313.

EPCRA Section 302 Extremely Hazardous Substances

EPCRA Status:

This product contains no listed extremely hazardous substances that are subject to the reporting requirements of SARA Title III, Section 302.

CERCLA Hazardous Substances and Reportable Quantities (RQ)

CERCLA Status:

This product contains no CERCLA listed hazardous substances.

TSCA (The Toxic Substances Control Act)

TSCA Status:

All components are included or are otherwise exempt from inclusion on this inventory.

CAA 112(b) - Hazardous Air Pollutants

CAA 112(r) - List of Substances for Accidental Release Prevention:

This product contains no chemicals subject to CAA 112(b) or CAA 112(r).

California Proposition 65:

This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive harm.

OSHA Hazard Communication Standard (29 CFR 1910.1200):

Eastwood 2K Self Leveling Seam Sealer 51653 Z Part B

OSHA Status: Hazardous Product (See Section 2 for details).

This product has been classified in accordance with the hazard criteria of the USA OSHA Hazard Communication Standard (29CFR 1910.1200) and the Safety Data Sheet contains all the information required by the OSHA Hazard Communication Standard (HazCom 2012).

CANADA

WHMIS Hazard Symbol and Classification

See Section 2 for details.

WHMIS Regulatory Status:

This product has been classified in accordance with the hazard criteria of the Canadian Hazardous Products Regulations and the Safety Data Sheet contains all the information required by the Hazardous Products Regulations (WHMIS 2015).

WHMIS Classification:

WHMIS 2015 (Canada) Status: Hazardous Product (See Section 2 for details).

CEPA - National Pollutant Release Inventory (NPRI):

This product contains no chemicals subject to CEPA - NPRI.

Domestic Substances List (DSL) / Non-Domestic Substances List (NDSL):

All components are included or are otherwise exempt from inclusion on this inventory.

Comments VOC Content -- See section 9.

16. OTHER INFORMATION

Reason for Issue: NEW

Prepared By : Regulatory Compliance / Conformité réglementaire **Date Revised:** 12/08/2016


Information Contact: 800-345-1178

Revision Summary: This MSDS replaces the 04/26/2016 MSDS. Revised: **Section 2:** Hazards Not Otherwise Classified, Emergency Overview - Immediate concerns Hazards Not Otherwise Classified. **Section 4:** Eye Contact, Signs and Symptoms of Overexposure (Ingestion, Skin Contact), Skin Contact. **Section 11:** Specific Target Organ Toxicity - Repeated Exposure, , Skin Irritation / Corrosion. **Section 14:** DOT (Department of Transportation) (Technical Name , Primary Hazard Class/Division, UN/NA Number , Packing Group , Other Shipping Information), Packing Group , Primary Hazard Class/Division, Technical Name , UN/NA Number , Shipping Name , Vessel (IMO/IMDG) (Technical Name , Primary Hazard Class/Division, Packing Group , UN/NA Number , Note), TDG Note. **Section 15:** Comments. **Section 16:** Comments, General Statements, HMIS RATING - HEALTH Manufacturer Supplemental Notes, NFPA CODES - HEALTH.

HMIS RATING

HEALTH		3
FLAMMABILITY		1
PHYSICAL HAZARD		0
PERSONAL PROTECTION		B

NFPA CODES



NFPA 30 / 30B Storage Classification: Combustible Liquid IIIB

Manufacturer Supplemental Notes: None

Data Sources: Not Available

Additional SDS Information:

N/AV Not Available

N/AP Not Applicable

ND Not yet determined

ACGIH American Conference of Governmental Industrial Hygienists

CAA The Clean Air Act

CCCR The Consumer Chemicals and Containers Regulations

CEPA The Canadian Environmental Protection Act

CERCLA Comprehensive Environmental Response, Compensation, and Liability Act

EPCRA The Emergency Planning and Community Right-To-Know Act

IARC International Agency for Research on Cancer

MSHA Mine Safety and Health Administration

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA The Occupational Safety and Health Administration

SARA The Superfund Amendments and Reauthorization Act

WHMIS Workplace Hazardous Materials Information System

General Statements: No data available.

Comments: None

Manufacturer Disclaimer: The information contained herein is based on data considered accurate. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. No responsibility is assumed for personal injury or property damage to vendees or users or third parties, caused by the material. Such vendees or users assume all risks with the use of this material.