

WARNING: Causes skin irritation. Causes serious eye irritation. Wash face, hands and any exposed skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Keep container tightly closed. Do not allow to freeze. Dispose of contents/container to an approved waste treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.



FIRST AID: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation occurs get medical advice/attention. IF ON SKIN: Take off contaminated clothing and wash before reuse. Wash skin with plenty of soap and water. If irritation occurs get medical advice/attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call POISON CENTER/doctor if you feel unwell. IF SWALLOWED: Call POISON CENTER/doctor if you feel unwell. Rinse mouth. Do not induce vomiting.

CONTAINS (CAS#):

2-butoxyethanol (111-76-2), Glycolic acid (79-14-1).

HMS RATINGS:

Health - 3; Flammability - 0; Reactivity - 1. Keep out of reach of children. Read Safety Data Sheet provided.

Only in the Event of a Chemical Emergency Involving A Spill, Leaks, Fire, or Exposure Call Chemtrec Toll Free Day or Night: 1-800-424-9300 International Call Collect: (202) 483-7616



DO THE JOB RIGHT.®

RUST CONVERTER



- Transforms Rust Into a Paintable Surface
- Eliminates Need for Sanding
- Compatible with Most Top Coats

WARNING: Causes skin irritation. Causes serious eye irritation. Keep out of reach of children. See additional precautionary statements on back panel.

Net Contents 1 US Quart / .946 liter

51676ZP

EASTWOOD'S RUST CONVERTER halts residual rust in its tracks and converts the surface to a black protective polymeric coating. This protective coating seals out moisture and can be top coated with most paints. This single component converter can be sprayed or brush applied. One quart covers about 50-75 square feet on a non-porous smooth surface. Irregular or textured surfaces may require more product. **MUST BE TOP COATED.**

DIRECTIONS – READ ALL INSTRUCTIONS BEFORE USING!

SURFACE PREPARATION: Use a wire brush or sandpaper to remove all loose rust and scale. Use Eastwood PRE to remove all residual grease and oils on surface to be treated.

APPLICATION EQUIPMENT: Eastwood Rust Converter can be applied with an HVLP or conventional spray gun. Use a 1.0 to 1.4 nozzle at low pressure for best results. A trigger bottle may also be used – it is recommended that the trigger bottle not be used for any other products or disposed of after use. For brushing, use a common household paint brush or a foam type brush.

APPLICATION: Shake well before using. No dilution or reducing is necessary; this product is most effective right out of the bottle. Do not apply this product to surfaces that are below 50°F. Do not apply this product to painted surfaces, as damage may occur. Using a brush or spray gun, liberally apply Eastwood Rust Converter to corroded surface. In about 20 minutes the surface will turn to a dark finish, then apply a second coat and let cure for 48 hours. Temperatures may alter cure times. After 48 hour cure time, the surface must be top coated with a paint, or for maximum corrosion resistance, recoat with Eastwood Rust Converter, then apply final top coat.

IMPORTANT: DO NOT RETURN UNUSED MATERIAL TO ORIGINAL CONTAINER

Manufactured for The Eastwood Company, 263 Shoemaker Road, Pottstown, PA 19464 1-800-343-9353 www.eastwood.com © Copyright 2019 Eastwood Automotive Group LLC Made in USA

Label #51676ZPL 12/19 Rev 2



Scan for product info