Printing date 05/01/2008 Reviewed on 05/01/2008

# 1 Identification of substance

· Product details

• Trade name: 13003-13023 Clear Aerosol • Article number: 13003, 13013, 13023

· Distributed By: The Easthill Group dba/ The Eastwood Company 263 Shoemaker Road Pottstown, PA 19464

· Information department: USA & Canada: 800-345-1178 Outside USA: 610-323-2200

· Emergency information: 24 HR EMERGENCY CHEMTREC 1-800-424-9300

# 2 Composition/Data on components

- · Chemical characterization
- · Description: Mixture of the substances listed below with nonhazardous additions.

| Dangerous | s components:                   |  |          |
|-----------|---------------------------------|--|----------|
| 67-64-1   | acetone                         | Danger: 🐽 2.6/2<br>Warning: 🕦 3.3/2A, 3.8/3                            | 40 - 60% |
| 74-98-6   | propane                         | Danger: ♠ 2.2/1<br>Warning: ← 2.5/C                                    | 13 - 30% |
| 108-88-3  | toluene                         | Danger: ( 2.6/2; ( 3.10/1, 3.7/2 Warning: ( 3.2/2, 3.3/2A, 3.8/3       | 7 - 10%  |
| 110-19-0  | isobutyl acetate                | Danger: 🚳 2.6/2  | 7 - 10%  |
| 108-10-1  | 4-methylpentan-2-one            | Danger: <b>(b)</b> 2.6/2<br>Warning: <b>(1)</b> 3.1.I/4, 3.3/2A, 3.8/3 | 5 - 7%   |
| 78-93-3   | butanone                        | Danger: • 2.6/2<br>Warning: • 3.3/2A, 3.8/3                            | 1.5 - 5% |
| 108-65-6  | 2-methoxy-1-methylethyl acetate | Warning: 🚸 2.6/3; 🕚 3.3/2A   | 1.5 - 5% |
| 2807-30-9 | 2-(propyloxy)ethanol            | Danger: 💮 3.1.D/3, 3.3/2A<br>Warning: 🌑 2.6/3                          | 1-1.5%   |

# 3 Hazards identification

· Hazard description:





Harmful Extremely flammable

· Information pertaining to particular dangers for man and environment:

The product has to be labelled due to the calculation procedure of international guidelines.

Warning! Pressurized container.

Extremely flammable.

Harmful by inhalation.

Irritating to eyes, respiratory system and skin.

(Contd. on page 2)

Printing date 05/01/2008 Reviewed on 05/01/2008

Trade name: 13003-13023 Clear Aerosol

(Contd. of page 1)

Possible risk of harm to the unborn child.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

91.8 % by mass of the contents are flammable

Keep out of the reach of children.

#### Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

· NFPA ratings (scale 0 - 4)



Health = 2Fire = 4Reactivity = 0

#### · HMIS-ratings (scale 0 - 4)



Health = 2Fire = 4

#### GHS label elements



2.2/1 - Extremely flammable gas.

2.3/1 - Extremely flammable aerosol.



# Warning

3.7/2 - Suspected of damaging fertility or the unborn child.



### Warning

3.1/4 - Harmful if inhaled.

3.2/2 - Causes skin irritation.

3.3/2A - Causes serious eye irritation.

3.8/3 - May cause respiratory irritation.

### · Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Use personal protective equipment as required.

#### · Response:

IF ON SKIN: Wash with plenty of soap and water.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

(Contd. on page 3)

Printing date 05/01/2008 Reviewed on 05/01/2008

Trade name: 13003-13023 Clear Aerosol

(Contd. of page 2)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a POISON CENTER or doctor/physician if you feel unwell.

Specific treatment (see label).

If skin irritation occurs: Get medical advice/attention.

*If eye irritation persists: Get medical advice/attention.* 

Take off contaminated clothing and wash before reuse.

Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

Eliminate all ignition sources if safe to do so.

· Storage:

Store in a well-ventilated place.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight. Do no expose to temperatures exceeding 50°C/122°F.

· Disposal:

Dispose of contents/container in accordance with local/regional/national/international regulations.

### 4 First aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

*In case of unconsciousness place patient stably in side position for transportation.* 

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: If symptoms persist consult doctor.

### 5 Fire fighting measures

- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Protective equipment: Mouth respiratory protective device.

### 6 Accidental release measures

- · Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.
- · Measures for environmental protection: Do not allow to enter sewers/ surface or ground water.
- · Measures for cleaning/collecting:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

USA

(Contd. on page 4)

Printing date 05/01/2008 Reviewed on 05/01/2008

Trade name: 13003-13023 Clear Aerosol

(Contd. of page 3)

# 7 Handling and storage

- · Handling:
- · Information for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about protection against explosions and fires:

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Store away from oxidizing agents.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Do not gas tight seal receptacle.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

# 8 Exposure controls and personal protection

· Additional information about design of technical systems: No further data; see item 7.

|        | onal information about design of technical systems: No further data, see tiem 7. |
|--------|--|
| · Comp | onents with limit values that require monitoring at the workplace:               |
| 67-64  | -1 acetone   |
| PEL    | 2400 mg/m³, 1000 ppm   |
| REL    | 590 mg/m³, 250 ppm   |
| TLV    | Short-term value: 1782 mg/m³, 750 ppm  |
|        | Long-term value: 1188 mg/m³, 500 ppm   |
|        | BEI  |
| 74-98  | -6 propane   |
| PEL    | $18000 \text{ mg/m}^3, 1000 \text{ ppm}$   |
| REL    | $1800 \text{ mg/m}^3, 1000 \text{ ppm}$  |
| TLV    | Varies mg/m³, 1000 ppm   |
| 108-8  | 8-3 toluene  |
| PEL    | Short-term value: C 300; 500* ppm  |
|        | Long-term value: 200 ppm   |
|        | *10-min peak per 8-hr shift  |
| REL    | Short-term value: 560 mg/m³, 150 ppm   |
|        | Long-term value: 375 mg/m³, 100 ppm  |
| TLV    | $75 \text{ mg/m}^3, 20 \text{ ppm}$  |
| 110-1  | 9-0 isobutyl acetate   |
| PEL    | 700 mg/m³, 150 ppm   |
| REL    | 700 mg/m³, 150 ppm   |
| TLV    | 713 mg/m³, 150 ppm   |
|        | (Contd. on page 5)   |

(Contd. on page 5)

Printing date 05/01/2008 Reviewed on 05/01/2008

Trade name: 13003-13023 Clear Aerosol

|        | (Contd. of page                                       |
|--------|---|
| 108-10 | 0-1 4-methylpentan-2-one                              |
| PEL    | 410 mg/m³, 100 ppm                                    |
| REL    | Short-term value: 300 mg/m³, 75 ppm                   |
|        | Long-term value: 205 mg/m³, 50 ppm                    |
| TLV    | Short-term value: 307 mg/m³, 75 ppm                   |
|        | Long-term value: (205) NIC-123 mg/m³, (50) NIC-30 ppm |
|        | BEI;NIC-A3  |
| 78-93- | 3 butanone  |
| PEL    | 590 mg/m³, 200 ppm                                    |
| REL    | Short-term value: 885 mg/m³, 300 ppm                  |
|        | Long-term value: 590 mg/m³, 200 ppm                   |
| TLV    | Short-term value: 885 mg/m³, 300 ppm                  |
|        | Long-term value: 590 mg/m³, 200 ppm                   |
|        | BEI   |
| 108-65 | 5-6 2-methoxy-1-methylethyl acetate                   |
| WEEL   | 50 ppm  |

- · Additional information: The lists that were valid during the creation were used as basis.
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



### Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

(Contd. of page 5)

# Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 05/01/2008 Reviewed on 05/01/2008

Trade name: 13003-13023 Clear Aerosol

· Eye protection:

· General Information



Tightly sealed goggles

# 9 Physical and chemical properties

| Form:<br>Color:<br>Odor:  | Aerosol<br>According to product specification<br>Characteristic |
|---|---|
| · Change in condition<br>Melting point/Melting range:<br>Boiling point/Boiling range: |   |
| · Flash point:  | < -17°C (< 1°F)   |
| · Ignition temperature:   | 405°C (761°F)   |
| · Auto igniting:  | Product is not selfigniting.                                    |
| · Danger of explosion:  | In use, may form flammable/explosive vapour-air mixture.        |
| · Explosion limits:<br>Lower:<br>Upper:   | 1.7 Vol %<br>13.0 Vol %   |
| · Vapor pressure at 20°C (68°F):  | 8300 hPa (6226 mm Hg)   |
| · Density at 20°C (68°F):   | 0.753 g/cm <sup>3</sup>   |

# 10 Stability and reactivity

· Solubility in / Miscibility with

Water:

· Solvent content: Organic solvents:

· Solids content:

**VOC** content:

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Not miscible or difficult to mix.

91.8 %

51.6 %

8.2 %

388.0 g/l / 3.24 lb/gl

- · Dangerous reactions No dangerous reactions known.
- · Dangerous products of decomposition:

Nitrogen oxides

Hydrocarbons

Carbon monoxide and carbon dioxide

. . . .

Printing date 05/01/2008 Reviewed on 05/01/2008

Trade name: 13003-13023 Clear Aerosol

(Contd. of page 6)

# 11 Toxicological information

- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

| 108 | -88- | 3 to | luene |
|-----|------|------|-------|
|     |      |      |       |

| Oral       | LD50        | 5000 mg/kg (rat)     |
|------------|-------------|----------------------|
| Dermal     | <i>LD50</i> | 12124 mg/kg (rabbit) |
| Inhalative | LC50/4 h    | 5320 mg/l (mouse)    |

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful Irritant

# 12 Ecological information

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

# 13 Disposal considerations

- · Product:
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

### 14 Transport information

· DOT regulations:



· Hazard class:· Identification number:UN1950

· Packing group:

· Proper shipping name (technical name): AEROSOLS, flammable

(Contd. on page 8)

Printing date 05/01/2008 Reviewed on 05/01/2008

Trade name: 13003-13023 Clear Aerosol

(Contd. of page 7)

• **Label** 2.1

 $\cdot \textit{Land transport TDG (Canada) and ADR/RID (Europe):} \\$ 



· Hazard class:· UN-Number:2 5F Gases1950

· UN-Number: · Packaging group:

• *Label*: 2.1

• Description of goods: 1950 AEROSOLS

· Maritime transport IMDG:



· IMDG Class: 2.1
 · UN Number: 1950
 · Label 2.1
 · Packaging group: -

EMS Number: F-D,S-U
 Marine pollutant: No

· Propper shipping name: AEROSOLS

· Air transport ICAO-TI and IATA-DGR:



· ICAO/IATA Class: 2.1
 · UN/ID Number: 1950
 · Label 2.1

· Packaging group:

• Propper shipping name: AEROSOLS, flammable

· UN "Model Regulation": UN1950; AEROSOLS; 2.1; -

# 15 Regulations

Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

108-88-3 toluene

108-10-1 4-methylpentan-2-one

78-93-3 butanone

(Contd. on page 9)

USA

# EW #52059Z - Vinyl Coat Clear High Gloss Aerosol Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 05/01/2008 Reviewed on 05/01/2008

Trade name: 13003-13023 Clear Aerosol

| · TSCA (Toxic   | Substances Control Act):   |
|-----------------|--|
| 67-64-1         | acetone  |
| <i>74-98-6</i>  | propane  |
| 108-88-3        | toluene  |
| 110-19-0        | isobutyl acetate   |
| 108-10-1        | 4-methylpentan-2-one   |
| 78-93-3         | butanone   |
| 108-65-6        | 2-methoxy-1-methylethyl acetate  |
| <i>763-69-9</i> | ethyl 3-ethoxypropionate   |
| 2807-30-9       | 2-(propyloxy)ethanol   |
| 104810-48-2     | alpha-3-(3-(2H-Benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-omeghydroxypoly (oxy-ethylen)  |
| 104810-47-1     | alpha-3-(2H-Benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl)-omega-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylen) |
| 111-76-2        | 2-butoxyethanol  |
| 25322-68-3      | Polyethylene glycol  |
| Proposition 6   | 5  |
| · Chemicals kn  | nown to cause cancer:  |
| None of the ir  | ngredients is listed.  |
| · Chemicals kn  | nown to cause reproductive toxicity for females:   |
|                 | ngredients is listed.  |
|                 | nown to cause reproductive toxicity for males:   |
|                 | ngredients is listed.  |
| <u> </u>        | nown to cause developmental toxicity:  |
| 108-88-3 toli   |  |
|                 |  |
| Cancerogenii    | nmental Protection Agency)   |
| 67-64-1 ace     |  |
| 108-88-3 toli   |  |
| 78-93-3 but     |  |
|                 |  |
|                 | ational Agency for Research on Cancer)   |
| 108-88-3 toli   |  |
| 111-76-2 2-b    | utoxyethanol   |
| · NTP (Nation   | al Toxicology Program)   |
| None of the in  | ngredients is listed.  |
| · TLV (Thresh   | old Limit Value established by ACGIH)  |
| 67-64-1 ace     | etone  |
| 108-88-3 toli   | uene   |
| · NIOSH-Ca (    | National Institute for Occupational Safety and Health)   |
| ,               | ngredients is listed.  |
| •               | Occupational Safety & Health Administration)   |
| · บรกล•しน (U    | ссиранонан Зајену & Пеант Антингичноп)   |

Printing date 05/01/2008 Reviewed on 05/01/2008

Trade name: 13003-13023 Clear Aerosol

(Contd. of page 9)

#### · Product related hazard informations:

The product has been classified and marked in accordance with directives on hazardous materials.

#### · Hazard symbols:

Harmful

Extremely flammable

### · Hazard-determining components of labelling:

toluene

#### · Risk phrases:

Extremely flammable.

Harmful by inhalation.

Irritating to eyes, respiratory system and skin.

Possible risk of harm to the unborn child.

#### · Safety phrases:

Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).

Wear suitable protective clothing and gloves.

Use only in well-ventilated areas.

This material and its container must be disposed of as hazardous waste.

# · Special labeling of certain preparations:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

91.8 % by mass of the contents are flammable

Keep out of the reach of children.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing MSDS: Environment protection department.
- · Contact: Steve Gaver
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises Dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Reglement internationale concernent le transport des merchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IICA -