

MSDS Revised 01/01/02 Zone Dry Max

Material Safety Data Sheet Zone Dry Max

Product Name:

Zone Dry

Uses:

For dehumidifying air in enclosed areas

Manufacturer:

Desiccare, Inc. 211 Industrial Drive, Richland, MS

DOT Hazard Class:

N.A.

DOT Shipping Name:

N.A.

Hazardous Ingredient and Health Hazard Information:

A mixture of calcined clay of white and off-white particles with calcium chloride granules.

When used in accordance with the instructions and contents are not removed from the inner package, no masks or special equipment is required.

If handled in bulk, the following applies:

HAZCHEM CODE: 4

0

UN#:

N/A

Class:

N/A

Transport:

Non hazardous

OSHA PEL (ACGIH TLV) for Crystalline Silica 1 mg/m³ (1 mg/m³)
To sample for dust refer to NIOSH Analytical Method 7500 or OSHA method ID 142

ZoneDry Max is considered a low hazard however, avoid ingestion and prolonged and repeated inhalation of dust. Avoid contact with skin and eyes. Wear protective mask.

Precaution When Handling Out of Package

Flammability:

Non-combustible

Other Hazards:

Avoid generating and inhaling dust

Ventilation:

Normally, mechanical ventilation is required

Protective Equipment:

Safety glasses, dust masks

		¥		
				<i>.</i>

First Aid

Eyes:

Flush eyes with water for approximately 15 minutes while holding

Eyelids open occasionally. Seek medical attention if irritation or

Soreness persists.

Inhalation:

Remove from exposure area to fresh air. Seek medical attention if any

symptoms persist.

Skin:

First aid is normally not needed. As a precaution, brush powered material from

the skin and wash with soap and water.

Ingestion:

If swallowed, as a precaution, rinse mouth with water.

Induce vomiting if large amounts are ingested and call a physician

Safe Handling Procedures

Storage:

Transport is not regulated. Keep product dry to avoid deterioration. Protect

containers against physical damage.

Spillage:

Sweep up and wash down residue with water.

Waste Disposal:

Landfill according to local, state, and federal regulations.

Fire Explosion:

Non-combustible.

Extinguishing:

Not applicable

For further information contact:

Desiccare, Inc.

211 Industrial Drive Richland, MS 39218 Phone: 601.932.0405 Fax: 601.932.0442

	•		
1			
		•	
			l.