1. Product and Company Identification

Product number

Product name Water Based Multi-Purpose Adhesive Remover

Effective date 30-Dec-2008
Distributed by The Easthill Group

dba/ The Eastwood Company 263 Shoemaker Road

Pottstown, PA 19464

USA & Canada: 800-345-1178 Outside USA: 610-323-2200 Chem-Trec 800-424-9300

Emergency contact Ch Version # 03

Supersedes date 13-Nov-2007

2. Hazards Identification

Emergency overview FLAMMABLE

CONTENTS UNDER PRESSURE. Aerosol. Pressurized container may explode when

exposed to heat or flame.

Cancer hazard. Irritating to eyes. Prolonged exposure may cause chronic effects.

Potential health effects

Eyes Causes eye irritation.

Skin Prolonged or repeated contact can result in defatting and drying of the skin which may

result in skin irritation and dermatitis (rash).

Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

Prolonged inhalation may be harmful.

Ingestion Exposure by ingestion of an aerosol is unlikely. Ingestion may cause gastrointestinal

irritation, nausea, vomiting and diarrhea. May cause delayed lung damage.

Target organs Central nervous system.

Chronic effects May cause central nervous system disorder (e.g., narcosis involving a loss of

coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage.

May cause delayed lung damage.

3. Composition / Information on Ingredients

Components	CAS#	Percent
d-Limonene	5989-27-5	15 - 20
Diethylene Glycol Monobutyl Ether	112-34-5	10 - 15
n-Methyl-2-Pyrrolidinone	872-50-4	5 - 8
Dimethyl Ether	115-10-6	5 - 8
Polyethylene Glycol Nonylphenol Ether	9016-45-9	5 - 8
Isobutane	75-28-5	5 - 8
Propane	74-98-6	1 - 3
Nitromethane	75-52-5	0.1 - 0.5
Non-hazardous and other components below reportable levels		40 - 60

4. First Aid Measures

First aid procedures

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact

lenses, if present and easy to do. Get medical attention if irritation develops or persists.

Skin contactRemove and isolate contaminated clothing and shoes. Wash off with warm water and soap. Get medical attention if irritation develops or persists. For minor skin contact, avoid

spreading material on unaffected skin.

trade_name MSDS US

EW #52350 Z - Multi Purpose Water Soluble Adhesive Remover

Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth Inhalation

> method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Call a physician if symptoms develop or persist.

Ingestion

Rinse mouth. Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

5. Fire Fighting Measures

Flammable properties

Containers may explode when heated. Vapor or gas may spread to distant ignition

sources and flash back.

Extinguishing media

Suitable extinguishing media

Water fog. Alcohol foam. Dry chemical. Polymer foam. Dry chemical powder. Carbon

dioxide (CO2).

Level 2 Aerosol.

Protection of firefighters

Specific hazards arising from the chemical

Fire may produce irritating, corrosive and/or toxic gases.

Protective equipment and precautions for firefighters

In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Containers should be cooled with water to prevent vapor pressure build up. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

6. Accidental Release Measures

Methods for containment

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable.

Methods for cleaning up

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.

7. Handling and Storage

Handling

Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Do not use if spray button is missing or defective. Use only with adequate ventilation. Do not get this material in contact with eyes. Do not breathe gas/fumes/vapor/spray. Avoid contact with skin. Wear personal protective equipment. Avoid prolonged exposure.

Storage

Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Avoid exposure to long periods of sunlight. Keep in an area equipped with sprinklers. Keep out of the reach of children.

8. Exposure Controls / Personal Protection

Exposure limits

ACGIH

Components	CAS#	TWA	STEL	Ceiling
Diethylene Glycol Mo Ether	nobutyl 112-34-5	20 ppm	Not established	Not established
Isobutane	75-28-5	1000 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established
Nitromethane	75-52-5	20 ppm	Not established	Not established

OSHA

Components	CAS#	TWA	STEL	Ceiling
Diethylene Glycol Monobuty Ether	l 112-34-5	100 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established
Nitromethane	75-52-5	100 ppm	Not established	Not established

trade_name MSDS US Personal protective equipment

Eye / face protectionWear chemical goggles. **Skin protection**Protective gloves.

Respiratory protection When workers are facing concentrations above the exposure limit they must use

appropriate certified respirators.

9. Physical & Chemical Properties

AppearanceCompressed liquefied gas.Boiling point176 °F (80 °C) estimated

Color Light yellow.

Flammability (HOC) 21.1363 kJ/g estimated

Flash back No

Flash point -156 °F (-104.4 °C) estimated

Form Aerosol.

Odor Sweet.
pH 8.93 - 9.93

Physical state Liquid.

Pressure 40 - 50 psig @ 70F

Solubility Partially

Specific gravity 0.8905 estimated

10. Chemical Stability & Reactivity Information

Chemical stability Risk of ignition.

Conditions to avoid Heat, flames and sparks.

Incompatible materials Isocyanates.

Hazardous decomposition products May include oxides of oxides of carbon.

11. Toxicological Information

Acute effects Acute LD50: 5690 mg/kg estimated, Rat, Dermal

Acute LC50: 31 mg/l/4h estimated, Rat, Inhalation

Sensitization Not expected to be hazardous by OSHA criteria.

Carcinogenicity Hazardous by OSHA criteria.

Reproductive effects

Not expected to be hazardous by OSHA criteria.

Teratogenicity

Not expected to be hazardous by OSHA criteria.

12. Ecological Information

Ecotoxicity LC50 2195 mg/L estimated, Fish, 96.00 Hours,

EC50 873 mg/L estimated, Daphnia, 48.00 Hours, IC50 2119 mg/L estimated, Algae, 72.00 Hours,

Components of this product have been identified as having potential environmental

concerns.

13. Disposal Considerations

Waste codes D001: Waste Flammable material with a flash point <140 F

Disposal instructionsContents under pressure. Do not allow this material to drain into sewers/water supplies. If

discarded, this product is considered a RCRA ignitable waste, D001. Dispose in

accordance with all applicable regulations.

trade_name MSDS US

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name Consumer commodity

Hazard class ORM-D Subsidiary hazard class None

Additional information:

Packaging exceptions 156, 306 Packaging non bulk 156, 306 None Packaging bulk

IMDG

Basic shipping requirements:

Proper shipping name **AEROSOLS**

Hazard class 2.1 1950 **UN** number

Additional information:

LTD QTY Packaging exceptions Labels required None



IATA

Basic shipping requirements:

Aerosols, flammable Proper shipping name

2.1 **Hazard class** 1950 **UN** number

Additional information:

Packaging exceptions LTD QTY Labels required 2.1



15. Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

Diethylene Glycol Monobutyl Ether 112-34-5 1.0 % de minimis concentration (applies to R-(OCH2CH2)n-OR', where n = 1,2, or 3,

R=alkyl C7 or less, or R = phenyl or alkyl substituted phenyl, R' = H or alkyl C7 or less, or OR' consisting of carboxylic acid ester, sulfate, phosphate, nitrate, or

sulfonate, Chemical Category N230)

n-Methyl-2-Pyrrolidinone 872-50-4 1.0 % de minimis concentration

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous

chemical

CERCLA (Superfund) reportable quantity

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

Section 302 extremely hazardous substance

Section 311 hazardous chemical Yes

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations

WARNING: This product contains a chemical known to the State of California to cause

birth defects or other reproductive harm.

U.S. - Pennsylvania - RTK (Right to Know) List

Diethylene Glycol Monobutyl Ether 112-34-5 Environmental hazard Dimethyl Ether 115-10-6 Present Isobutane 75-28-5 Present Nitromethane 75-52-5 Present n-Methyl-2-Pyrrolidinone 872-50-4 Present 74-98-6 Propane Present

16. Other Information

HMIS® ratings Health: 1

Flammability: 3 Physical hazard: 0

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our

knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified

in the text.

MSDS sections updated Hazards Identification: Emergency overview

Handling and Storage: Storage

Physical & Chemical Properties: Physical & Chemical Properties Transport Information: Product Shipping Name/Packing Group

Regulatory Information: United States Regulatory Information: State regulations