


Eastwood
Elite

Items #54277

PAINT GUN REGULATOR

INSTRUCTIONS



The **EASTWOOD ELITE PAINT GUN REGULATOR** is constructed with an efficient diaphragm design and features a 0 to 160 PSI Gauge for accuracy. Compact and lightweight, it makes the perfect “on the gun” regulator.

SPECIFICATIONS

- 1/4” MNPT Inlet
- 1/4” FNPT Outlet
- Maximum 160 PSI (11 bar)

SAFETY INFORMATION

The following explanations are displayed in this manual, on the labeling, and on all other information provided with this product:

DANGER

DANGER indicates a hazardous situation which, if not avoided, will result in death or serious injury.

WARNING

WARNING indicates a hazardous situation which, if not avoided, could result in death or serious injury.


CAUTION

CAUTION used with the safety alert symbol, indicates a hazardous situation which, if not avoided, could result in minor or moderate injury.

NOTICE

NOTICE is used to address practices not related to personal injury.

SAFETY INFORMATION



⚠ READ INSTRUCTIONS

- Thoroughly read and understand these product instructions before using this equipment. Failure to follow all warnings can result in tool damage or serious physical injury.
- Keep these product instructions for future reference.



⚠ DANGER

- This device is specifically designed to be used for compressed air ONLY. Use with any other fluid (liquid or gas) is a misapplication and not permitted. Use with certain hazardous liquids or gasses could be harmful to the unit or result in a combustible condition or hazardous external leakage.



⚠ WARNING HEALTH HAZARD!

- Air discharged from this Regulator is not intended for and should never be used as supply air for human consumption.



⚠ CAUTION EXPLOSION HAZARD!

- Do not exceed 90 psi (6.2 bar) of tool inlet pressure. Permanent equipment damage and/or bursting could occur and cause personal injury.

ASSEMBLY

- Wrap a good quality Teflon Sealing Tape (Not Included) around the threads of the Male 1/4" NPT Regulator Inlet and thread into a suitable fitting or air hose.
- Wrap a good quality Teflon Sealing Tape (Not Included) around the threads of the Male 1/4" NPT paint gun or other accessory inlet then thread the Regulator on to it.

INSTALLATION

- The Regulator is designed for installation at the inlet of or as close as possible to any air tools and spray guns to be used.
- Connect the Regulator with the cast-in directional arrow on the underside consistent with the direction of airflow.

NOTE: For best results, one of the Eastwood Air Filter/Regulators and or 2 Stage Air Filter/Desiccant Dryer Systems should be installed before this Regulator.

OPERATION

- Pull upward on Locking Cap until a “snap” is heard.
- Rotate Locking Cap in a Clockwise direction as viewed from the top to increase air pressure setting.
- Rotate Locking Cap in a Counter-Clockwise direction as viewed from the top to decrease air pressure setting.
- Push downward on Locking Cap until a “snap” is heard to lock the setting.

ADDITIONAL ITEMS

- #31733 Rockwood 3/8” NPT Air Filter/Regulator
- #31734 Rockwood 1/2” NPT Air Filter/Regulator
- #31726 Rockwood 3/8” NPT 2 Stage Air Filter/Desiccant Dryer System.
- #31727 Rockwood 1/2” NPT 2 Stage Air Filter/Desiccant Dryer System
- #31521 5 Piece Type-M Air Coupler Set

If you have any questions about the use of this product, please contact

The Eastwood Technical Assistance Service Department: 800.343.9353 >> email: techhelp@eastwood.com

PDF version of this manual is available at eastwood.com

The Eastwood Company 263 Shoemaker Road, Pottstown, PA 19464, USA

800.343.9353 eastwood.com