

**DANGER!** Highly flammable liquid and vapor. Harmful if inhaled. May cause respiratory irritation, drowsiness or dizziness.

**PRECAUTIONS:** Read all warning statements on all labels, for this and any other products to be mixed with it prior to use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and other tools or equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust, fumes, gas, mist, vapors or spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, protective clothing and eye protection/face protection. Wear an appropriate, properly fitted fresh-air supplied respirator (NIOSH-approved TC19 or equivalent) during and after application, and until all organic solvent vapors or spray mists are exhausted, or any time airborne contaminant levels exceed exposure limits indicated on the Safety Data Sheet.

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction, do not use water. Keep container tightly closed. Store locked up, in a cool, well ventilated place. Dispose of unused amounts and empty container with an approved waste disposal facility only, in accordance with all local, regional and national regulations. Avoid release to environment. If spilled, contain material with inert absorbent, in compliance with local, regional and national regulations.

**FIRST AID:** IF ON SKIN (or hair): Wash with plenty of soap and water. Take off immediately all contaminated clothing and wash before reuse. Rinse skin with water or shower. If skin irritation or rash occurs: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Get medical attention. If exposed or concerned: Get medical attention. Call a POISON CENTER, doctor or physician if you feel unwell.

**REFER TO SAFETY DATA SHEET FOR FURTHER SAFETY AND FIRST AID INFORMATION.**  
**FOR PROFESSIONAL USE ONLY. KEEP OUT OF REACH OF CHILDREN AND PETS AT ALL TIMES**

**CONTENTS:** Acrylic Resin, Tertiary Butyl Acetate 540-88-5.

**VOC INFORMATION:** Coatings category: Additive/Component. Actual VOC (as supplied): 0.0 grams/liter (0.0 lbs/gallon). Regulatory VOC (as supplied): 0.0 grams/liter (0.0 lbs/gallon)



**WARNING:**  
**Cancer and Reproductive Harm –**  
**[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)**

**OSHA HMIS Rating**

Health	2
Flammability	3
Personal Hazard	0
Personal Protection	J

**EASTWOOD METALLI-FLOW PAINT ENHANCER** is a specifically designed paint additive for use with Eastwood Single Stage paints to help stabilize metallic and pearl particles, resulting in an even, streak and mottle free finish.

**SURFACE PREP:** Follow the instructions for surface prep from the label of your Eastwood Single Stage Urethane to ensure that you have removed all traces of wax, grease, silicone, oil or other contaminants.

**MIXING:** Thoroughly shake and then stir contents before use. If you do not have the means to shake, stir vigorously for at least 5 minutes to make sure all traces of sediments on the bottom of the can have been re-incorporated back into the fluid of the additive. Eastwood Metalli-Flow is to be mixed with Eastwood Single Stage colors at a 3:1:1 ratio. This means three parts of paint, one part of activator and one part of Eastwood Metalli-Flow.

**CURING:** Follow the instructions for cure time as normal from the label on the Eastwood Single Stage Urethane color. Use of this additive will make the finish of the cured paint appear satin/matte so it is recommended to Clear Coat when using this product.

**WARRANTY:** All recommendations for the use of EASTWOOD products are based on tests and experience believed to be reliable. It is the responsibility of the purchaser to determine the suitability of this product for its intended use. Since the methods of use, conditions of application and the application itself are beyond the manufacturer's and seller's control, product warranty is restricted to replacement of defective materials only. No other warranty, written or oral, is expressed or implied.

**Only in the Event of a Chemical Emergency Involving A Spill, Leaks, Fire, or Exposure Call Chemtrec Toll Free Day or Night: 1-800-424-9300 International Call Collect: (202) 483-7616**

Manufactured for The Eastwood Company 263 Shoemaker Road, Pottstown, PA 19464 1-800-343-9353 [www.eastwood.com](http://www.eastwood.com) © Copyright 2021 Eastwood Automotive Group LLC

Made in the USA Label #58176ZP 7/21 Rev 1

