

**EASTWOOD INTERNAL FRAME COATING PLUS** is a high performance, moisture-cured urethane coating that encapsulates and stops rust from spreading. Internal Frame Coating PLUS does not require a top coat except when exposed to direct sunlight. Internal Frame Coating PLUS may be top coated with most high quality coatings. Apply over bare metal surfaces or rusted areas. Internal Frame Coating PLUS is ideal for any type of rusted metal surface and can withstand temperatures of 350°F.

**DIRECTIONS – READ ALL INSTRUCTIONS BEFORE USING THIS PRODUCT!**

**NOTE: USE ALL PRODUCT IN CAN WITHIN 6 MONTHS**

1. Always wear eye protection and chemical resistant gloves when using.
2. Shake can vigorously for at least 1 minute before and occasionally during use.
3. Insert extension tube into spray nozzle.
4. Insert extension nozzle into frame openings, bolt holes, etc.
5. Depress spray button and apply coating while pulling the extension nozzle back to the opening.
6. Continue in all accessible areas for complete coverage. Internal Frame Coating's viscosity will "creep" into deep pockets and under heavy rust to assure coverage.
7. To clean the extension tube, attach to Eastwood's PRE Painting Prep. A few short bursts will clean out the tube and brass nozzle.

**IMPORTANT: To prevent clogging, after each use, turn can upside down and spray in safe direction for 5 seconds.**

**CONTAINS:** Tert-butyl acetate (CAS #540-88-5), 4,4-Methylenediphenyl diisocyanate (CAS #101-68-8), aluminum powder (stabilized) (CAS #7429-90-5), Diphenylmethanediisocyanate, isomers and homologues (CAS #9016-87-9), Solvent naphtha (petroleum), light arom (CAS #64742-95-6), O-(p-isocyanatobenzyl)phenyl isocyanate (CAS #5873-54-1), N-methyl-2-pyrrolidone (CAS #872-50-4).

**DANGER:** Extremely flammable aerosol.

Contains gas under pressure; may explode

if heated. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause genetic defects. May cause cancer. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure.

**PRECAUTIONARY STATEMENTS:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing, eye protection and face protection. Use only outdoors or in a well-ventilated area. Wash face, hands and any exposed skin thoroughly after handling. In case of inadequate ventilation wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Do not breathe dust, fume, gas, mist, vapors and spray. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 122°F / 50°C. Dispose of contents and container to an approved waste disposal plant. 8.13 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist). May be harmful in contact with skin. Harmful to aquatic life with long lasting effects. Harmful to aquatic life.

**FIRST AID:** IF exposed or concerned: Get medical advice/attention.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice and attention.

**IF ON SKIN:** Wash with plenty of water and soap. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice and attention.

**IF INHALED:** Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor.



**WARNING: Cancer and Reproductive Harm –**  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**Category:** Non-flat coating

**Federal:** OTC does not exceed 1.4 MIR

**KEEP OUT OF THE REACH OF CHILDREN**

Only in the Event of a Chemical Emergency Involving A Spill, Leaks, Fire, or Exposure  
Call Chemtrec Toll Free Day or Night: 1-800-424-9300  
International Call Collect: (202) 483-7616

Manufactured for The Eastwood Company, 263 Shoemaker Road, Pottstown, PA 19464  
1-800-343-9353 [www.eastwood.com](http://www.eastwood.com) © Copyright 2023 Eastwood Automotive Group LLC  
Label #67054ZL Rev 1



**DO THE JOB RIGHT.®**

# INTERNAL FRAME COATING PLUS

**MATTE BLACK FINISH**



- Penetrates Deep Under Heavy Rust
- Prevents Rust From Spreading
- Over 1000 Hours Salt Spray Protection
- Heat Resistant to 350°F

**DANGER:**  
CONTENTS EXTREMELY FLAMMABLE  
AND UNDER PRESSURE. EYE IRRITANT.  
Read Precautions On Rear Panel Before Use.

Net wt. 16 oz. / 453 grams

67054Z