

EASTWOOD RUST ENCAPSULATOR PLUS is a high performance, moisture-cured urethane coating that encapsulates and stops rust from spreading. Rust Encapsulator PLUS does not require a top coat except when exposed to direct sunlight. Rust Encapsulator PLUS may be top coated with most high quality coatings. Apply over bare metal surfaces or rusted areas. Rust Encapsulator PLUS is ideal for any type of rusted metal surface and can withstand temperatures of 350°F.

DIRECTIONS – READ ALL INSTRUCTIONS BEFORE USING THIS PRODUCT!

NOTE: USE ALL PRODUCT IN CAN WITHIN 6 MONTHS

1. Clean loose rust with stiff wire brush before application.
2. Remove dust, oil, grease and contaminants with PRE PAINTING PREP #10041Z or Lacquer thinner.
3. Shake can for 2 minutes after mixing ball rattles freely.
4. Shake intermittently during use.
5. Apply when can and surface temperature is between 50°F and 80°F.
6. Hold can 10" from surface and apply in multiple coats.
7. Allow coating to flash 10 minutes or until tacky between coats.
8. Apply 2nd wet coat and allow to dry 4 hours before top coating.
9. Product can be top coated after 4 hours or up to 24 hours.
10. After 24 hours scuff with Scotch Brite pad for best adhesion.

IMPORTANT: To prevent clogging, after each use, turn can upside down and spray in safe direction for 5 seconds.

CONTAINS: Tert-butyl acetate (CAS #540-88-5), 4,4-Methylenediphenyl diisocyanate (CAS #101-68-8), aluminum powder (stabilized) (CAS #7429-90-5), Diphenylmethanediisocyanate, isomers and homologues (CAS #9016-87-9), Solvent naphtha (petroleum), light arom (CAS #64742-95-6), O-(p-isocyanatobenzyl)phenyl isocyanate (CAS #5873-54-1), N-methyl-2-pyrrolidone (CAS #872-50-4).

DANGER: Extremely flammable aerosol.

Contains gas under pressure; may explode if heated. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause genetic defects. May cause cancer. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure.

PRECAUTIONARY STATEMENTS: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing, eye protection and face protection. Use only outdoors or in a well-ventilated area. Wash face, hands and any exposed skin thoroughly after handling. In case of inadequate ventilation wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Do not breathe dust, fume, gas, mist, vapors and spray. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 122°F / 50°C. Dispose of contents and container to an approved waste disposal plant. 8.13 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist). May be harmful in contact with skin. Harmful to aquatic life with long lasting effects. Harmful to aquatic life.

FIRST AID: IF exposed or concerned: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice and attention.

IF ON SKIN: Wash with plenty of water and soap. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice and attention.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor.



WARNING: Cancer and Reproductive Harm –
www.P65Warnings.ca.gov

Category: Non-flat coating

Federal: OTC does not exceed 1.4 MIR

KEEP OUT OF THE REACH OF CHILDREN

Only in the Event of a Chemical Emergency Involving A Spill, Leaks, Fire, or Exposure
Call Chemtrec Toll Free Day or Night: 1-800-424-9300
International Call Collect: (202) 483-7616

Manufactured for The Eastwood Company, 263 Shoemaker Road, Pottstown, PA 19464
1-800-343-9353 www.eastwood.com © Copyright 2023 Eastwood Automotive Group LLC
Label #67060ZL Rev 1



DO THE JOB RIGHT.®

RUST ENCAPSULATOR® PLUS

MATTE BLACK



- Penetrates Deep Under Heavy Rust
- Prevents Rust From Spreading
- Over 1000 Hours Salt Spray Protection
- Heat Resistant to 350°F

DANGER:
CONTENTS EXTREMELY FLAMMABLE
AND UNDER PRESSURE. EYE IRRITANT.
Read Precautions On Rear Panel Before Use.

Net wt. 16 oz. / 453 grams

67060Z