

EASTWOOD RUBBERIZED UNDERCOATING is a premium sealant with many automotive applications. Can be used for sealing trunk interiors, fender walls, floorboards, etc. It is good on any area where rust could be a problem. Will not chip or crack under normal conditions. Flexible and abrasion resistant. Covers approximately 30 sq. ft. **DO NOT APPLY ON, OR VERY CLOSE TO, ENGINE OR EXHAUST COMPONENTS.**

DIRECTIONS – READ ALL INSTRUCTIONS BEFORE USING THIS PRODUCT!

1. Clean and dry surface thoroughly before application. Remove wax, grease, dirt, etc from the surface.
2. For best results, use when surface is between 70°-90°F (21°-32°C).
3. SHAKE CAN VIGOROUSLY. Apply with an application gun, such as Eastwood's #20441.
4. Attach the application gun or pour into application gun cup.
5. Experiment with different application distances to achieve different textures. Allow 24-48 hours to fully cure.
6. Clean overspray and equipment with mineral spirits, or PRE Painting Prep (#10041Z) immediately after use.
7. Store in a cool, dry place with lid on tightly.

Removal: Soak the surface with mineral spirits, kerosene, or use PRE Painting Prep #10041Z.

DANGER: Combustible liquid. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.

PRECAUTIONS: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not breathe mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. Take off contaminated clothing and wash before reuse. If skin irritation occurs: Get medical advice/attention. If inhaled: Remove person to fresh air. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Call a poison center/doctor. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

CONTAINS (CAS No): Calcium Carbonate (1317-65-3), Toluene (108-88-3), Acetone (67-64-1), Propylene Glycol Monomethyl Ether Acetate (108-65-6), Carbon Black (1333-86-4), Crystalline Silica (14808-60-7), Naphtha (petroleum), hydrotreated light (64742-49-0), Solvent Naphtha (Petroleum), Light Aromatic (64742-95-6).

CAUTION: See Safety Data Sheet for complete safety information. **KEEP OUT OF REACH OF CHILDREN**

Only in the Event of a Chemical Emergency Involving A Spill, Leaks, Fire, or Exposure Call Chemtrec
Toll Free Day or Night: 1-800-424-9300 International Call Collect: (202) 483-7616

Manufactured for The Eastwood Company 263 Shoemaker Road, Pottstown, PA 19464 USA: 1-800-343-9353 Canada: 1-800-820-9042
International: (610) 323-2200 www.eastwood.com © Copyright 2017 Easthill Group, Inc. Made in Canada



DO THE JOB RIGHT.®

RUBBERIZED UNDERCOATING

FOR UNDERBODY PROTECTION

- Protects Your Car From Rust and Corrosion
- Withstands Extreme Conditions
- Reduces Road Noise
- Fast Drying and Flexible

DANGER:
CONTENTS EXTREMELY FLAMMABLE LIQUID AND VAPOR.
Read Precautions On Rear Panel Before Use.

28 fl. oz / 830 ml (788 g)

16008 ZP