

*Eastwood*<sup>®</sup>

DO THE JOB RIGHT.<sup>®</sup>

Item #31879

# COB LED RECHARGEABLE FLOOD LIGHT

## INSTRUCTIONS



The **EASTWOOD COB LED RECHARGEABLE FLOOD LIGHT** utilizes the latest LED technology to achieve the brightest output and most energy efficiency possible. A solid cast aluminum housing with rubber shock resistant protection provides tactical level reliability.

## CONTENTS

- (1) Work Light
- (1) USB Charging Cable
- (1) USB Output Wall Charger

## FEATURES

- Three function Switch:
  - One, Low Illumination
  - Two, High Illumination
  - Three, Off
- 180° rotating stand.
- Power bank 5 Volt, 1 Amp USB output function can charge mobile devices
- Battery power display function: 4 blue LED's indicate charge level
- Durable aluminum housing with rubber coated grips
- 30" USB Charging Cable
- 5 Volt, 1 Amp USB output AC wall charger

## SPECIFICATIONS

- 3.7 Volt, 4400mAh Integral Rechargeable Battery
- 1100 Lumens light output (high), 350 Lumens light output (low)
- 3 hours working time (high), 6 hours working time (low)
- 6 hour charge time
- Moisture resistant to IP-54 rating

# SAFETY INFORMATION

The following explanations are displayed in this manual, on the labeling, and on all other information provided with this product:

## **DANGER**

DANGER indicates a hazardous situation which, if not avoided, will result in death or serious injury.

## **WARNING**


WARNING indicates a hazardous situation which, if not avoided, could result in death or serious injury.

## **CAUTION**

CAUTION used with the safety alert symbol, indicates a hazardous situation which, if not avoided, could result in minor or moderate injury.


## **NOTICE**

NOTICE is used to address practices not related to personal injury.



### **READ INSTRUCTIONS**

- Thoroughly read and understand this manual before using.
- Save for future reference.



### **CAUTION EYE INJURY HAZARD!**

- Do Not allow LED lamps to project directly into eyes.  
Temporary blindness may occur.



### **CAUTION SHOCK HAZARD!**

- Keep metal housing of work light away from live electrical sources.



### **NOTICE**

- Keep work light away from excessive heat sources to avoid damage.

# OPERATION

- Grip Handle/Stand and rotate through 180° to support or hang lamp.
- Depress Switch located at rear of housing once for Low, 2nd for High, 3rd for Off.

# CHARGING

- When the Lamp fails to illuminate and/or the 4 Blue LED's at the rear of the Housing do not illuminate, a charge is required. Note that the number of illuminated LED's will decrease in number as the charge depletes.
  - Plug round terminal of included Cable into rear of Housing.
  - Plug USB end of included Cable into the included Wall Charger or other standard 5 Volt, 1 Amp USB port.
  - Allow 6 hours for full charge.
  - The array of 4 Blue LED's at the rear of the Housing will all illuminate to indicate full charge.
  - Close Charging Port Cover to maintain IP-54 rating.

# POWER BANK FUNCTION

- The 5 Volt, 1 Amp USB output port may be used to charge a mobile device.
  - Fully charge the lamp battery as described in "Charging" section.
  - Plug the cable from your mobile device into the USB port on the rear of the Lamp Housing.

---

**If you have any questions about the use of this product, please contact**

The Eastwood Technical Assistance Service Department: 800.343.9353 >> email: [techhelp@eastwood.com](mailto:techhelp@eastwood.com)

PDF version of this manual is available online >> [eastwood.com/31879manual](http://eastwood.com/31879manual)

The Eastwood Company 263 Shoemaker Road, Pottstown, PA 19464, USA

US and Canada: 800.343.9353 Outside US: 610.718.8335

Fax: 610.323.6268 [eastwood.com](http://eastwood.com)